

AEROSOL GREEN 14110

MSDS Number

BJDSS

National Stock Number

8010-00-721-9483

Product Name

AEROSOL GREEN 14110

Manufacturer

NATIONAL AEROSOL PRODUCTS CO SUB OF GROW GROUP INC

Product Identification

Product ID:AEROSOL GREEN 14110

MSDS Date:01/01/1987

FSC:8010

NIIN:00-721-9483

MSDS Number: BJDSS

Responsible Party

NATIONAL AEROSOL PRODUCTS CO SUB OF GROW GROUP INC

2193 E. 14TH STREET

LOS ANGELES , CA 90021

US

Emergency Phone: 213-627-2668

Info Phone: 213-627-2668

Cage: 59986

Contractor

NATIONAL AEROSOL PRODUCTS CO SUB OF GROW GROUP INC

LOS ANGELES, CA 90021-2843

US

502-361-2536

Cage: 59986

Ingredients

VINYL TOLUENE ALKYD

PIGMENTS AND BINDERS

ALIPHATIC HYDROCARBONS

Fraction By Weight: 26.0%

ACGIH TLV: 400 PPM

CHLORINATED HYDROCARBONS

Fraction By Weight: 34.0%

ACGIH TLV: 200 PPM

ISOBUTANE-PROPANE

Fraction By Weight: 30.0%

ACGIH TLV: 800 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:INGESTION: NAUSEA. EYES: IRRITATION.
INHALATION: ANESTHETIC. AND SKIN: MINOR IRRITATION.
Effects of Overexposure:INGESTION: NAUSEA. EYES: IRRITATION.
INHALATION: ANESTHETIC. AND SKIN: MINOR IRRITATION.

First Aid

First Aid:INGESTION: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION. EYES: FLUSH WITH WATER FOR MINIMUM OF 5 MINUTES.
INHALATION: REMOVE TO FRESH AIR. CALL A PHYSICIAN. GIVE MOUTH-TO-MOUTH RESUCITATION IF BREATHING STOPS. AND SKIN: WASH WITH WATER, SEEK MEDICAL HELP.

Fire Fighting

Flash Point:NR
Extinguishing Media:WATER FOG, STANDARD FOAM, CO2, DRY CHEMICAL AND HALON.
Fire Fighting Procedures:TEMPS >120F MAY CAUSE BURST/VENTING. KEEP CONTAINERS COOL. USE EQUIP/SHIELD TO PROTECT PERSONNEL AGAINST BURST/VENTING CONTAINERS. DO NOT PUNCTURE OR INCINERATE
Unusual Fire/Explosion Hazard:DO NOT USE NEAR OPEN FLAME, FIRE OR WHILE SMOKING.

Accidental Release

Spill Release Procedures:MOP UP, SOAK UP OR WIPE UP IMMEDIATELY. PROVIDE VENTILATION. DISPOSE.

Handling

Handling and Storage Precautions:DO NOT STORE WHERE TEMPERATURE COULD EXCEED 120F.
Other Precautions:USE AND FOLLOW LABEL DIRECTIONS.

Exposure Controls

Respiratory Protection:ADEQUATE VENTILATION IS REQUIRED.
Ventilation:RECOMMENDED. LOCAL EXHAUST IS ADEQUATE.
Protective Gloves:REQUIRED FOR PROLONGED CONTACT.
Eye Protection:SOLVENT RESISTANT.
Other Protective Equipment:NORMAL PROTECTIVE CLOTHING.
Supplemental Safety and Health

Chemical Properties

Vapor Pres:40-50 @70F
Vapor Density:> (AIR=1)
Spec Gravity:0.976 (H2O=1)
Solubility in Water:SLIGHT
Appearance and Odor:PAINT/SOLVENT ODOR.

Stability

Stability Condition to Avoid:DO NOT STORE ABOVE 120 F(49C).

Disposal

Waste Disposal Methods:DO NOT PUNCTURE OR INCINERATE "EMPTY" OR FULL CANS. ONCE SPILLS OR LEAKS ARE CLEANED UP. DISPOSE OF WASTE IN ACCORDANCE WITH GOVERNMENTAL ORDINANCES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.