

## **TT-S-711C**

### **MSDS Number**

BJLDY

### **National Stock Number**

8010-00-281-2077

### **Product Name**

TT-S-711C

### **Manufacturer**

TRIAD PAINT AND CHEMICAL CORP

### **Product Identification**

Product ID:TT-S-711C  
MSDS Date:01/01/1987  
FSC:8010  
NIIN:00-281-2077  
MSDS Number: BJLDY

### **Responsible Party**

TRIAD PAINT AND CHEMICAL CORP.

810 EVERGREEN AVENUE

BROOKLYN , NY 11207

US

Emergency Phone: 718-443-2778

Info Phone: 718-443-2778

Cage: 33151

### **Contractor**

TRIAD PAINT AND CHEMICAL CORP

BROOKLYN, NY 11207-1140

US

201-437-6501

Cage: 33151

### **Ingredients**

PIGMENTS

Fraction By Weight: 6.6%

VEHICLE

Fraction By Weight: 93.4%

SOLVENTS

Fraction By Weight: 62.4%

ACGIH TLV: 100 PPM

### **Hazards**

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO  
Health Hazards Acute and Chronic:VAPORS MIGHT BE IRRITATING TO EYES,  
NOSE & THROAT. POSSIBLE DEFATTING.  
Effects of Overexposure:VAPORS MIGHT BE IRRITATING TO EYES NOSE &

THROAT. REPEATED EXCESSIVE EXPOSURE MAY RESULT IN HEADACHE, DIZZINESS, SLEEPINESS & NAUSEA. POSSIBLE DEFATTING.

## First Aid

First Aid:INHALATION: PROVIDE FRESH AIR & REST. SKIN CONTACT: WASH WITH MILD SOAP & WATER. USE EMOLLIENT CREAM OR LOTION. EYE CONTACT: WASH WITH A GENTLE STREAM OF WATER FOR 10 MINUTES. SEE A DOCTOR.

## Fire Fighting

Flash Point Method:PMCC

Flash Point:105 F/41 C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:FOAM, CO2, DRY CHEMICALS.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED RESPIRATORS. WATER STREAM WILL SPREAD OIL FIRES.

Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE OF HOT METAL SURFACES & OTHER SURFACES OF IGNITION. VAPORS FORM EXPLOSIVE MIXTURE BETWEEN UPPER & LOWER EXPLOSIVE UNITS.

## Accidental Release

Spill Release Procedures:AVOID FLAME & SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. WIPE UP SPILL WITH INERT ABSORBENT(S) & NON-SPARKING TOOLS. SAFELY DISCARD SATURATED ABSORBENT(S). AVOID PROLONGED BREATHING OF VAPORS WHILE CLEANING UP SPILL.

## Handling

Handling and Storage Precautions:AVOID OPEN FLAMES & SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE HEAT.

Other Precautions:DO NOT TAKE INTERNALLY. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. AVOID PROLONG OR REPEATED BREATHING OF VAPORS.

## Exposure Controls

Respiratory Protection:ORGANIC CANNISTER MASK OR AIR PACK IF VENTILATION IS INADEQUATE.

Ventilation:MECHANICAL (GENERAL) WITH APPROVED CLASS D EXPLOSION PROOF MOTOR & SWITCHES.

Protective Gloves:NEOPRENE RUBBER GLOVES

Eye Protection:CHEMICAL SAFETY GOGGLES.

Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:315 TO 382F

Vapor Pres:100 F

Vapor Density:5.0

Spec Gravity:.901

Evaporation Rate & Reference:.12 (N-BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:MAPLE COLORED LIQUID. HYDROCARBON ODOR.

Percent Volatiles by Volume:72

## Stability

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZING AGENTS

Hazardous Decomposition Products:CO, CO2, ACRID FUMES & SMOKE WHEN COMBUSTED.

## Disposal

Waste Disposal Methods:DISPOSAL PROCEDURES MUST COMPLY WITH LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.