

# **EA9446, PART B, ADHESIVE**

# **MSDS Number**

**BJMJD** 

#### **National Stock Number**

8040-01-143-2014

# **Product Name**

EA9446, PART B, ADHESIVE

#### Manufacturer

DEXTER CORP HYSOL DIV

### **Product Identification**

Product ID:EA9446,PART B,ADHESIVE MSDS Date:01/01/1987 FSC:8040 NIIN:01-143-2014 Kit Part:Y

MSDS Number: BJMJD

# **Responsible Party**

DEXTER CORPORATION, HYSOL DIVISION

2850 WILLOW PASS ROAD

PITTSBURG, CA 94565

US

Emergency Phone: 415-687-4201

Info Phone: 415-687-4201

Cage: 79436

# Contractor

DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

312

BAY POINT, CA 94565-3299

US

202-483-7616

Cage: 33564

#### **Ingredients**

**CATALYST** 

Fraction By Weight: 100%

OSHA PELN/K ACGIH TLV: N/K

#### **Hazards**

LD50 LC50 Mixture:N/K

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: DANGER! CAUSES SEVERE EYE BURNS. MAY

CAUSE SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSES.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: EYES: CAUSES SEVERE BURNS. SKIN: MAY CAUSE SENSITIZATION OR OTHER ALLERGIC RESPONSES. INGESTION: N/K

.INHALATION: MAY CAUSE ALLERGIC RESPONSES.

Medical Cond Aggravated by Exposure: N/K



#### First Aid

First Aid:EYES:FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES.GET MEDICAL ATTENTION.SKIN:WASH IMMEDIATELY WITH SOAP AND WATER.DO NOT WASH WITH SOLVENTS.INGESTION/INHALATION:N/K.

# Fire Fighting

Flash Point Method:PMCC Flash Point:255F,124C Lower Limits:N/K Upper Limits:N/K

Extinguishing Media: FOAM, CARBON DIOXIDE.

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS WHEN

FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard: CLASSIFIED BY DOT AS "COMBUSTIBLE".

### **Accidental Release**

Spill Release Procedures: SOAK UP WITH ABSORBENT MATERIAL.

Neutralizing Agent: N/K

# Handling

Handling and Storage Precautions: MIX WITH PART "A" IN SMALL BATCHES OR

EXCESSIVE HEAT MAY BE GENERATED.

Other Precautions: N/K

# **Exposure Controls**

Respiratory Protection: N/K

Ventilation: LOCAL EXHAUST AND MECHANICAL VENTILATION RECOMMENDED.

Protective Gloves: IMPERVIOUS LATEX OR RUBBER. Eye Protection: CHEMICAL SAFETY GOGGLES.

Other Protective Equipment: SPECIAL EYE WASH FOUNTAIN.

Work Hygienic Practices: N/K Supplemental Safety and Health

DISTRIB 1:JOSE, CA 95103 (408-289-0111). ROUTES OF

ENTRY: INHALATION/SKIN/INGESTION .

# **Chemical Properties**

Boiling Pt:B.P. Text:N/K

Melt/Freeze Pt:M.P/F.P Text:N/K Decomp Temp:Decomp Text:N/K Spec Gravity:0.98 (WATER=1) Solubility in Water:INSOLUBLE

Appearance and Odor:TRANSLUCENT DARK AMBER LIQUID WITH AROMATIC ODOR.

# Stability

Stability Indicator/Materials to Avoid:YES

N/K

Stability Condition to Avoid: N/K

Hazardous Decomposition Products: GASES OF NITROGEN, CARBON MONOXIDE AND CARBON DIOXIDE.

#### Disposal

Waste Disposal Methods: DISP MUST BE IAW FEDERAL, STATE, & LOCAL REGULATIONS. COORDINATION W/ SUPPORTING INSTALLATION/MACOM ENVIRONMENTAL COORDINATION PRIOR TO DISP IS RECOMMENDED TO DETERMINE APPROPRIATE DISP METHODS .LA NDFILL AS REGULATED BY ALL GOVERNMENTALAGENCIES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

https://msdsreport.com/msds/BJMJD

