

1775 BAY COUNTRY LATEX SEMI-GLOSS WHITE

MSDS Number

BJTPD

National Stock Number

8010-00F014095

Product Name

1775 BAY COUNTRY LATEX SEMI-GLOSS WHITE

Manufacturer

BRUNING PAINT CO INC

Product Identification

Product ID:1775 BAY COUNTRY LATEX SEMI-GLOSS WHITE

MSDS Date:10/08/1989

FSC:8010

NIIN:00F014095

MSDS Number: BJTPD

Responsible Party

BRUNING PAINT CO INC

601 S HAVEN ST

BALTIMORE , MD 21224-4347

US

Emergency Phone: 301-342-3641

Info Phone: 301-302-342-3636

Cage: EO376

Contractor

KYANIZE PAINT

BALTIMORE, MD 21224

US

800-368-2076

Cage: 85520

Ingredients

ETHYLENE GLYCOL, GLYCOL

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 2.06%

ACGIH TLV: C 127 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

9.7

RTECS: 9999999WG

1.136

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: IRRITATION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

First Aid

First Aid:EYES/SKIN: FLUSH W/LUKE WARM WATER FOR 15 MINS. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING IF REQUIRED. INGESTION: RINSE MOUTH IMMEDIATELY. GIVE EXPOSED INDIVIDUAL 6 TO 8 OUNCES OF LIQUID. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. DON'T INDUCE VOMITING UNLESS ADVISED BY A PHYSICIAN. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TCC
Unusual Fire/Explosion Hazard:CONTAINERS EXPOSED TO HEAT FROM FIRES SHOULD BE COOLED W/WATER TO PREVENT VAPOR PRESSURE BUILD UP WHICH COULD RESULT IN CONTAINER RUPTURE.

Accidental Release

Spill Release Procedures:DON'T FLUSH TO SEWER, WATERSHED, OR WATERWAY.

Handling

Handling and Storage Precautions:KEEP FROM FREEZING. DON'T STORE >120F. DON'T TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN.
Other Precautions:DON'T BREATHE VAPORS OR SPRAY MISTS. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Exposure Controls

Respiratory Protection:IN OUTDOOR OR OPEN AREAS USE NIOSH/MSHA APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY DURING SPRAY APPLICATION. IN RESTRICTED VENTILATION AREA USE A NIOSH/MSHA CHEMICAL MECHANICAL FILTERS. SEE SUPP.
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST IN VOLUME & PATTERN TO KEEP BELOW TLV.
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS THOROUGHLY BEFORE EATING OR USING WASHROOM.
Supplemental Safety and Health
CON'T RESPIRATORY PROTECTION: IN CONFINED AREAS USE NIOSH/MSHA APPROVED AIR LINE TYPE RESPIRATORS OR HOODS. PERCENT VOLATILE BY WEIGHT: 63.74.

Chemical Properties

Boiling Pt:B.P. Text:212-490F
Vapor Pres:17
Vapor Density:>1
Evaporation Rate & Reference:SLOWER THAN BU AC
Percent Volatiles by Volume:73.4

Stability

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS
Stability Condition to Avoid:FREEZING, TEMPS >120F
Hazardous Decomposition Products:CO, CO2, & OXIDES OF NITROGEN

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.