

## **4075 BAY COUNTRY VINYL FLAT WHITE**

### **MSDS Number**

BJTPF

### **National Stock Number**

8010-00F014096

### **Product Name**

4075 BAY COUNTRY VINYL FLAT WHITE

### **Manufacturer**

BRUNING PAINT CO INC

### **Product Identification**

Product ID:4075 BAY COUNTRY VINYL FLAT WHITE

MSDS Date:10/11/1989

FSC:8010

NIIN:00F014096

MSDS Number: BJTPF

### **Responsible Party**

BRUNING PAINT CO INC

601 S HAVEN ST

BALTIMORE , MD 21224-4347

US

Emergency Phone: 301-342-3641

Info Phone: 301-302-342-3636

Cage: EO376

### **Contractor**

KYANIZE PAINT

BALTIMORE, MD 21224

US

800-368-2076

Cage: 85520

### **Ingredients**

SILICA DIOXIDE, CRYSTALLINE QUARTZ, SAND (SUSPECTED HUMAN

CAS: 14808-60-7

RTECS: VV7330000

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

ETHYLENE GLYCOL, GLYCOL

CAS: 107-21-1

RTECS: KW2975000

ACGIH TLV: C 127 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

### **Hazards**

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:EYES: IRRITATION.  
Explanation of Carcinogenicity:SEE INGREDIENTS  
Effects of Overexposure:INHALATION: SILICOSIS. PERMANENT BRAIN &  
NERVOUS SYSTEM DAMAGE.

## First Aid

First Aid:EYES/SKIN: FLUSH W/LUKE WARM WATER FOR 15 MINS. INHALATION:  
REMOVE TO FRESH AIR. RESTORE BREATHING IF REQUIRED. INGESTION:  
RINSE MOUTH IMMEDIATELY. GIVE EXPOSED INDIVIDUAL 6 TO 8 OUNCES OF  
LIQUID. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.  
DON'T INDUCE VOMITING UNLESS ADVISED BY A PHYSICIAN. OBTAIN MEDICAL  
ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point Method:TCC  
Extinguishing Media:CO2, DRY CHEMICAL OR FOAM EXTINGUISHER.  
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. USE WATER TO  
COOL CLOSED CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE  
PREFERABLE.  
Unusual Fire/Explosion Hazard:CONTAINERS EXPOSED TO TO HEAT OR FIRE MAY  
BUILD UP PRESSURE, AUTO IGNITE OR EXPLODE.

## Accidental Release

Spill Release Procedures:DON'T FLUSH TO SEWER, WATERSHED, OR WATERWAY.

## Handling

Handling and Storage Precautions:KEEP FROM FREEZING. DON'T STORE >120F.  
DON'T TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF  
REACH OF CHILDREN.  
Other Precautions:DON'T BREATHE VAPORS OR SPRAY MISTS. INTENTIONAL  
MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE  
HARMFUL OR FATAL.

## Exposure Controls

Respiratory Protection:IN OUTDOOR OR OPEN AREAS USE NIOSH/MSHA APPROVED  
MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF  
OVERSPRAY DURING SPRAY APPLICATION. IN RESTRICTED VENTILATION AREA  
USE A NIOSH/MSHA CHEMICAL MECHANICAL FILTERS. SEE SUPP.  
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST IN VOLUME &  
PATTERN TO KEEP BELOW TLV.  
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE. WASH HANDS THOROUGHLY BEFORE EATING OR USING WASHROOM.  
Supplemental Safety and Health  
CON'T RESPIRATORY PROTECTION: IN CONFINED AREAS USE NIOSH/MSHA APPROVED  
AIR LINE TYPE RESPIRATORS OR HOODS. PRODUCT CONTAINS PIGMENTS WHICH  
MAY BECOME A DUST NUISANCE WHEN REMOVED BY ABRASIVE BLASTING ,  
SANDING OR GRINDING.

## Chemical Properties

Vapor Pres:17  
Vapor Density:>1  
Volatile Org Content %:54  
Evaporation Rate & Reference:SLOWER THAN BU AC  
Percent Volatiles by Volume:70.07

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG ACIDS  
Stability Condition to Avoid:FREEZING, TEMPS >120F  
Hazardous Decomposition Products:CO, CO2, & OXIDES OF NITROGEN

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, &  
FEDERAL REGULATIONS.

---

## Other Information

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.