

TRIM 2

MSDS Number

BJWSL

National Stock Number

6520-00F014306

Product Name

TRIM 2

Manufacturer

HARRY J BOSWORTH COMPANY

Product Identification

Product ID:TRIM 2
MSDS Date:01/01/1987
FSC:6520
NIIN:00F014306
MSDS Number: BJWSL

Responsible Party

HARRY J. BOSWORTH COMPANY
7227 NORTH HAMLIN AVENUE
SKOKIE , IL 60076-9999
Emergency Phone: (312) 679-3400
Info Phone: (312) 679-3400
Cage: FO572

Contractor

HARRY J. BOSWORTH COMPANY
SKOKIE, IL 60076
US
(312) 679-3400
Cage: FO572

Ingredients

ETHYL METHYLCRYLATE POLYMER
Fraction By Weight: 99%

Hazards

LD50 LC50 Mixture:ORAL LD50 (RATS): 6,500-12,800 MG/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES/INGESTION: IRRITATION. SKIN:
RASHES. INHALATION: IRRITATION TO THE RESPIRATORY SYSTEM.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:EYES/INGESTION: IRRITATION. SKIN: RASHES.
INHALATION: IRRITATION TO THE RESPIRATORY SYSTEM.

First Aid

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN:
WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR.
GIVE CPR OR OXYGEN IF NEEDED. INGESTION: INDUCE VOMITING. OBTAIN
MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TCC

Flash Point:111F
Extinguishing Media:CHEMICAL FOAM, CO2, DRY CHEMICALS, WATER FOG
Fire Fighting Procedures:FIGHT FIRES FROM SAFE DISTANCE OR PROTECTED AREAS. COOL CONTAINERS OF MATERIAL EXPOSED TO HEAT W/COLD WATER SPRAY. WEAR NIOSH APPROVED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:SEALED CONTAINERS ELEVATED TO ELEVATED TEMPS. MAY RUPTURE DUE TO POLYMERIZATION. LIQUID VAPORS ARE >AIR & MAY TRAVEL TO IGNITION SOURCE. FLAMMABLE LIQUID.

Accidental Release

Spill Release Procedures:LIQUID: EVACUATE AREA. ELIMINATE IGNITION SOURCES. WEAR PROTECTIVE CLOTHING. DIKE & ABSORB SPILL W/INERT MATERIAL. TRANSFER TO SUITABLECONTAINER FOR DISPOSAL. POWDER: SWEEP UP INTO SUITABLE CONTAINER FOR DISPOSSAL.

Handling

Handling and Storage Precautions:STORE IN AN INERT ATMOSPHERE. MATERIAL HAS STRONG SOLVENT ACTION. CAN SOFTEN PAINT & RUBBER.
Other Precautions:GROUND CONTAINERS WHEN TRANSFERRING LIQUID. ALLOW AIR SPACE TO EXIST INSIDE STORAGE CONTAINERS. AVOID CONTAMINATION W/FOREIGN MATERIALS.

Exposure Controls

Respiratory Protection:USE SELF CONTAINED BREATHING APPARATUS WHEN VAPORS >100PPM.
Ventilation:PROVIDE SUFFICIENT LOCAL EXHAUST VENTILATION TO KEEP
Protective Gloves:IMPERVIOUS, NEOPRENE
Eye Protection:SPLASH PROOF GOGGLES
Other Protective Equipment:EYEWASH, SAFETY SHOWER, COVERALLS & OVERSHOES.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:311F
Vapor Pres:3
Vapor Density:4.91
Spec Gravity:0.899
Appearance and Odor:LIQUID-COLORLESS W/ACRYLIC ODOR OR POWDER-SHADED VERY FINE MESH.

Stability

Stability Indicator/Materials to Avoid:YES
REDUCING & OXIDIZING AGENTS, FOREIGN MATERIALS
Stability Condition to Avoid:HEAT, IGNITION SOURCES,
Conditions to Avoid Polymerization:EXCESSIVE HEAT, INHIBITOR, & INADVERTANT ADDITION OF CATALYST.

Disposal

Waste Disposal Methods:MATERIAL SHOULD NOT BE DRAINED TO SEWERS. INCINERATE LIQUID IN PROPER CONTAINERS. LANDFILL IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. BIOLOGICAL DIGESTION CAN BE CONSIDERED.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.