

## **COVER COAT COMPOUND**

### **MSDS Number**

BJWZF

### **National Stock Number**

5640-00F012520

### **Product Name**

COVER COAT COMPOUND

### **Manufacturer**

UNITED STATES GYPSUM COMPANY

### **Product Identification**

Product ID: COVER COAT COMPOUND

MSDS Date: 09/03/1992

FSC: 5640

NIIN: 00F012520

MSDS Number: BJWZF

### **Responsible Party**

UNITED STATES GYPSUM COMPANY

125 S FRANKLIN ST

CHICAGO , IL 60606-4678

US

Emergency Phone: 312-606-4542

Info Phone: 312-606-4542

Cage: 61357

### **Contractor**

UNITED STATES GYPSUM CO

CHICAGO, IL 60606-4302

US

312-606-4000 (EMERG /4542)

Cage: 61357

### **Ingredients**

CALCIUM CARBONATE, DOMOLITE, LIMESTONE, WHITING

CAS: 1317-65-3

RTECS: EV9580000

OSHA PEL15 MG/CUM (DUST)

ACGIH TLV: 10 MG/CUM (DUST)

WATER

CAS: 7732-18-5

RTECS: ZC0110000

SILICA, MICA, MUSCOVITE

CAS: 12001-26-2

RTECS: VV8760000

OSHA PEL20 MPPCF

ACGIH TLV: 3 MG/M3 RDUST; 9293

TALC (POWDER), (ASBESTOS FREE), TALCUM; HYDROUS MAGNESIUM

CAS: 14807-96-6

RTECS: WW2710000

OSHA PEL20 MPPCF

ACGIH TLV: 2 MG/CUM (RESP DUST)

PERLITE

CAS: 93763-70-3

RTECS: SD5254000

OSHA PEL5 MG/CUM (DUST)

ACGIH TLV: 10 MG/CUM TOTAL DUST

POLYVINYL ACETATE, VINYL ACETATE POLYMER

CAS: 9003-20-7

RTECS: AK0920000

ETHYLENE GLYCOL, GLYCOL

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 0-1%

ACGIH TLV: C 127 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

GYP SUM

CAS: 13397-24-5

RTECS: MG2360000

OSHA PEL15 MG/CUM TOTAL DUST

ACGIH TLV: 10 MG/CUM

RTECS: 9999999VO

## Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: NOSE, THROAT & UPPER  
RESPIRATORY SYSTEM IRRITATION. EYES: TRANSITORY IRRITATION. SKIN:  
DRYNESS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: LUNG DAMAGE (PULMONARY FIBROSIS).

Medical Cond Aggravated by Exposure:UPPER RESPIRATORY & LUNG DISEASE,  
BRONCHITIS, EMPHYSEMA, & ASTHMA

---

## First Aid

First Aid:EYES: FLUSH W/PLENTY OF WATER TO REMOVE PARTICLES. SKIN: WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Extinguishing Media:NOT COMBUSTIBLE

## Accidental Release

Spill Release Procedures:SCOOP UP. WASH DOWN AREA BEFORE MATERIAL DRIES.

## Handling

Handling and Storage Precautions:STORE IN COOL, DRY PLACE. AVOID FREEZING.

Other Precautions:WHEN FINISHING JOINTS USING THESE PRODUCTS, WET SANDING IS RECOMMENDED.

## Exposure Controls

Respiratory Protection:USE NIOSH APPROVED DUST RESPIRATOR IF DRY SANDED

Ventilation:GENERAL MECHANICAL OR LOCAL EXHAUST

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

HEALTH EFFECTS ARE DERIVED FROM SPRAY MIST OR DUST FROM DRY SANDING.

PRODUCT MAY CONTAIN INGREDIENTS 1317-65-3 OR 13397-24-5.

## Chemical Properties

Spec Gravity:1.6

pH:8-9.5

Appearance and Odor:OFF WHITE PASTE W/LOW ODOR

Percent Volatiles by Volume: 35

## Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FREEZING

## Disposal

Waste Disposal Methods:SANITARY LANDFILL IN ACCORDANCE W/FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.