

METAL POLISH

MSDS Number

BJXKT

National Stock Number

7930-00-266-7137

Product Name

METAL POLISH

Manufacturer

INDUSTRIAL FLOOR FINISHES

Product Identification

Product ID:METAL POLISH MSDS Date:05/01/1987 FSC:7930 NIIN:00-266-7137 MSDS Number: BJXKT

Responsible Party

INDUSTRIAL FLOOR FINISHES

605 SPRINGS ROAD

BEDFORD, MA 01730

US

Emergency Phone: 617-667-5161 OR POISON CENTER

Info Phone: 617-667-5161 Preparer: T. PITROLFFY

Cage: 0J4J4

Contractor

PERMA, INCORPORATED

BEDFORD, MA 01730

US

978-667-5161

Cage: 0J4J4

Ingredients

STODDARD SOLVENT

CAS: 8052-41-3 RTECS: WJ8925000

Fraction By Weight: 17%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

Hazards

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Health Hazards Acute and Chronic:ACUTE: PRIMARY EYE AND SKIN IRRITANT WITH CONTACT. INHALATION: MAY CAUSE HEADACHE, DIZZINESS AND NAUSEA. CHRONIC: NOT SUFFICIENT DATA, EXERCISE CARE, DO NOT USE ABOVE TLV.

First Aid

First Aid: EYE: FLUSH WITH WATER. SKIN: WASH WITH SOAP AND WATER, APPLY



SKIN CREAM. INHALATION: REMOVE TO FRESH AIR, RESTORE BREATHING, CALL PHYSICIAN. INGESTION: DRINK WATER OR MILK, DO NOT INDUCE VOMITING, CAL L POISON CONTROL.

Fire Fighting

Flash Point Method:TCC Flash Point:104F,40C Lower Limits:0.8 Upper Limits:6.0

Extinguishing Media: FOAM, CO2, DRY CHEMICAL.

Fire Fighting Procedures: WATER MAY BE USED TO COOL CONTAINRS TO PREVENT

PRESSURE BUILD-UP OR AUTO-IGNITION.

Unusual Fire/Explosion Hazard: ISOLATE FROM HEAT, CLOSED CONTAINERS MAY

EXPLODE IF EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures: REMOVE SOURCES OF IGNITION, SPRINKLE WITH ABSORBENT. FOG WITH WATER. FLUSH OR SCRAPE INTO RETAINING AREA OR CONTAINER. INCREASE VENTILATION. AVOID BREATHING VAPORS.

Handling

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. USE ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED CONTACT. KEEP CONTAINER CLOSED.

Other Precautions: AVOID STATIC BUILD-UP. KEEP AWAY FROM CHILDREN.

Exposure Controls

Respiratory Protection: SELF-CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE TLV.

Ventilation:LOCAL EXHAUST-YES. MECHANICAL EXHAUST: EXHAUST FROM LOWER

LEVELS.

Protective Gloves: USE RUBBER GLOVES.

Eye Protection: SAFETY GLASSES.

Other Protective Equipment: EYE BATH, SAFETY SHOWER, PROTECTIVE CREAM.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:215F,102C

Vapor Pres:2 Vapor Density:3.8 Spec Gravity:1.1

Evaporation Rate & Reference: 0.8 (WATER)

Solubility in Water: PARTIAL

Appearance and Odor: PINK CREAMY LIQUID, AMMONIA ODOR

Percent Volatiles by Volume: 74

Stability

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDERS.

Stability Condition to Avoid: HEAT, SPARKS, OPEN FLAME AND FIRE.

Hazardous Decomposition Products: THERMAL DECOMPOSITION PRODUCES FUMES, MAY YIELD CARBON MONOXIDE.

Disposal

Waste Disposal Methods:INCINERATE OR DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. EMPTY CONTAINERS MAY RETAIN FUMES. DO NOT EXPOSE TO HEAT OR FLAME.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.