

PW-120 KAR WAX

MSDS Number

BJXLD

National Stock Number

7930-00-281-3267

Product Name

PW-120 KAR WAX

Manufacturer

INDUSTRIAL FLOOR FINISHES

Product Identification

Product ID:PW-120 KAR WAX

MSDS Date:01/17/1991

FSC:7930

NIIN:00-281-3267

MSDS Number: BJXLD

Responsible Party

INDUSTRIAL FLOOR FINISHES

605 SPRINGS ROAD

BEDFORD , MA 01730

US

Emergency Phone: 800-255-3924 OR POISON CENTER

Info Phone: 508-667-5161

Preparer: T. PITROLFFY

Cage: 0J4J4

Contractor

PERMA, INCORPORATED

BEDFORD, MA 01730

US

978-667-5161

Cage: 0J4J4

Ingredients

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8925000

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:UNKNOWN OSHA:NO

Health Hazards Acute and Chronic:SEVERE EYE IRRITATION, DRYING OF SKIN, DIZZINESS, NAUSEA. VAPORS MAY BE NARCOTIC. CHRONIC: RESPIRATORY TRACT IRRITATION, COULD DAMAGE LIVER AND KIDNEY.

Effects of Overexposure:IRRITATION AND REDNESS OF SKIN, DIZZY FEELING, PALE AND NAUSEOUS.

Medical Cond Aggravated by Exposure:KIDNEY, LIVER AND LUNG PROBLEMS

First Aid

First Aid:EYE & SKIN CONTACT: FLUSH WITH PLENTY OF WATER. INHALATION:
REMOVE TO FRESH AIR, BEGIN ARTIFICIAL RESPIRATION IF NEEDED.
INGESTION: DO NOT INDUCE VOMITING, GET IMMEDIATE MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:TCC
Flash Point:103F,39C
Autoignition Temp:Autoignition Temp Text:510
Lower Limits:0.7
Upper Limits:6.0
Extinguishing Media:CO2, FOAM, DRY CHEMICAL
Fire Fighting Procedures:COOL CONTAINERS WITH WATER, USE SELF-
CONTAINED BREATHING APPARATUS, BURNING PRODUCT IS TOXIC.

Accidental Release

Spill Release Procedures:COLLECT MATERIAL INTO METAL CONTAINER. AVOID
SPARKS, FLAME, HOT SURFACES. WIPE OFF RESIDUE WITH RAG.

Handling

Handling and Storage Precautions:COMBUSTABLE, KEEP AWAY FROM HEAT,
SPARKS, AND OPEN FLAME. USE ADEQUATE VENTILLATION. AVOID PROLONGED
OR REPEATED COCTACT. KEEP CONTAINERS CLOSED.
Other Precautions:STORE IN SECURE AREA. DISPOSE OF EMPTY CONTAINERS
SAFELY KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:USE SELF-CONTAINED BREATHING APPARATUS FOR
CONCENTRATIONS ABOVE THRESHOLD LIMIT VALUE.
Ventilation:LOCAL EXHAUST RECOMMENDED. MECHANICAL: ASSURE FRESH AIR
CIRCULATION
Protective Gloves:RECOMMENDED: RUBBER
Eye Protection:RECOMMENDED: GOGGLES
Other Protective Equipment:EYE BATH, SHOWER
Work Hygienic Practices:DO NOT EAT/DRINK OR SMOKE NEXT TO MATERIAL.
WASH HANDS/FACE AFTER WORK.
Supplemental Safety and Health

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:320F,160C
Melt/Freeze Pt:M.P/F.P Text:131F,55C
Vapor Pres:2.0
Vapor Density:4.7
Spec Gravity:0.79
Viscosity:45 CPS
Evaporation Rate & Reference:0.21
Solubility in Water:NEGLIGIBLE
Appearance and Odor:LIGHT BLUE PASTE, SOLVENT ODOR

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON
MONOXIDE.

Disposal

Waste Disposal Methods:RECYCLE, INCINERATE, OR USE HAZARDOUS WASTE
DAMAGEMENT FACILITY FOR DISPOSAL ACCORDING TO STATE AND FEDERAL
REGULATIONS. EPA WASTE NO. D001

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.