
LBP-CX;EP CARTRIDGE # LBP-0002-000

MSDS Number

BJYNF

National Stock Number

6850-01-261-6064

Product Name

LBP-CX;EP CARTRIDGE # LBP-0002-000

Manufacturer

CANON U S A INC

Product Identification

Product ID:LBP-CX;EP CARTRIDGE # LBP-0002-000

MSDS Date:11/01/1985

FSC:6850

NIIN:01-261-6064

MSDS Number: BJYNF

Responsible Party

CANON U S A INC

1 CANON PLAZA

LAKE SUCCESS , NY 11040-1113

US

Emergency Phone: 516-488-6700

Info Phone: 516-488-6700

Cage: 1BA63

Contractor

CANON USA INC

LAKE SUCCESS, NY 11042

US

516-328-5600

Cage: 1BA63

Ingredients

IRON OXIDE

CAS: 1317-61-9

Fraction By Weight: 35-40%

STYRENE-ACRYLIC COPOLYMER

CAS: 25767-47-9

Fraction By Weight: 55-60%

SALICYLIC ACID CHELATE

CAS: 72869-85-3

Fraction By Weight: 1-5%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF
EYES,SKIN,RESPIRATORY OR G,I.TRACT;REDNESS OR BURNS OF EYES ARE
POSSIBLE.
Explanation of Carcinogenicity:DATA PER MGF MSDS.
Effects of Overexposure:SEE HEALTH HAZARDS DATA.
Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE
WORSEN.

First Aid

First Aid:EYES AND SKIN:FLUSH WITH LARGE AMOUNT OF WATER FOR ABOUT
15-20 MINUTES;SEEK MEDICAL ATTENTION IMMEDIATELY.INHALATION:REMOVE
TO FRESH AIR;CALL A PHYSICIAN.INGESTION:SEEK MEDICAL ATTENTION
IMMEDIATELY.

Fire Fighting

Flash Point:NONE
Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL
FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:MAY CAUSE DUST EXPLOSION ;COMBUSTION OR
HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND
VAPORS.

Accidental Release

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;SWEEP UP OR
VACUUM AND COLLECT FOR PROPER DISPOSAL IN AN APPROVED CONTAINER.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED
AREA.KEEP CONTAINER CLOSED WHEN NOT IN USE.
Other Precautions:WASH THOROUGHLY AFTER EACH USE.

Exposure Controls

Respiratory Protection:NONE REQUIRED;USE NIOSH/MSHA APPROVED RESPIRATOR
FOR DUST/MIST IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED AREA.
Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.
Protective Gloves:AS REQUIREED
Eye Protection:SAFETY GLASSES/GOGGLES
Other Protective Equipment:PROTECTIVE CLOTHINGS.EYE-WASH
FACILITIES,SAFETY SHOWER.
Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE
VAPORS/MIST/DUST.WASH THOROUGHLY AFTER EACH USE;DO NOT
EAT,DRINK,SMOKE.
Supplemental Safety and Health
KEEP OUT OF REACH OF CHILDREN.KEEP AWAY FROM OXIDIZING MATERIAL.

Chemical Properties

HCC:N1
Vapor Pres:NEGLIGIBLE
Spec Gravity:1.4
Evaporation Rate & Reference:NEGLIGIBLE
Solubility in Water:NEGLIGIBLE
Appearance and Odor:FINE POWDER,SLIGHT,PLASTIC ODOR

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HIGH HEAT
Hazardous Decomposition Products:CO AND CO*2

Disposal

Waste Disposal Methods:CONSULT LOCAL AUTHORITIES;DISPOSAL MUST BE IN
ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.