

A-A-15 POLISH, AUTO, T II, PASTE

MSDS Number

BJZVB

National Stock Number

7930-00-489-5606

Product Name

A-A-15 POLISH, AUTO, T II, PASTE

Manufacturer

INDUSTRIAL FLOOR FINISHES

Product Identification

Product ID:A-A-15 POLISH, AUTO, T II, PASTE

MSDS Date:02/25/1991

FSC:7930

NIIN:00-489-5606

MSDS Number: BJZVB

Responsible Party

INDUSTRIAL FLOOR FINISHES

605 SPRINGS ROAD

BEDFORD , MA 01730

US

Emergency Phone: 800-255-3924 OR POISON CENTER

Info Phone: 508-667-5161

Preparer: A. VADASZ

Cage: 0J4J4

Contractor

PERMA, INCORPORATED

BEDFORD, MA 01730

US

978-667-5161

Cage: 0J4J4

Ingredients

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight:

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO

Health Hazards Acute and Chronic:CAUSES EYE IRRITATION, DRYING OF SKIN, DIZZINESS. CHRONIC:RESPIRATORY TRACT IRRITATION, DERMATITIS. TARGET ORGANS: SKIN, EYES, RESPIRATORY SYSTEM.

Effects of Overexposure:EXCESSIVE INHALATION MAY CAUSE HEADACHE & DIZZINESS

Medical Cond Aggravated by Exposure:DERMATITIS. BRONCHO-PULMONARY

PROBLEMS

First Aid

First Aid:EYE & SKIN CONTACT:BLOT WITH TOWEL, FLUSH WITH LARGE QUANTITIES OF WATER. INHALATION:REMOVE TO FRESH AIR. INGESTION: INDUCE VOMITING, GET IMMEDIATE MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:TCC
Flash Point:141 F/61 C
Autoignition Temp:Autoignition Temp Text:500F
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM, DRY CHEMICAL.
(PH: 8.2 +/- .5)
Fire Fighting Procedures:COOL CONTAINERS WITH WATER. USE SELF CONTAINED BREATHING APPARATUS. BURNING PRODUCT IS TOXIC.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY BURST WHEN EXPOSED TO EXTREME HEAT. ISOLATE FROM HEAT, SPARKS & OPEN FLAME.

Accidental Release

Spill Release Procedures:DIKE & COLLECT MATERIAL INTO METAL CONTAINER. USE NON-SPARKING TOOLS. USE WATER OR FOAM SPRAY TO LESSEN FIRE HAZARD. USE ABSORBENT FOR SMALL SPILL.

Handling

Handling and Storage Precautions:COMBUSTIBLE, KEEP AWAY FROM HEAT, SPARKS & OPEN FLAME. USE ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED CONTACT.
Other Precautions:STORE IN SECURE AREA. DISPOSE OF EMPTY CONTAINERS SAFELY. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:USE SELF CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE THRESHOLD LIMIT VALUE
Ventilation:LOCAL RECOMMEND.MECH:REQUIRED,EXCHANGE EVERY 10-15 MIN.
SPECIAL:BLOW AIR TO PITS/DEPRESSIONS.ASSURE FRESH AIR CIRCULATIO
Protective Gloves:REQUIRED:RUBBER, PLASTIC
Eye Protection:REQUIRED:SAFETY GLASSES
Other Protective Equipment:APRON OR SHOP COAT RECOMMENDED
Work Hygienic Practices:DO NOT EAT/DRINK OR SMOKE NEXT TO MATERIAL.
WASH HANDS/FACE AFTER WORK.
Supplemental Safety and Health

Chemical Properties

HCC:F8
Boiling Pt:B.P. Text:230F,110C
Vapor Pres:2.0
Vapor Density:4.7
Spec Gravity:0.82
pH: *
Evaporation Rate & Reference:0.06 (BU AC=1)
Solubility in Water:APPRECIABLE
Appearance and Odor:GREEN, SOFT PASTE

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME & FIRE
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE & DIOXIDE

Disposal

Waste Disposal Methods:RECYCLE, INCINERATE OR USE HAZARDOUS WASTE MANAGEMENT FACILITY FOR DISPOSAL ACCORDING TO STATE & FEDERAL REGULATIONS. EPA WASTE NO. D001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.