

## **OLIVE DRAB CANVAS COAT**

### **MSDS Number**

BKBCL

### **National Stock Number**

8030-00-281-2346

### **Product Name**

OLIVE DRAB CANVAS COAT

### **Manufacturer**

EVERSEAL MANUFACTURING CO INC

### **Product Identification**

Product ID:OLIVE DRAB CANVAS COAT

MSDS Date:04/06/1987

FSC:8030

NIIN:00-281-2346

MSDS Number: BKBCL

### **Responsible Party**

EVERSEAL MANUFACTURING CO, INC.

475 BROAD AVENUE

RIDGEFIELD , NJ 07657

US

Emergency Phone: 201-943-4986

Info Phone: 201-943-4986

Cage: EO432

### **Contractor**

EVERSEAL MFG CO INC

RIDGEFIELD, NJ 07657-2329

US

201-943-4986

Cage: 72988

### **Ingredients**

CHLORINATED PARAFFINS

CAS: 61788-76-9

Fraction By Weight: 19%

ALKYD RESIN

Fraction By Weight: 2%

IRON OXIDE

CAS: 1332-37-2

RTECS: NO7380000

Fraction By Weight: 9%

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 2 - 10%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 44%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9192

CARBON TETRACHLORIDE (SARA III)

CAS: 56-23-5

RTECS: FG4900000

Fraction By Weight: 0.1%

OSHA PEL10 PPM

ACGIH TLV: S,5PPM/10 STEL,A3 93

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

COPPER SOLUTION - AS CU (VP 5)

Fraction By Weight: 0.2%

5 G/KG (ORAL)

Fraction By Weight: 21%

## Hazards

Explanation of Carcinogenicity:HAS BEEN DETERMINED TO BE A POSSIBLE CARCINOGEN

Effects of Overexposure:INHALE:DIZZINESS, NAUSEA, POSSIBLE UNCONSCIOUSNESS. IRRITATION TO SKIN & EYES. LEVELS ABOVE TLV, CARBON TETRACHLORIDE HAS BEEN DETERMINED TO BE A POSSIBLE CARCINOGEN & ALSO A CAUSE OF LIVER, KIDNEY & INTESTINAL DAMAGE. MEASURES SHOULD BE TAKEN TO ENSURE TLV IS NOT ACHIEVED OR PROTECTION PROVIDED IF THIS IS NOT POSSIBLE

## First Aid

First Aid:INHALATION:REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF NECESSARY. SKIN:WASH WITH SOAP & WATER, APPLY MILD CREAM. EYES:FLUSH WITH WATER. CALL PHYSICIAN.

## Fire Fighting

Flash Point:105 F/41 C

Lower Limits:1

Extinguishing Media:FOAM, CO2, DRY CHEMICAL. WATER IS NOT A SUITABLE EXTINGUISHING MEDIUM

Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR SELF-CONTAINED

BREATHING APPARATUS. COMBUSTION MAY YIELD TOXIC OR NOXIOUS FUMES.

## **Accidental Release**

Spill Release Procedures:ABSORB SMALL SPILLS ON DRY ABSORPTION MATERIAL. USE SPARK PROOF SCOOP FOR LARGER SPILLS. ENSURE ADEQUATE VENTILATION. REMOVE IGNITION SOURCES.

## **Handling**

Handling and Storage Precautions:AVOID EXCESSIVE HEAT. KEEP AWAY FROM ALL IGNITION SOURCES.

Other Precautions:NPCA/HMIS RATING 3,2,0,H

## **Exposure Controls**

Respiratory Protection:IF TLV MAY BE ACHIEVED USE FUME-DUST MASK OR AIR-SUPPLIED HOOD

Ventilation:SUFFICIENT TO ENSURE LEL NOT ACHIEVED

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES

Other Protective Equipment:PROTECT SKIN WITH CLOTHES OR BARRIER CREAM  
Supplemental Safety and Health

## **Chemical Properties**

Boiling Pt:B.P. Text:323 TO 390F

Vapor Density:> THAN AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:44

## **Stability**

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING MATERIALS - EXCESSIVE HEAT.

Hazardous Decomposition Products:HIGH HEAT OR COMBUSTION MAY YIELD COPPER OXIDES & OTHER NOXIOUS GASES

## **Disposal**

Waste Disposal Methods:DISPOSE OF AS A HAZARDOUS WASTE PER LOCAL & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.