

00537 WHITE OIL 22

MSDS Number

BKBPK

National Stock Number

9150-01-307-0287

Product Name

00537 WHITE OIL 22

Manufacturer

TEXACO INC

Product Identification

Product ID:00537 WHITE OIL 22

MSDS Date:07/24/1987

FSC:9150

NIIN:01-307-0287

MSDS Number: BKBPK

Responsible Party

TEXACO INC

BEACON , NY 12508-0509

US

Emergency Phone: 914-831-3400 EXT 204

Cage: 7B131

Contractor

TEXACO INC

509

BEACON, NY 12508-0509

US

914-831-3400

Cage: 7B131

Ingredients

WHITE MINERAL OIL

CAS: 8042-47-5

RTECS: PY8047000

Fraction By Weight: 100%

OSHA PEL5 MG/M3 OIL MIST

ACGIH TLV: 5 MG/M3 OIL MIST

Hazards

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 5 G/KG

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: MILD EYE IRRITATION. SKIN: MILD IRRITATION. INGESTION:NO ILL EFFECTS EXPECTED, CAN CAUSE LUNG INJURY IF ASPIRATED.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:MILD EYE & SKIN IRRITATION.

Medical Cond Aggravated by Exposure:NONE

First Aid

First Aid:INGESTION:DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.
SKIN:WASH WITH SOAP & WATER. REMOVE AND LAUNDER CONTAMINATED CLOTHING. EYE:FLUSH WITH PLENTY OF WATER FOR ATLEAST 15 MINUTES. GET MEDICAL ATTEN TION. INHALATION: REMOVE TO FRESH AIR.

Fire Fighting

Flash Point Method:COC

Flash Point:315F,157C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

Accidental Release

Spill Release Procedures:CONTAIN SPILL. PROTECT FROM IGNITION. ABSORB WITH SAND OR INERT MATERIAL. SWEEP OR SCOOP UP AND TRANSFER TO DISPOSAL DRUM.

Neutralizing Agent:NONE

Handling

Handling and Storage Precautions:KEEP AWAY FROM SPARKS AND OPEN FLAMES.

Other Precautions:DO NOT GET IN EYES, OR ON CLOTHING. KEEP AWAY FROM SPARKS AND OPEN FLAMES.

Exposure Controls

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:USE WITH ADEQUATE VENTILATION.

Protective Gloves:NEOPRENE/BUTYL RUBBER/POLYETHYLENE

Eye Protection:FACE SHIELD

Other Protective Equipment:NONE

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

Chemical Properties

HCC:V6

Melt/Freeze Pt:M.P/F.P Text:NO

Spec Gravity:0.89

Viscosity:19.3 CST@40C

Appearance and Odor:WHITE OIL

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

Disposal

Waste Disposal Methods:INCINERATE, RECYCLE OR OTHERWISE MANAGE IN A PERMITTED WASTE MANAGEMENT FACILITY IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.