

12/16 OZ. PRE-DRAIN CRANKCASE CL

MSDS Number

BKCCH

National Stock Number

9999-00B070052

Product Name

12/16 OZ. PRE-DRAIN CRANKCASE CL

Manufacturer

GOLD EAGLE CO

Product Identification

Product ID:12/16 OZ. PRE-DRAIN CRANKCASE CL

MSDS Date:08/01/1990

FSC:9999

NIIN:00B070052

MSDS Number: BKCCH

Responsible Party

GOLD EAGLE CO.

4400 S. KILDARE BLVD.

CHICAGO , IL 60632-4372

US

Emergency Phone: 800-535-5053 (INFOTRAC)

Info Phone: 312-376-4400

Cage: DO861

Contractor

GOLD EAGLE COMPANY

97267

CHICAGO, IL 60632-4372

US

773-376-4400

Cage: 2M612

Ingredients

PARAFFINIC PETROLEUM OIL

CAS: 64742-50-3

Fraction By Weight: 40-50%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Health Hazards Acute and Chronic:NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure:INHALATION MAY CAUSE DROWSINESS, DIZZINESS, HEADACHE, NAUSEA, LUNG IRRITATION OR CHEMICAL PNEUMONITIS. SKIN AND EYE CONTACT ARE SLIGHT IRRITANTS. LARGE QUANTITY INGESTION MAY CAUSE GI DISCOMFORT, DIAR RHEA AND HEADACHE.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:INHALATION: REMOVE VICTIM TO FRESH AIR. RESTORE/SUPPORT BREATHING AS REQUIRED. GET MEDICAL ATTENTION. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL

ATTENTION. EYES: FLUSH EYES W/LARGE QUANTITIES OF WATERFOR 15 MIN., GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITTING, GET PROMPT MEDICAL ATTENTION

Fire Fighting

Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER FOG.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE.
Unusual Fire/Explosion Hazard:WATER MAY CAUSE FROTHING.

Accidental Release

Spill Release Procedures:CONTAIN SPILL, TRANSFER TO SECURE CONTAINERS. IN THE EVENT OF AN UNCONTROLLED MATERIAL RELEASE, THE USER SHOULD DETERMINE IF RELEASE IS REPORTABLE UNDER APPLICABLE LAWS AND REGULATINS. ABSORB SMALL SPILLS WITH SUITABLE MATERIAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE BELOW 150F. DO NOT APPLY HIGH HEAT OR FLAMES TO CONTAINER. KEEP SEPARATE FROM STRONG OXIDIZING AGENTS.
Other Precautions:EMPTY CONTAINER SMAY CONTAIN PRODUCT RESIDUE WHICH COULD BE FLAMMABLE OR EXPLOSIVE VAPORS.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA RESPIRATOR APPROVED FOR ORGANIC VAPORS AND MISTS IF MIST OR VAPORS EXCEED NIOSH TLV.
Ventilation:PROVIDE PROPERLY ENGINEERED VENTILATION TO MINIMIZE OIL MIST/ VAPORS BELOW 5 MG/CUBIC METER NIOSH TLV.
Protective Gloves:CHEMICAL RESISTANT.
Eye Protection:SAFETY GLASSES, CHEMICAL SPLASH GOGGLES.
Other Protective Equipment:OIL IMPERVIOUS CLOTHING IF REQUIRED.
Work Hygienic Practices:STANDARD PERSONAL HYGIENE.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

HCC:N1
Boiling Pt:B.P. Text:>600F,>316C
Vapor Pres:Vapor Density:>1.0
Spec Gravity:0.900
Evaporation Rate & Reference:Solubility in Water:NEGLIGIBLE
Appearance and Odor:BROWN LIQUID, ADDITIVE COLOR. NO ODOR SPECIFIED BY MANUFACTURER.

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS
Stability Condition to Avoid:HEAT, OPEN FLAME, SOURCES OF IGNITION.
Hazardous Decomposition Products:CO2, CO
Conditions to Avoid Polymerization:HEAT, OPEN FLAME, SOURCES OF IGNITION

Disposal

Waste Disposal Methods:DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. BEFORE ATTEMPTING CLEAN UP, REFER TO OTHER SECTIONS OF MSDS FOR HAZARD CAUTION INFORMATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.