

SILICONE OIL,RUST-INHIBITED BEESTON B-331-R

MSDS Number

BKCJB

National Stock Number

9150-01-086-9466

Product Name

SILICONE OIL,RUST-INHIBITED BEESTON B-331-R

Manufacturer

BEESTON INC

Product Identification

Product ID:SILICONE OIL,RUST-INHIBITED BEESTON B-331-R

MSDS Date:04/08/1985

FSC:9150

NIIN:01-086-9466

MSDS Number: BKCJB

Responsible Party

BEESTON, INC.

540 DEERING AV

SCARBOROUGH , ME 04074

US

Emergency Phone: 207-883-5541/800-424-9300(CHEMTREC)

Info Phone: 207-883-5541

Cage: LO373

Contractor

BEESTON, INC.

1116

SCARBROUGH, ME 04074

US

207-883-5541

Cage: LO373

Ingredients

"NOT HAZARDOUS"

Fraction By Weight: 100%

Hazards

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT AVAILABLE

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:HUMAN EFFECTS OF OVEREXPOSURE-HUMAN EXPERIENCE WITH POLYDIMETHYLSILOXANE FLUIDS HAS NOT INDICATED ANY SERIOUS EFFECTS RELATED TO EXPOSURE BY ANY ROUTE. DIRECT EYE

CONTACT CAN CAUSE A TRANSITORY IRRITATION BUT IS NOT INJURIOUS.THIS IRRITATION MAY PERSISTS FOR UP TO 24 HOURS.

Effects of Overexposure:SEE HEALTH HAZARDS SECTION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:SKIN:WASH OFF CONTACTED SKIN WITH SOAP AND WATER. EYES:FLUSH WITH WATER.IF IRRITATION PERSISTS, CONSULT A

PHYSICIAN.INHALATION/ORAL: NO PROBLEM.

Fire Fighting

Flash Point Method:OC

Flash Point:400F,204C

Extinguishing Media:WATER, WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures:USE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS & FULL PROTECTIVE EQUIPMENT IF NEEDED. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:NONE KNOWN TO MANUFACTURER.

Accidental Release

Spill Release Procedures:WIPE UP MATERIAL. RESIDUE IS SLIPPERY. APPLY SAWDUST OR SWEEPING COMPOUND TO AREA OF SPILL TO MINIMIZE SLIP.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORAGE-STORE IN A COOL, DRY PLACE. KEEP AWAY FROM OPEN FLAMES & HIGH TEMPERATURES. CLEAN UP SPILLS PROMPTLY.

Other Precautions:DO NOT GET IN EYES.

Exposure Controls

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:NONE NORMALLY REQUIRED.

Protective Gloves:PLASTIC OR RUBBER

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

Chemical Properties

HCC:V6

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres:Spec Gravity:1.06

Evaporation Rate & Reference:Solubility in Water:Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH TEMPERATURES AND FLAMES

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF SILICON

Disposal

Waste Disposal Methods:INCINERATE OR LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.