

1.1-5 GASKET SEALANT TYPE I

MSDS Number

BKCKP

National Stock Number

8030-00F015027

Product Name

1.1-5 GASKET SEALANT TYPE I

Manufacturer

VERSACHEM CORP

Product Identification

Product ID:1.1-5 GASKET SEALANT TYPE I

MSDS Date:04/01/1987

FSC:8030

NIIN:00F015027

MSDS Number: BKCKP

Responsible Party

VERSACHEM CORPORATION

6643 42ND TERRACE NORTH

WEST PALM BEACH , FL 33407

Emergency Phone: (407) 845-2425

Info Phone: (407) 845-2425

Preparer: RONALD J. COSTELLO

Cage: 0FY40

Contractor

VERSACHEM CORPORATION

WEST PALM BEACH, FL 33407

US

561-845-2425

Cage: 0FY40

Ingredients

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 10-15%

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

KAOLIN

CAS: 1332-58-7

RTECS: GF1670500

Fraction By Weight: 50-55%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 2 MG/M3 TDUST; 9293

MODIFIED NATURAL RESINS

Fraction By Weight: 30-35%

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: IRRITATE NOSE & THROAT,
HEADACHE, DIZZINESS & NAUSEA. EYES: IRRITATION. INGESTION:
MODERATELY TOXIC.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION: IRRITATION TO NOSE & THROAT,
HEADACHE, DIZZINESS & NAUSEA. EYES: IRRITATION. INGESTION:
MODERATELY TOXIC.

First Aid

First Aid:INGESTION: INDUCE VOMITING. INHALATION: REMOVE TO AIR. SKIN:
WASH W/SOAP & WATER. EYE: FLUSH W/WATER FOR 15 MINUTES. OBTAIN
MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:CC
Flash Point:60F
Lower Limits:2%
Upper Limits:12%
Extinguishing Media:CO2, DRY CHEMICAL, FOAM
Unusual Fire/Explosion Hazard:FLAMMABLE LIQUID.

Accidental Release

Spill Release Procedures:SCRAPE/WIPE UP AS MUCH AS POSSIBLE & STORE IN
CLOSED CONTAINERS. RESIDUE MAY BE CLEANED W/ISOPROPYL ALC. OR
1,1,1-TRICHLOROETHANE. FOR LARGE QUANTITY SPILLS VENTILATE AREA
WELL & ELIMINATE SOURCES OF IGNITION.

Handling

Handling and Storage Precautions:AVOID PROLONGED BREATHING OF VAPORS &
CONTACT W/EYES. DON'T STORE NEAR HEAT, SPARKS OR FLAME.

Exposure Controls

Ventilation:MUST BE ADEQUATE TO AVOID EXCEEDING TLV
Eye Protection:SAFETY GLASSES
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:180F
Vapor Pres:33
Vapor Density:2.07
Spec Gravity:1.5
Solubility in Water:APPRECIABLE
Appearance and Odor:BROWN; ALCOHOLIC ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:HEAT, SPARKS, FLAME, SOURCE OF IGNITION
Hazardous Decomposition Products:CARBON, CO, CO2

Disposal

Waste Disposal Methods:LAND FILL OR INCINERATE FOLLOWING EPA & LOCAL
REGULATIONS. DOT: ORM-D. FLAMMABLE LIQUID.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.