

26800 PERMATEX HIGH TACK ADHESIVE SEALANT

MSDS Number

BKCPB

National Stock Number

8030-00F015103

Product Name

26800 PERMATEX HIGH TACK ADHESIVE SEALANT

Manufacturer

BOWMAN DISTRIBUTION BARNES GROUP INC

Product Identification

Product ID:26800 PERMATEX HIGH TACK ADHESIVE SEALANT

MSDS Date:07/09/1986

FSC:8030

NIIN:00F015103

MSDS Number: BKCPB

Responsible Party

BOWMAN DISTRIBUTION, BARNES GROUP INC

850 EAST 72ND STREET

CLEVELAND , OH 44103

Emergency Phone: (216) 391-7200

Info Phone: (216) 391-7200

Cage: 05575

Contractor

BOWMAN DISTRIBUTION, BARNES GROUP INC.

CLEVELAND, OH 44103

US

(216) 391-7200

Cage: 05575

Ingredients

BUTADIENE ACRYLONITRILE COPOLYMER

RTECS: 9999999VO

Fraction By Weight: 50-60%

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 35-40%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

HEXANE (N-HEXANE)

CAS: 110-54-3

RTECS: MN9275000

Fraction By Weight: 15-20%

OSHA PEL500 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

RESIN

Fraction By Weight: 35-40%

DYE

Fraction By Weight:

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INGESTION: MODERATELY TOXIC.

EYES/SKIN: IRRITATION, INJURY. INHALATION: HEADACHES, DIZZINESS, NAUSEA, NOSE/THROAT IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYE/SKIN: IRRITATION, INJURY. INHALATION:

NOSE/THROAT IRRITATION, HEADACHES, DIZZINESS, NAUSEA.

First Aid

First Aid:INGESTION: DRINK GLASS OF WATER OR MILK. INHALATION: REMOVE TO FRESH AIR. SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:0F

Lower Limits:2%

Upper Limits:13%

Extinguishing Media:FOAM, DRY CHEMICAL

Unusual Fire/Explosion Hazard:FLAMMABLE LIQUID

Accidental Release

Spill Release Procedures:VENTILATE AREA WELL. ELIMINATE SOURCES OF IGNITION. USE ABSORBENT TO SOAK UP MATERIAL. CLEAN AREA W/NONFLAMMABLE SOLVENT.

Handling

Handling and Storage Precautions:DON'T STORE NEAR HEAT OR FLAME.

PROVIDE ADEQUATE CROSS VENTILATION.

Other Precautions:USE PROPER SAFETY PRECAUTIONS AS W/ALL EXTREMELY FLAMMABLE MATERIALS.

Exposure Controls

Ventilation:PROVIDE ADEQUATE VENTILATION TO AVOID EXCEEDING TLV

Protective Gloves:NONE NEEDED

Eye Protection:NONE NEEDED

Other Protective Equipment:NONE

Supplemental Safety and Health

PERCENT SOLID/WT: 45-55%.

Chemical Properties

Vapor Pres:400

Vapor Density:2.5

Spec Gravity:0.872
Solubility in Water:INSOLUBLE
Appearance and Odor:RED COLOR LIQUID, ACETONE ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:HEAT, FLAME, SOURCES OF IGNITION.

Disposal

Waste Disposal Methods:LANDFILL OR INCINERATE FOLLOWING EPA & LOCAL
REGULATIONS. REPORTABLE QUANTITY: ACETONE-5000 LBS. FLAMMABLE
LIQUID; UN 1993.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.