

## **SOUNDONEL C AWS A5.11**

### **MSDS Number**

BKCWH

### **National Stock Number**

3439-00F015277

### **Product Name**

SOUNDONEL C AWS A5.11

### **Manufacturer**

HOBART BROTHERS CO

### **Product Identification**

Product ID: SOUNDONEL C AWS A5.11

MSDS Date: 09/01/1989

FSC: 3439

NIIN: 00F015277

MSDS Number: BKCWH

### **Responsible Party**

HOBART BROTHERS CO

600 WEST MAIN STREET

TROY , OH 45373

Emergency Phone: (513) 332-4000

Info Phone: (513) 332-4000

Cage: 28835

### **Contractor**

HOBART BROTHERS CO

TROY, OH 45373

US

513-339-6000

Cage: 28835

### **Ingredients**

MICA - SILICATES (< 1% CRYSTALLINE SILICA)

CAS: 12001-26-2

RTECS: VV8760000

Fraction By Weight:

OSHA PEL20 MPPCF

ACGIH TLV: 3 MG/M3 RDUST; 9293

IRON

CAS: 7439-89-6

RTECS: NO4565500

Fraction By Weight:

MANGANESE (SARA III)

CAS: 7439-96-5

RTECS: OO9275000

Fraction By Weight:

OSHA PEL(C) 5 MG/M3 DUST

ACGIH TLV: 5 MG/M3 DUST 9293

CHROMIUM (SARA III)

CAS: 7440-47-3

RTECS: GB4200000

Fraction By Weight: 8-15%

OSHA PEL1 MG/M3

ACGIH TLV: 0.5 MG/M3; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

NICKEL (SARA III)

CAS: 7440-02-0

RTECS: QR5950000

Fraction By Weight: 60-65%

OSHA PEL1 MG/M3

ACGIH TLV: 1 MG/M3; 9192

SILICON

CAS: 7440-21-3

RTECS: VW0400000

Fraction By Weight:

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

MOLYBDENUM

CAS: 7439-98-7

RTECS: QA4680000

Fraction By Weight:

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3; 9293

COLUMBIUM, NIOBIUM

CAS: 7440-03-1

Fraction By Weight:

CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 5-12%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9192

SILICATE BINDERS (SODIUM SILICATE)

CAS: 1344-09-8

Fraction By Weight:

ACGIH TLV: 10 MG/CUM

POTASSIUM SILICATE, POTASSIUM METASILICATE

CAS: 1312-76-1

Fraction By Weight:

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight:

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

CALCIUM FLUORIDE (FLUORSPAR, CALCIUM DIFLUORIDE, IRTRAN 3,

CAS: 7789-75-5

RTECS: EW1760000

Fraction By Weight: 3-11%

OSHA PEL2.5 MG/CUM (AS F)

ACGIH TLV: 2.5 MG/CUM (AS F)

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:YES  
Health Hazards Acute and Chronic:EYE: IRRITATION/BURN & DRYNESS. SKIN: BURN & ULCERS. INHALATION: DIZZINESS/NAUSEA/DRYNESS OR IRRITATION OF NOSE & THROAT/PULMONARY EDEMA BRONCHITIS/CHEST TIGHTNESS/FEVER/ALLERGIC REACTION/RESPIRATORY & CNS IRRITATION/LUNG DAMAGE/ASTHMA/SIDEROSIS & PULMONARY FUNCTIONS. INGESTION: METALLIC TASTE/SEVERE INJURY & DEATH.  
Explanation of Carcinogenicity:NICKEL & CHROMIUM ARE SUSPECTED CARCINOGENS.  
Effects of Overexposure:EYE: IRRITATION/BURN & DRYNESS. SKIN: BURN & ULCERS. INHALATION: BONE EROSION/MUSCULAR WEAKNESS/TREMOR (PARKINSON'S DISEASE)/BEHAVIORAL & HANDWRITING CHANGES/MANGANISM/LUNG FIBROSIS/PNEUMOCONIOSIS/LUN G & NASAL CANCER. INGESTION: METALLIC TASTE/SEVERE INJURY & DEATH.

## First Aid

First Aid:EYES/SKIN: FLUSH W/PLENTY OF WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR OR OXYGEN IF NEEDED. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point:NON-FLAMMABLE  
Unusual Fire/Explosion Hazard:CONSUMABLES AS SHIPPED ARE NON-REACTIVE, NON-EXPLOSIVE & ESSENTIALLY NON-HAZARDOUS UNTIL WELDED. WELDING ARCS/SPARKS CANIGNITE COMBUSTIBLES, FLAMMABLE PRODUCTS.

## Handling

Handling and Storage Precautions:WELDING FUMES/GASES CAN'T BE CLASSIFIED SIMPLY. ELEMENTS & OXIDES ARE VIRTUALLY ALWAYS PRESENT AS COMPLEX OXIDES & NOT METALS.

Other Precautions:CONDITIONS INFLUENCE THE COMPOSITION & QUANTITY OF FUMES, GASES, COATINGS ON THE METAL BEING WELDED SUCH AS PAINT, PLATING & GALVANIZING WELDERS & VOLUME CONTAMINANTS SUCH AS CHLORINATED HYDROCARBON V APORS. ELECTRIC SHOCK.

## Exposure Controls

Respiratory Protection:USE NIOSH APPROVED OR EQUIVALENT FUME RESPIRATOR/AIR SUPPLIED RESPIRATOR WHEN WELDING IN CONFINED AREAS OR WHERE LOCAL EXHAUST/VENTILATION DOES NOT KEEP BELOW TLV.

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP FUMES & GASES BELOW TLV.

Protective Gloves:RECOMMENDED

Eye Protection:FACE SHIELD W/FILTER LENS; SEE SUPP

Other Protective Equipment:HELMET, FULL PROTECTIVE CLOTHING, ARM/SHOULDER PROTECTORS & APRON

Supplemental Safety and Health

MATERIAL TO AVOID CONT: NICKEL, NICKEL/CHROMIUM (VI)/COPPER COMPOUNDS, COLUMBIUM, MOLYBDENUM & FLOURIDE. EYE PROTECTION CONT: SHADE NO.

14, PROTECTIVE SCREENS & FLASH GOGGLES.

## Stability

Stability Indicator/Materials to Avoid:YES

IRON OXIDES, FLOURIDES, SECONDARILY COMPLEX OXIDES OF CALCIUM, MANGANESE, CHROMIUM, SILICON & TITANIUM; SEE SUPP

Hazardous Decomposition Products:CO, CO<sub>2</sub>, OZONE & NITROGEN OXIDE

## Disposal

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CONTAINER OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE W/FEDERAL, STATE & LOC AL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.