

## **215-10 INTERIOR SEMI GLOSS LATEX ENAMEL SRP15-84**

### **MSDS Number**

BKCZG

### **National Stock Number**

8010-00F015338

### **Product Name**

215-10 INTERIOR SEMI GLOSS LATEX ENAMEL SRP15-84

### **Manufacturer**

O'BRIEN CORP

### **Product Identification**

Product ID:215-10 INTERIOR SEMI GLOSS LATEX ENAMEL SRP15-84

MSDS Date:10/25/1986

FSC:8010

NIIN:00F015338

MSDS Number: BKCZG

### **Responsible Party**

O'BRIEN CORPORATION

450 EAST GRAND AVENUE

SOUTH SAN FRANCISCO , CA 94080

Emergency Phone: (415) 761-2300

Info Phone: (415) 761-2300

Cage: 85207

### **Contractor**

O'BRIEN CORPORATION, FULLER O'BRIEN PAINTS

SOUTH SAN FRANCISCO, CA 94080-6207

US

Cage: 85207

### **Ingredients**

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 15 - 20%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

PROPANOIC ACID, 2-METHYL, MONOESTER

CAS: 25265-77-4

RTECS: UF6000000

Fraction By Weight:

### **Hazards**

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN/EYE: IRRITATION. INHALATION:  
HEADACHE, NAUSEA, & IRRITATION TO THE UPPER RESPIRATORY TRACT.

INGESTION: IRRITATION & LOW TOXICITY.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:SKIN/EYE: IRRITATION. INHALATION: HEADACHE,  
NAUSEA, & IRRITATION TO THE UPPER RESPIRATORY TRACT. INGESTION: LOW  
TOXICITY & IRRITATION.

## First Aid

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN:  
WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR.  
GIVE CPR OR OXYGEN IF NEEDED. INGESTION: DRINK 1 OR 2 GLASSES OF  
WATER & INDUCE VOMITING BY PLACING FINGER AT BACK OF THROAT. NEVER  
GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. OBTAIN MEDICAL  
ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point:>200F  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN  
EXPOSED TO EXTREME HEAT. COMBUSTIBLE LIQUID CLASS III B.

## Accidental Release

Spill Release Procedures:SOAK UP & REMOVE W/INERT ABSORBENT MATERIAL.  
PROVIDE ADEQUATE VENTILATION.

## Handling

Handling and Storage Precautions:KEEP FROM FREEZING. AVOID CONTACT  
W/SKIN & BREATHING OF SPRAY MIST. KEEP OUT OF REACH OF CHILDREN.  
DON'T INGEST.

## Exposure Controls

Respiratory Protection:USE APPROVED MECHANICAL RESPIRATOR OR MASK TO  
AVOID BREATHING SPRAY MIST.  
Ventilation:PROVIDE SUFFICIENT VENTILATION IN VOLUME & PATTERN TO KEEP  
Protective Gloves:AS REQUIRED  
Eye Protection:GOGGLES, SAFETY GLASSES W/SIDE SHIELDS  
Other Protective Equipment:PROTECTIVE OVERALLS.  
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE. DISCARD CONTAMINATED SHOES.  
Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:212F  
Vapor Pres:0.01  
Vapor Density:Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:69.8%

## Stability

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:EXTREME HEAT & FREEZING.  
Hazardous Decomposition Products:FUMES, CO, CO2, & NITROGEN DIOXIDE.

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, &  
FEDERAL REGULATIONS. DON'T INCINERATE IN CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.