

263 HENRY ALL WEATHER OUTDOOR CARPET ADHESIVE, 3 1/2 GALLON

MSDS Number

BKGHH

National Stock Number

8040-00F016342

Product Name

263 HENRY ALL WEATHER OUTDOOR CARPET ADHESIVE, 3 1/2 GALLON

Manufacturer

W W HENRY COMPANY

Product Identification

Product ID:263 HENRY ALL WEATHER OUTDOOR CARPET ADHESIVE, 3 1/2 GALLON

MSDS Date:02/01/1988

FSC:8040

NIIN:00F016342

MSDS Number: BKGHH

Responsible Party

W.W. HENRY COMPANY

5608 SOTO STREET

HUNTINGTON PARK , CA 90255

Emergency Phone: (213) 583-4961

Info Phone: (213) 583-4961

Cage: FO818

Contractor

W.W. HENRY COMPANY

3001

HUNTINGTON PARK, CA 90255

US

(213) 583-4961

Cage: FO818

Ingredients

HEXANE (N-HEXANE)

CAS: 110-54-3

RTECS: MN9275000

Fraction By Weight: 18-25%

OSHA PEL500 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

BENZIN, NAPHTHA, MINERAL SPIRITS, PETROLEUM NAPHTHA

CAS: 8030-30-6

RTECS: DE3030000

Fraction By Weight: 10-14%

OSHA PEL500 PPM

ACGIH TLV: 300 PPM

396 - 400 G/L

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: WATERING & DISTRESS. SKIN: IRRITATION & DERMATITIS. INHALATION: HARMFUL/FATAL, HEADACHES, DIZZINESS, ASPHYXIA, NOSE, THROAT, & LUNG DISTRESS, PERMANENT BRAIN & NERVOUS SYSTEMDAMAGE. INGESTION: H ARMFUL

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES: WATERING & DISTRESS. SKIN: IRRITATION & DERMATITIS. INHALATION: HARMFUL, FATAL, HEADACHES, DIZZINESS, ASPHYXIA, NOSE, THROAT, LUNG DISTRESS, PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INGESTION: H ARMFUL

Medical Cond Aggravated by Exposure:CURRENT ANEMIA, RESPIRATORY TRACT OR LIVER AILMENTS & SKIN CONDITIONS.

First Aid

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR 15 MIN. SKIN: WASH THOROUGHLY W/SOAP & WATER OR HAND CLEANER. INHALATION: REMOVE TO FRESH AIR & APPLY ARTIFICIAL RESPIRATION IF NEEDED. INGESTION: OBTAIN MEDICAL ATTE NTION IN ALL CASES.

Fire Fighting

Flash Point:Lower Limits:1%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, OR WATER FOG.

Unusual Fire/Explosion Hazard:VAPORS >AIR MAY TRAVEL DISTANCE, IGNITE EXPLOSIVELY/FLASH FIRE IF ALLOWED TO COLLECT/CONCENTRATE. CLOSED CONTAINERS PRESSURIZE/ERUPT WHEN HEATED. FLAMMABLE.

Accidental Release

Spill Release Procedures:REMOVE OR EXTINGUISH ALL SOURCES OF IGNITION IN THE AREA, INCLUDING EQUIPMENT WHICH MAY SPARK. SCOOP MATERIAL INTO APPROVED DOT CONTAINER & REMOVE TO SAFE PLACE WHERE MATERIAL CAN DRY.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT/SPARKS/FLAMES/IGNITION SOURCES/CHILDREN/SWITCHES/FANS/TOOLS. USE AS DIRECTED ON LABEL. DON'T SMOKE. USE OUTDOORS ONLY.

Other Precautions:CLOSE CONTAINER AFTER EACH USE. DON'T RE-USE CONTAINER OR USE INDOORS DON'T USE OVER ROOFING ASPHALT OR PLANK DECKING. A SOLVENT ODOR IS NOTED UNTIL ADHESIVE DRIES. TURN OFF ELECTRICAL/GAS APPLIANCES/ WATER HEATER. AVOID SPLASHING.

Exposure Controls

Respiratory Protection:OUTDOOR FRESH AIR CROSS VENTILATION NORMALLY SUFFICIENT. PROVIDE FRESH AIR SUPPLY IF NECESSARY. WEAR NIOSH APPROVED RESPIRATORY EQUIPMENT, OR LEAVE AREA.

Ventilation:PROVIDE ADEQUATE FRESH AIR CROSS VENTILATION.

Protective Gloves:RECOMMENDED

Eye Protection:GLASSES W/SPLASH SHIELDS

Other Protective Equipment:AS REQUIRED

Work Hygienic Practices:WASH HANDS THOROUGHLY W/SOAP & WATER AFTER HANDLING.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:150-220F

Vapor Pres:100
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:TAN W/SOLVENT ODOR
Percent Volatiles by Volume:50-55%

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME, PILOT LIGHTS, &
ALL OTHER SOURCES OF IGNITION.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, &
FEDERAL REGULATIONS. DON'T FLUSH ADHESIVE DOWN DRAINS. FLAMMABLE,
DOT UN1133.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.