

## **R 150 STRIP-X PLUS**

### **MSDS Number**

BKGZD

### **National Stock Number**

6850-00F016644

### **Product Name**

R 150 STRIP-X PLUS

### **Manufacturer**

CERTIFIED COATINGS PRODUCTS CO

### **Product Identification**

Product ID: R 150 STRIP-X PLUS

MSDS Date: 02/01/1985

FSC: 6850

NIIN: 00F016644

MSDS Number: BKGZD

### **Responsible Party**

CERTIFIED COATINGS PRODUCTS CO

2414 S CONNOR AVE

LOS ANGELES , CA 90040

Emergency Phone: (213) 263-6884

Info Phone: (213) 263-6884

Cage: 99522

### **Contractor**

CERTIFIED COATINGS PRODUCTS CO

LOS ANGELES, CA 90040

(213) 263-6884

Cage: 99522

### **Ingredients**

THICKENING AGENT

Fraction By Weight: 1%

METHYLENE CHLORIDE (SARA III)

CAS: 75-09-2

RTECS: PA8050000

Fraction By Weight: 89.1%

OSHA PEL500 PPM/C,1000; Z2

ACGIH TLV: 50 PPM, A2; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ALCOHOL (METHANOL) (SARA III)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight: 19.8%

OSHA PELS,200PPM/250STEL

ACGIH TLV: S,200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:INHALATION: HEADACHE, DIZZINESS, STUPOR, NAUSEA, & VOMITING. SKIN: IRRITATION, BURNING SENSATION, & REDNESS. EYE: IRRITATION, PAIN, LACRIMATION, & GENERAL INFLAMMATION. INGESTION: IRRITATION.

Explanation of Carcinogenicity:METHYLENE CHLORIDE IS A SUSPECTED A2 CARCINOGEN BY ACGIH.

Effects of Overexposure:INHALATION: HEADACHE, DIZZINESS, NAUSEA, & VOMITING. SKIN: IRRITATION, BURNING SENSATION, & REDNESS. EYE: IRRITATION, PAIN, LACRIMATION, & GENERAL INFLAMMATION. INGESTION: IRRITATION.

## First Aid

First Aid:EYES/SKIN: FLUSH W/PLENTY OF WATER. INHALATION: REMOVE TO FRESH AIR. KEEP QUIET & WARM. INGESTION: INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point:NONE

## Accidental Release

Spill Release Procedures:SMALL: MOP UP, WIPE UP OR SOAK UP IMMEDIATELY. REMOVE TO OUT DOORS. LARGE: EVACUATE AREA. CONTAIN LIQUID. TRANSFER TO CLOSED METAL CONTAINERS.

## Handling

Handling and Storage Precautions:AVOID EXPOSURE TO SUN & HEAT.

## Exposure Controls

Respiratory Protection:UNDER NORMAL CONDITIONS, NONE REQUIRED.

Ventilation:LOCAL EXHAUST: RECOMMENDED

Protective Gloves:SOLVENT RESISTANT

Eye Protection:SAFETY GLASSES

Other Protective Equipment:LONG SLEEVE CLOTHING

Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:104F

Vapor Pres:340

Vapor Density:2.80

Spec Gravity:1.2

Solubility in Water:SLIGHT

Appearance and Odor:WATER WHITE W/MILD ODOR.

Percent Volatiles by Volume:99%

## Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:SUN & HEAT

## Disposal

Waste Disposal Methods:IN SOME CASES MATERIAL CAN BE TRANSPORTED TO AN AREA, PLACED ON THE GROUND & ALLOWED TO EVAPORATE SAFELY. KEEP OUT OF WATER SUPPLY. DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.