

AA1550 WAX, PASTE, TYPE II

MSDS Number

BKJHL

National Stock Number

7930-00-266-7128

Product Name

AA1550 WAX, PASTE, TYPE II

Manufacturer

INDUSTRIAL FLOOR FINISHES

Product Identification

Product ID:AA1550 WAX, PASTE, TYPE II

MSDS Date:01/21/1991

FSC:7930

NIIN:00-266-7128

MSDS Number: BKJHL

Responsible Party

INDUSTRIAL FLOOR FINISHES

605 SPRINGS ROAD

BEDFORD , MA 01730

US

Emergency Phone: 800-255-3924

Info Phone: 508-667-5161

Preparer: T. PITROLFFY

Cage: 0J4J4

Contractor

PERMA, INCORPORATED

BEDFORD, MA 01730

US

978-667-5161

Cage: 0J4J4

Ingredients

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight:

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO

Health Hazards Acute and Chronic:ACUTE: SEVERE EYE IRRITATION, DRYING OF SKIN, DIZZINESS, NAUSEA. VAPORS MAY BE NARCOTIC. CHRONIC: RESPIRATORY TRACT IRRITATION, COULD DAMAGE LIVER AND KIDNEY.

Effects of Overexposure:IRRITATION AND REDNESS OF SKIN, DIZZY FEELING, PALE AND NAUSEOUS.

Medical Cond Aggravated by Exposure:KIDNEY, LIVER AND LUNG PROBLEMS.

First Aid

First Aid:EYE & SKIN CONTACT: FLUSH WITH PLENTY OF WATER. INHALATION: REMOVE TO FRESH AIR, BEGIN ARTIFICIAL RESPIRATION IF NEEDED. INGESTION: DO NOT INDUCE VOMITING, GET IMMEDIATE MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:TCC
Flash Point:103F,39C
Autoignition Temp:Autoignition Temp Text:510F
Lower Limits:0.7
Upper Limits:6.0
Extinguishing Media:CO2, FOAM, DRY CHEMICAL.
Fire Fighting Procedures:COOL CONTAINERS WITH WATER, USE SELF-CONTAINED BREATHING APPARATUS, BURNING PRODUCT IS TOXIC.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY BURST WHEN EXPOSED TO EXTREME HEAT. ISOLATE FROM HEAT, SPARKS, OPEN FLAME.

Accidental Release

Spill Release Procedures:COLLECT MATERIAL INTO METAL CONTAINER. AVOID SPARKS, FLAME AND HOT SURFACES. WIPE OFF RESIDUE WITH RAG.

Handling

Handling and Storage Precautions:COMBUSTIBLE, KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. USE ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED CONTACT. KEEP CONTAINERS CLOSED.
Other Precautions:STORE IN SECURE AREA. DISPOSE OF EMPTY CONTAINERS SAFELY. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:USE SELF-CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE THRESHOLD LIMIT VALUE.
Ventilation:LOCAL EXHAUST-RECOMMENDED. MECHANICAL-ASSURE FRESH AIR CIRCULATION.
Protective Gloves:RECOMMENDED: RUBBER.
Eye Protection:RECOMMENDED: GOGGLES.
Work Hygienic Practices:DO NOT EAT, DRINK OR SMOKE NEXT TO MATERIAL. WASH HANDS AND FACE AFTER WORK.
Supplemental Safety and Health

Chemical Properties

HCC:F8
Boiling Pt:B.P. Text:320F,160C
Melt/Freeze Pt:M.P/F.P Text:130F,54C
Vapor Pres:2.0
Vapor Density:4.7
Spec Gravity:0.8
Evaporation Rate & Reference:0.21 (BUAC=1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:WAXY PASTE, SOLVENT ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME.
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE.

Disposal

Waste Disposal Methods:RECYCLE, INCINERATE OR USE HAZARDOUS WASTE MANAGEMENT FACILITY FOR DISPOSAL ACCORDING TO STATE AND FEDERAL REGULATIONS. EPA WASTE NO. D001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.