

## **PROCESS 92EBXJ ELECTROLYTIC (SEE SUPP DATA)**

### **MSDS Number**

BKKNT

### **National Stock Number**

6750-00N014105

### **Product Name**

PROCESS 92EBXJ ELECTROLYTIC (SEE SUPP DATA)

### **Manufacturer**

AGFA CORP

### **Product Identification**

Product ID:PROCESS 92EBXJ ELECTROLYTIC (SEE SUPP DATA)

MSDS Date:04/01/1988

FSC:6750

NIIN:00N014105

Kit Part:Y

MSDS Number: BKKNT

### **Responsible Party**

AGFA CORPORATION

100 CHALLENGER RD

RIDGEFIELD PARK , NJ 07660

US

Emergency Phone: 303-623-5716;800-424-9300(CHEMTREC)

Info Phone: 201-440-2500

Cage: HO792

### **Contractor**

BAYER CORP / AGFA DIVISION

RIDGEFIELD, NJ 07660

US

201-440-2500

Cage: 59735

### **Ingredients**

THIOSULFURIC ACID, DIAMMONIUM SALT (AMMONIUM THIOSULFATE)

CAS: 7783-18-8

RTECS: XN6465000

Fraction By Weight: 30-35%

1)

CAS: 7757-83-7

RTECS: WE2150000

Fraction By Weight: 15-20%

ETHYLENEDIAMINE-TETRAACETIC ACID (EDTA) (SARA III)

CAS: 60-00-4

RTECS: AH4025000

Fraction By Weight: 1-5%

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

## Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:EYE/SKIN:MAY CAUSE IRRITATION.

INHAL:NORMALLY NO PROBLEM, BUT INHALATION OF MIST COULD CAUSE RESPIRATORY IRRITATION. INGEST:MAY CAUSE IRRITATION OF MUCOUS MEMBRANES OR DIGESTIVE TRACT. CHRONIC:N O EFFECTS ASSOCIATED WITH THESE MATERIALS.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

## First Aid

First Aid:EYES:IMMEDIATELY FLUSH W/PLENTY OF RUNNING WATER FOR AT LEAST 15 MINUTES. CALL MD. SKIN:FLUSH AFFECTED AREAS PROMPTLY W/WATER FOR 15 MINUTES. REMOVE CONTAMINATED CLOTHING. IN CASE CONTINUED IRRITATION CALL MD. INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O\*2/ARTIFICIAL RESPIRATION) . INGEST:CALL MD IMMEDIATELY.

## Fire Fighting

Flash Point:NONCOMBUSTIBLE

Extinguishing Media:ANY APPLICABLE TO PRIMARY CAUSE OF FIRE.

Fire Fighting Procedures:EVACUATE PERSONNEL TO SAFE AREA. KEEP PERSONNEL REMOVED & UPWIND OF FIRE. WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:WHEN HEATED TO DECOMPOSITION EMISSION OF TOXIC FUMES OF SO\*2 IS POSSIBLE.

## Accidental Release

Spill Release Procedures:USE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT DURING CLEAN UP. DIKE SPILL. PVNT LIQUID FROM ENTERING SEWERS, WATERWAYS OR LOW AREAS. SOAK UP W/SAWDUST, SAND, OIL DRY OR OTHER ABSORBENT MATERIAL.

Neutralizing Agent:POWDERED SODIUM CARBONATE.

## Handling

Handling and Storage Precautions:STORE IN WELL VENT AREA. KEEP CNTNR TIGHTLY CLOSED. DO NOT STORE W/INCOMPATIBLE MATLS. DO NOT STORE OR CONSUME FOOD, DRINK OR TOBACCO (SEE SUPP DATA)

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

## Exposure Controls

Respiratory Protection:NONE NEEDED W/WORKING MIXTURES & NORMAL ROOM VENTILATION. IF NEEDED, USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:ROOM VENTILATION IS SUFFICIENT. AVOID USE OF PRODUCT IN UNVENTILATED AREAS.

Protective Gloves:CHEMICAL GLOVES.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:CHEMICAL RESISTANT APRONS.

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE AND BEFORE EATING, SMOKING OR USING SANITARY FACILITIES .

Supplemental Safety and Health

MFR TRADE NAME/PART NO:BLEACH-FIX REJUVENATOR PART B. WASTE DISP:AUTHORITY AND MAY REQUIRE PRETREATMENT. DISPOSE OF I/A/W FEDERAL, STATE AND LOCAL REGULATIONS . HNDLG/STOR PREC:IN AREA WHERE THE Y MAY BECOME CONTAMINATED W/THIS MATERIAL.

## Chemical Properties

HCC:N1  
Boiling Pt:B.P. Text:212F,100C  
Vapor Pres:21.07  
Vapor Density:SAME/WATER  
Spec Gravity:1.290  
pH:5.40  
Evaporation Rate & Reference:0.3 (N-BUTYL ACETATE = 1)  
Solubility in Water:100%  
Appearance and Odor:CLEAR, COLORLESS, SLIGHT AMMONIA ODOR.

## Stability

Stability Indicator/Materials to Avoid:YES  
ALKALI, STRONG ACIDS, OXIDIZERS.  
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.  
Hazardous Decomposition Products:SO\*X, CO\*2, CARBON MONOXIDE, AMMONIA.

## Disposal

Waste Disposal Methods:RECOVER NONUSABLE FREE LIQ &/OR CONTAM WATER &  
DISPOSE OF IN APPRVD/PERMITTED TREATMENT SYS. REMOVE NONUSABLE  
SOLID MATL &/OR CONTAM SOIL FOR DISPOSAL IN APPRVD/PERMITTED  
LANDFILL. DISCHARGE TO SEWER REQUIRES APPROVAL OF PERMITTING (SEE  
SUPP DATA)

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.