

AEROSOL SPRAY - AQUALYTE LINE #3330 ORANGE

MSDS Number

BKPLN

National Stock Number

8010-00B130059

Product Name

AEROSOL SPRAY - AQUALYTE LINE #3330 ORANGE

Manufacturer

MAJOR PAINT COMPANY

Product Identification

Product ID:AEROSOL SPRAY - AQUALYTE LINE #3330 ORANGE MSDS Date:12/01/1990 FSC:8010 NIIN:00B130059

MSDS Number: BKPLN **Responsible Party**

MAJOR PAINT COMPANY

4300 W. 190TH STREET

TORRANCE, CA 90509-2868

US

Emergency Phone: 213-542-7701/800-424-9300 TRANS.

Info Phone: 213-542-7701 PRODUCT INFO.

Cage: MAJOR
Contractor

MAJOR PAINT COMPANY

2868

TORRANCE, CA 90509-2868 US

310-542-7701 Cage: MAJOR

Ingredients

DIMETHYL ETHER
CAS: 115-10-6
RTECS: PM4780000

HANSA YELLOW

ORGANIC ORANGE

AMMONIUM HYDROXIDE, WITH < 12% AMMONIA

CAS: 1336-21-6 RTECS: BQ9625800



EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

PROPYLENE GLYCOL MONOMETHYL ETHER

CAS: 107-98-2

RTECS: UB7700000

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:EXCESSIVE VAPOR.R MISTS MAY CAUSE
IRRITATION OF NOSE AND THROAT CAUSING DIZZINESS, DROSINESS,
FATIGUE, OR LOSS OF COORDINATION. CAN CAUSE DEFATTING AND
DERMATITIS OF THE SKIN. MAY CAUSE MINOR GASTROIN TESTINAL
DISCOMFORT; DROWSINESS, DIZZINESS, OR FATIGUE. MAY CAUSE EYE
IRRITATION IF VAPORS PRESENT IN EXCESSIVE AMOUNT
Effects of Overexposure:INGESTION CAUSES DROWSINESS, INCOORDINATION,
NAUSEA, VOMITING, AND BREATHING DIFFICULTIES. NO ADVERSE EFFECTS
ARE EXPECTED FROM BRIEF EXPOSURE THROUGH SKIN. INHALATION WILL
CAUSE NOSE, THROAT AND RESP IRATORY TRACT IRRITATION AND POSSIBLE
NAUSEA, VOMITING, HEADACHE, DIZZINESS, DROWSINESS AND
INCOORDINATION.

Medical Cond Aggravated by Exposure: PERSONS WITH A HISTORY OF RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid

First Aid:SKIN/EYE CONTACT: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MIN., CALL A PHYSICIAN. INGESTION: CALL A PHYSICIAN IMMEDIATELY AND HAVE NAMES OF INGREDIENTS AVAILABLE. DO NOT INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR. RESTORE/SUPPORT BREATHING IF NECESSARY. IF BREATHING DIFFICULTY PERSISTS, OR OCCURRS LATER, CONSULT A PHYSICIAN.

Fire Fighting

Flash Point Method:TCC Flash Point:13F,-11C

Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures: FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS, IS RECOMMENDED. WATER MAY BE INEFFECTIVE, BUT USED TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard: CONTENTS UNDER PRESSURE. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO SUNLIGHT OR OTHER HEAT MAY CAUSE CANS TO BURSE, PROPELLING CONTENTS ACROSS AREA.

Accidental Release

Spill Release Procedures: VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. PREVENT SKIN CONTACT AND BREATHING OF VAPORS. CONFINE AND REMOVE WITH INERT ABSORBENT.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: OBSERVE LABEL PRECAUTIONS. KEEP AWAY



FROM HEAT, SPARKS AND FLAME. DO NOT STORE ABOVE 120F. DO NOT EXPOSE TO DIRECT SUNLIGHT.

Other Precautions: WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING AND SMOKING. DO NOT SAND, FLAME CUT, BRAZE OR WELD DRY COATING WITHOUT NIOSH/ MSHA APPROVED RESPIRATOR OR APPROPRIATE VENTILATION. DO NOT PUNCTURE. DO NOT SPRAY NEAR FIRE OR OPEN FLAME.

Exposure Controls

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR. Ventilation:PROVIDE SUFFICIENT VENTILATION IN VOLUME AND PATTERN TO KEEP CONTAMINANTS BELOW APPLICABLE OSHA REQUIREMENTS.

Protective Gloves: NEOPRENE GLOVES

Eye Protection: GOGGLES, SAFETY GLASSES W/SPLASH GUARDS.

Other Protective Equipment: COVERALLS.

Work Hygienic Practices: PROTECTIVE CREAMS MAY BE USED FOR EASE OF CLEAN- UP, NOT FOR PROTECTION. WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. EYE WATERING, HEADACHES, NAUSEA, DIZZINESS, AND LOSS OF COORDINATION ARE SIGNS T HAT SOLVENT LEVELS ARE TOO HIGH.

Chemical Properties

HCC:V3

Boiling Pt:B.P. Text:Vapor Density:>AIR

Evaporation Rate & Reference: FASTER THAN ETHER

Solubility in Water: MODERATE

Appearance and Odor: NOT SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:92%

Stability

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid:DO NOT STORE ABOVE 120F. Hazardous Decomposition Products:CO, CO2, SMOKE, OXIDES OF HEAVY METALS.

Disposal

Waste Disposal Methods: DO NOT ALLOW MATERIAL TO CONTAMINATE GROUND WATER SYSTEMS. INCINERATE ABSORBED MATERIAL IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.