

AEROSOL SPRAY - AQUALYTE LINE #3332 FLAT WH

MSDS Number

BKPLQ

National Stock Number

8010-00B130061

Product Name

AEROSOL SPRAY - AQUALYTE LINE #3332 FLAT WH

Manufacturer

MAJOR PAINT COMPANY

Product Identification

Product ID:AEROSOL SPRAY - AQUALYTE LINE #3332 FLAT WH MSDS Date:12/01/1990 FSC:8010 NIIN:00B130061 MSDS Number: BKPLQ

Responsible Party

MAJOR PAINT COMPANY

4300 W. 190TH STREET

TORRANCE , CA 90509-2868

US

Emergency Phone: 213-542-7701/800-424-9300 TRANS.

Info Phone: 213-542-7701

Cage: MAJOR

Contractor

MAJOR PAINT COMPANY

2868

TORRANCE, CA 90509-2868

US

310-542-7701

Cage: MAJOR

Ingredients

DIMETHYL ETHER CAS: 115-10-6 RTECS: PM4780000

TITANIUM DIOXIDE

CAS: 13463-67-7 RTECS: XR2275000 OSHA PEL15 MG/M3 TDUST ACGIH TLV: 10 MG/M3 TDUST; 9293

msds report

https://msdsreport.com/msds/BKPLQ

•

RTECS: BQ9625800 EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

PROPYLENE GLYCOL MONOMETHYL ETHER

CAS: 107-98-2

RTECS: UB7700000

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Health Hazards Acute and Chronic:CHRONIC: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Effects of Overexposure:INHALATION OVEREXPOSURE MAY CAUSE NOSE AND THROAT IRRITATION, CENTRAL NERVOUS SYSTEM EFFECTS, I.E., DIZZINESS, HEADACHE, NAUSEA, STAGGERING GAIT, CONFUSION AND UNCONSCIOUSNESS. INGESTION IS UNLIKELY. SKIN/EYE CONTACT MAY CAUSE IRRITATION. Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF SKIN AND RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid

First Aid:EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MIN. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. IF IRRITATION OCCURS, CONTACT A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. RESTORE/SUPP ORT BREATHING AS NECESSARY. IF BREATHING DIFFICULTY OCCURS OR PERSISTS, CONTACT A PHYSICIAN. INGESTION: IN THE UNLIKELY EVENT, DO NOT INDUCT VOMITING. CALL A PHYSICIAN WITH NAMES OF INGREDIENTS.

Fire Fighting

Flash Point Method:TCC

Flash Point:Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS, IS RECOMMENDED. WATER MAY BE IN-EFFECTIVE BUT USED TO COOL CLOSED CONTAINERS. Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO SUNLIGHT OR OTHER HEAT MAY CAUSE CANS TO BURST, PROPELLING CONTENTS ACROSS AREA.

Accidental Release

Spill Release Procedures: VENTILATE AREA. REMOVE SOURCES OF IGNITION. PREVENT SKIN CONTACT AND BREATHING OF VAPOR. CONFINE AND REMOVE WITH INERT ABSORBENT. DO NOT ALLOW MATERIAL TO CONTAMINATE GROUND WATER SYSTEMS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:OBSERVE LABEL PRECAUTIONS. KEEP AWAY FROM HEAT, SPARKS AND FLAME. DO NOT STORE ABOVE 120F. DO NOT EXPOSE TO DIRECT SUNLIGHT TO AVOID BURSTING.



Other Precautions: WASH THOROUGHLY AFTER HANDLING. DO NOT SAND, FLAME CUT, BRAZE OR WELD DRY COATING WITHOUT NIOSH/MSHA APPROVED RESPIRATOR OR APPROPRIATE VENTILATION. DO NOT PUNCTURE. DO NOT SPRAY NEAR FIRE OR OPEN FLA ME.

•

Exposure Controls

Respiratory Protection: IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR. Ventilation: PROVIDE SUFFICIENT VENTILATION IN VOLUME AND PATTERN TO KEEP CONTAMINANTS BELOW APPLICABLE OSHA REQUIREMENTS. Protective Gloves: NEOPRENE GLOVES. Eye Protection: GOGGLES, SAFETY GLASSES W/SPLASH GUARDS. Other Protective Equipment: COVERALLS. SHOWER AND EYE BATH. INDUSTRIAL TYPE WORK CLOTHING AND APRON AS REQUIRED TO AVOID PROLONGED/REPEATED CONTACT. Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

HCC:V3

Boiling Pt:B.P. Text: Evaporation Rate & Reference: FASTER THAN ETHER Solubility in Water: MODERATE Appearance and Odor: NOT SPECIFIED BY MANUFACTURER. Percent Volatiles by Volume: 92%

Stability

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid:DO NOT STORE ABOVE 120F. Hazardous Decomposition Products:CO, CO2, SMOKE, OXIDES OF HEAVY METALS.

Disposal

Waste Disposal Methods: INCINERATE ABSORBED MATERIAL OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.