

## **AEROSOL SPRAY - AQUALYTE LINE #3338 MEDIUM**

### **MSDS Number**

BKPLV

### **National Stock Number**

8010-00B130065

### **Product Name**

AEROSOL SPRAY - AQUALYTE LINE #3338 MEDIUM

### **Manufacturer**

MAJOR PAINT COMPANY

### **Product Identification**

Product ID:AEROSOL SPRAY - AQUALYTE LINE #3338 MEDIUM

MSDS Date:12/01/1990

FSC:8010

NIIN:00B130065

MSDS Number: BKPLV

### **Responsible Party**

MAJOR PAINT COMPANY

4300 W. 190TH STREET

TORRANCE , CA 90509-2868

Emergency Phone: 213-542-7701/800-424-9300 TRANS.

Info Phone: 213-542-7701

Cage: MAJOR

### **Contractor**

MAJOR PAINT COMPANY

2868

TORRANCE, CA 90509-2868

US

310-542-7701

Cage: MAJOR

### **Ingredients**

DIMETHYL ETHER

CAS: 115-10-6

RTECS: PM4780000

LIGHT LEMON YELLOW

TINTING BLACK

PHTHALO BLUE

AMMONIUM HYDROXIDE (AQUA AMMONIA)

CAS: 1336-21-6

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

GLYCOL ETHER PM

CAS: 107-98-2

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Health Hazards Acute and Chronic:CHRONIC: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Effects of Overexposure:INGESTION (UNLIKELY) GASTRO-INTESTINAL DISTRESS. INHALATION MAY CAUSE NOSE AND THROAT IRRITATION, CENTRAL NERVOUS SYSTEM EFFECTS I.E., DIZZINESS, HEADACHE, NAUSEA, STAGGERING GAIT,C ONFUSION AND UNCON SCIOUSNESS. SKIN CONTACT MAY CAUSE IRRITATION WITH DISCOMFORT AND DERMATITIS. EYE CONTACT MAY CAUSE EYE IRRITATION.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF SKIN AND RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

## First Aid

First Aid:EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. IF IRRITATION OCCURS, CONTACT A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. RESTORE/ SUPPORT BREATHING AS NECESSARY. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. HAVE PRODUCT INGREDIENTS AVAILABLE.

## Fire Fighting

Flash Point Method:TCC

Flash Point:Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS, IS RECOMMENDED. WATER MAY BE IN-EFFECTIVE BUT USED FOR COOLING CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO SUNLIGHT OR OTHER HEAT MAY CAUSE CANS TO BURSE, PROPELLING CONTENTS ACROSS AREA.

## Accidental Release

Spill Release Procedures:VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. PREVENT SKIN CONTACT AND BREATHING OF VAPORS. CONFINE AND REMOVE WITH INERT ABSORBENT. DO NOT ALLOW TO CONTAMINATE GROUND WATER SYSTEMS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS AND FLAME. DO NOT STORE ABOVE 120F. DO NOT EXPOSE TO DIRECT SUNLIGHT TO AVOID BURSTING. OBSERVE LABEL PRECAUTIONS.

Other Precautions:WASH THOROUGHLY AFTER HANDLING. DO NOT SAND, FLAME CUT, BRAZE OR WELD DRY COATING WITHOUT NIOSH/MSHA APPROVED RESPIRATOR OR APPROPRIATE VENTILATION. DO NOT PUNCTURE. DO NOT SPRAY NEAR FIRE OR OPEN FLA ME.

## Exposure Controls

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR.  
Ventilation:PROVIDE SUFFICIENT VENTILATION IN VOLUME AND PATTERN TO KEEP CONTAMINANTS BELOW APPLICABLE OSHA REQUIREMENTS.  
Protective Gloves:NEOPRENE GLOVES  
Eye Protection:GOGGLES, SAFETY GLASSES W/SPLASH GUARDS.  
Other Protective Equipment:SAFETY SHOWER AND EYE BATH. INDUSTRIAL TYPE WORK CLOTHING AND APRON AS REQUIRED TO AVOID PROLONGED OR REPEATED CONTACT.  
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.  
Supplemental Safety and Health  
NONE SPECIFIED BY MANUFACTURER.

## Chemical Properties

HCC:V3  
Boiling Pt:B.P. Text:Evaporation Rate & Reference:FASTER THAN ETHER  
Solubility in Water:MODERATE  
Appearance and Odor:NOT SPECIFIED BY MANUFACTURER.  
Percent Volatiles by Volume:92%

## Stability

Stability Indicator/Materials to Avoid:YES  
NONE SPECIFIED BY MANUFACTURER.  
Stability Condition to Avoid:DO NOT STORE ABOVE 120F.  
Hazardous Decomposition Products:CO, CO2, SMOKE, OXIDES OF HEAVY METALS.

## Disposal

Waste Disposal Methods:INCINERATE ABSORBED MATERIAL IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.