

V-108 SERIES STAINSEAL

MSDS Number

BKTPY

National Stock Number

8010-00F016898

Product Name

V-108 SERIES STAINSEAL

Manufacturer

DUNN EDWARDS CORP

Product Identification

Product ID:V-108 SERIES STAINSEAL

MSDS Date:06/16/1986

FSC:8010

NIIN:00F016898

MSDS Number: BKTPY

Responsible Party

DUNN-EDWARDS CORPORATION

4885 E 52ND PLACE

LOS ANGELES , CA 90040

Emergency Phone: (213) 771-3330 EXT 2341

Info Phone: (213) 771-3330 EXT 2340

Cage: 34483

Contractor

DUNN-EDWARDS CORPORATION

LOS ANGELES, CA 90040-2828

US

213-771-3330 EXT 2240

Cage: 34483

Ingredients

HYDROTREATED LIGHT DISTILLATE, PETROLEUM; C12-C15

CAS: 64742-47-8

Fraction By Weight: 60%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight:

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight:

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ETHYL ALCOHOL (ETHANOL)

CAS: 64-17-5

RTECS: KQ6300000

Fraction By Weight:

OSHA PEL1000 PPM

ACGIH TLV: 1000 PPM; 9192

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: DEFATTING, DRYING, IRRITATION, & DERMATITIS. INHALATION: MUCOUS MEMBRANES IRRITATION, HEADACHES, DIZZINESS, NAUSEA, LOSS OF CONSCIOUSNESS/COORDINATION, & CENTRAL NERVOUS SYSTEM DEPRESSION. INGESTION: CHEMICAL PNEUMONITIS & PULMONARY EDEMA/HEMORRHAGE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES: IRRITATION. SKIN: DEFATTING, DRYING, IRRITATION, & DERMATITIS. INHALATION: MUCOUS MEMBRANES IRRITATION, HEADACHES, DIZZINESS, NAUSEA, LOSS OF CONSCIOUSNESS/COORDINATION, & CENTRAL NERVOUS SYSTEM DEPRESSION. INGESTION: CHEMICAL PNEUMONITIS & PULMONARY EDEMA/HEMORRHAGE.

First Aid

First Aid:EYES: WASH W/FRESH WATER FOR AT LEAST 15 MINS. SKIN: WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR IF NEEDED. INGESTION: DON'T INDUCE VOMITING. MAY CAUSE CHEMICAL PNEUMONITIS & PULMONARY EDEMA/HEMORRHAGE. OBTAINMEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TCC

Flash Point:105F

Lower Limits:1%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, & WATER FOG.

Fire Fighting Procedures:USE AIR SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREAS. AVOID SPREADING BURNING LIQUID W/WATER USED FOR COOLING PURPOSES.

Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID CLASS II. LIQUID EVAPORATES & FORMS INVISIBLE VAPORS WHICH SPREAD & IGNITE BY IGNITION SOURCES. HAZARD IS GREATER AS LIQUID TEMP RISES >85F.

Accidental Release

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. VENTILATE CONFINED SPACES. EVACUATE AREA. ADD ABSORBENT SUCH AS SAND, EARTH, SAWDUST & RECOVER INTO A SUITABLE CONTAINER.

Handling

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DON'T HANDLE OR STORE NEAR HEAT, FLAMES, SPARKS, & STRONG OXIDANTS. STORE IN COOL WELL VENTILATED AREA.
Other Precautions:AVOID BREATHING VAPORS & CONTACT W/SKIN. ROTATE STOCK USE OLDER MATERIAL FIRST. INSPECT FOR LEAKY CONTAINERS.

Exposure Controls

Respiratory Protection:WEAR APPROVED ORGANIC VAPOR RESPIRATOR OR AN AIR SUPPLYING RESPIRATOR UNLESS VENTILATION EQUIPMENT IS ADEQUATE TO KEEP EXTREME CASES.

Ventilation:PROVIDE SUFFICIENT GENERAL MECHANICAL VENTILATION TO KEEP

Protective Gloves:IMPERMEABLE SOLVENT RESISTANT

Eye Protection:CHEMICAL SAFETY GLASSES, GOGGLES

Other Protective Equipment:FACE SHIELDS, IMPERMEABLE APRONS, PROTECTIVE CLOTHING, HEAD CAPS, EYE WASHES, & SAFETY SHOWERS.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:314-387F

Vapor Pres:5

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:LIQUID

Percent Volatiles by Volume:80%

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS, WILL DISSOLVE & SOFTEN SOME RUBBER & PLASTICS.

Stability Condition to Avoid:IGNITION SOURCES AS HEAT/HIGH TEMP/POORLY VENTED HOT AREAS/FLAME/SPARK/PILOT LIGHTS/WELDING EQUIP/ELECT MOTORS/SWITCHES.

Hazardous Decomposition Products:CO₂, CO, ACROLEIN, SMOKE & ACRID FUME.

Disposal

Waste Disposal Methods:DISPOSE OF SPILLED & ABSORBENT ACCORDING TO LOCAL, STATE, & FEDERAL REGULATIONS. DON'T DUMP INTO LAKES, STREAM OR OTHER WATER SUPPLY. CONSULT W/HAZARDOUS WASTE REGULATIONS REGARDING LANDFILL DUMPING & /OR INCINERATION. COMBUSTIBLE LIQUID CLASS II.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.