

V 188 LOGWOOD OIL, GLOSS

MSDS Number

BKTSY

National Stock Number

8010-00F016961

Product Name

V 188 LOGWOOD OIL, GLOSS

Manufacturer

DUNN EDWARDS CORP

Product Identification

Product ID:V 188 LOGWOOD OIL, GLOSS

MSDS Date:06/12/1986

FSC:8010

NIIN:00F016961

MSDS Number: BKTSY

Responsible Party

DUNN-EDWARDS CORPORATION

4885 E 52ND PLACE

LOS ANGELES , CA 90040

Emergency Phone: (213) 771-3330 EXT 2341

Info Phone: (213) 771-3330 EXT 2340

Cage: 34483

Contractor

DUNN-EDWARDS CORPORATION

LOS ANGELES, CA 90040-2828

US

213-771-3330 EXT 2240

Cage: 34483

Ingredients

HYDROTREATED LIGHT DISTILLATE, PETROLEUM; C12-C15

CAS: 64742-47-8

Fraction By Weight: 50%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight:

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ISOPARAFFINIC HYDROCARBONS (NAPHTHA PETROLEUM),

CAS: 64742-48-9

Fraction By Weight:

ACGIH TLV: 200 PPM

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: DEFATTING, DRYING, IRRITATION, & DERMATITIS. INHALATION: MUCOUS MEMBRANES IRRITATION, HEADACHES, DIZZINESS, NAUSEA, LOSS OF CONSCIOUSNESS/COORDINATION, & CENTRAL NERVOUS SYSTEM DEPRESSION. INGESTION: CHEMICAL PNEUMONITIS & PULMONARY EDEMA/HEMORRHAGE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES: IRRITATION. SKIN: DEFATTING, DRYING, IRRITATION, & DERMATITIS. INHALATION: MUCOUS MEMBRANES IRRITATION, HEADACHES, DIZZINESS, NAUSEA, LOSS OF CONSCIOUSNESS/COORDINATION, & CENTRAL NERVOUS SYSTEM DEPRESSION. INGESTION: CHEMICAL PNEUMONITIS & PULMONARY EDEMA/HEMORRHAGE.

First Aid

First Aid:EYES: WASH W/FRESH WATER FOR AT LEAST 15 MINS. SKIN: WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR IF NEEDED. INGESTION: DON'T INDUCE VOMITING. MAY CAUSE CHEMICAL PNEUMONITIS & PULMONARY EDEMA/HEMORRHAGE. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TCC

Flash Point:105F

Lower Limits:1%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, & WATER FOG.

Fire Fighting Procedures:USE AIR SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREAS. AVOID SPREADING BURNING LIQUID W/WATER USED FOR COOLING PURPOSES.

Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID CLASS II. LIQUID EVAPORATES & FORMS INVISIBLE VAPORS WHICH SPREAD & IGNITE BY IGNITION SOURCES. HAZARD IS GREATER AS LIQUID TEMP RISES >85F.

Accidental Release

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. VENTILATE CONFINED SPACES. EVACUATE AREA. ADD ABSORBENT SUCH AS SAND, EARTH, SAWDUST & RECOVER INTO A SUITABLE CONTAINER.

Handling

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DON'T HANDLE OR STORE NEAR HEAT, FLAMES, SPARKS, & STRONG OXIDANTS. STORE IN COOL WELL VENTILATED AREA.

Other Precautions:AVOID BREATHING VAPORS & CONTACT W/SKIN. ROTATE STOCK USE OLDER MATERIAL FIRST. INSPECT FOR LEAKY CONTAINERS. PRODUCT WILL DISSOLVE & SOFTEN SOME RUBBER & PLASTICS.

Exposure Controls

Respiratory Protection:WEAR APPROVED ORGANIC VAPOR RESPIRATOR OR AN AIR SUPPLYING RESPIRATOR UNLESS VENTILATION EQUIPMENT IS ADEQUATE TO KEEP EXTREME CASES.

Ventilation:PROVIDE SUFFICIENT GENERAL MECHANICAL VENTILATION TO KEEP

Protective Gloves:IMPERMEABLE SOLVENT RESISTANT

Eye Protection:CHEMICAL SAFETY GLASSES, GOGGLES

Other Protective Equipment:FACE SHIELDS, IMPERMEABLE APRONS, PROTECTIVE CLOTHING, HEAD CAPS, EYE WASHES, & SAFETY SHOWERS.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:314-387F
Vapor Pres:5
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:LIQUID
Percent Volatiles by Volume:61.25%

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS
Stability Condition to Avoid:IGNITION SOURCES AS HEAT/HIGH TEMP/POORLY
VENTED HOT AREAS/FLAME/SPARK/PILOT LIGHTS/WELDING EQUIP/ELECT
MOTORS/SWITCHES.
Hazardous Decomposition Products:CO₂, CO, ACROLEIN, SMOKE & ACRID FUME.

Disposal

Waste Disposal Methods:DISPOSE OF SPILLED & ABSORBENT ACCORDING TO
LOCAL, STATE, & FEDERAL REGULATIONS. DON'T DUMP INTO LAKES, STREAM
OR OTHER WATER SUPPLY. CONSULT W/HAZARDOUS WASTE REGULATIONS
REGARDING LANDFILL DUMPING & /OR INCINERATION. COMBUSTIBLE LIQUID
CLASS II.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.