

9127 METHANOL CAPILLARY ANALYZED

MSDS Number

BKTVX

National Stock Number

6810-00F016999

Product Name

9127 METHANOL CAPILLARY ANALYZED

Manufacturer

J T BAKER INC

Product Identification

Product ID:9127 METHANOL CAPILLARY ANALYZED MSDS Date: 05/01/1989 FSC:6810 NIIN:00F016999

MSDS Number: BKTVX **Responsible Party**

J T BAKER INC

222 RED SCHOOL LANE

PHILLIPSBURG, NJ 08865-2219

US

Emergency Phone: 908-859-2151

Info Phone: 908-859-2151

Cage: DO803

Contractor

LABCO SCIENTIFIC DIV OKLAHOMA CITY OK

PHILLIPSBURG, NJ 08865

US

1-800-582-2537 Cage: 1A109

Ingredients

METHANOL (METHYL ALCOHOL), COLUMBIAN SPIRITS *97-4*

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight: 90-100%

OSHA PEL200 PPM ACGIH TLV: 200 PPM

EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

Hazards

LD50 LC50 Mixture: ORAL LD50 (RAT): 5628 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: INHALATION:

HARMFUL/HEADACHE/NAUSEA/VOMITING/DIZZINESS/NARCOSIS/RESPIRATORY

FAILURE/LOW BLOOD PRESSURE/CNS DEPRESSION/FATAL. SKIN:



IRRITATION/DERMATITIS. EYE: IRRITATION/CORNEAL DAMAGE. INGESTION:

HAR

MFUL/BLINDNESS/HEADACHE/NAUSEA/VOMITING/DIZZINESS/GASTROINTESTINAL

IRRITATION/CNS DEPRESSION/HEARING LOSS/FATAL.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: INHALATION: KIDNEY/LIVER DAMAGE. SKIN: IRRITATION & DERMATITIS. EYES: IRRITATION & CORNEAL DAMAGE.

INGESTION: HARMFUL, BLINDNESS, HEADACHE, NAUSEA, VOMITING,

DIZZINESS, GASTROINTESTINAL IRRITATION, CN S DEPRESSION, HEARING

LOSS, & FATAL. POISON, CANNOT BE MADE NON-POISONOUS.

Medical Cond Aggravated by Exposure: EYE, SKIN, LIVER OR KIDNEY

DISORDERS.

First Aid

First Aid:INGESTION: IF CONSCIOUS, DRINK PLENTY OF WATER. INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR. GIVE CPR OR OXYGEN IF NEEDED. SKIN/EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. OBTAIN MEDICAL ATTENTION IN ALL CASES. POISON, CANNOT BE MADE NON-POISONOUS.

Fire Fighting

Flash Point Method:CC Flash Point:54F Lower Limits:6% Upper Limits:36%

Extinguishing Media: ALCOHOL FOAM, DRY CHEMICAL, OR CO2. WATER MAY BE

INEFFECTIVE. USE WATER SPRAY TO REDUCE VAPORS.

Fire Fighting Procedures: WEAR PROTECTIVE EQUIP & SCBA W/FULL FACEPIECE OPERATED IN POSITIVE PRESSURE MODE. SAFELY, MOVE CONTAINERS. USE

WATER TO KEEP FIRE EXPOSED CONTAINERS COOL.

Unusual Fire/Explosion Hazard: VAPORS MAY FLOW TO IGNITION SOURCES/FLASHBACK. CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE. BURNS W/CLEAR, ALMOST INVISIBLE FLAME. AUTO-IGNITION TEMP: 867F.

Accidental Release

Spill Release Procedures: WEAR PROTECTIVE EQUIP. SHUT OFF IGNITION SOURCES. SAFELY, STOP LEAK. USE WATER SPRAY TO REDUCE VAPORS. TAKE UP W/SAND OR OTHER NON-COMBUSTIBLE ABSORBENT MATERIAL & PLACE INTO CONTAINER FOR LATER DISPO SAL. FLUSH AREA W/WATER.

Handling

Handling and Storage Precautions: KEEP CONTAINER TIGHTLY CLOSED. STORE IN A COOL, DRY, WELL-VENTILATED, FLAMMABLE LIQUID STORAGE AREA. BOND/GROUND CONTAINERS WHEN TRANSFERRING LIQUID. Other Precautions: AVOID CONTACT W/EYES, SKIN, CLOTHING, & BREATHING VAPORS. KEEP OUT OF REACH OF CHILDREN. DON'T SMOKE. CONTACT W/STRONG OXIDIZERS MAY CAUSE FIRE.

Exposure Controls

Respiratory Protection: AT CONCENTRATIONS > 200 PPM, USE A SELF-CONTAINED BREATHING APPARATUS.

Ventilation:PROVIDE GENERAL/LOCAL EXHAUST VENTILATION TO KEEP Protective Gloves:RUBBER

Eye Protection: SAFETY GOGGLES, FACE SHIELD

Other Protective Equipment: UNIFORM, PROTECTIVE SUIT

Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE

REUSE.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:149F

Melt/Freeze Pt:M.P/F.P Text:-144F

Vapor Pres:96 Vapor Density:1.11 Spec Gravity:0.79

Evaporation Rate & Reference: (BU AC = 1): 4.6

Solubility in Water: COMPLETE

Appearance and Odor: CLEAR, COLORLESS LIQUID W/PUNGENT ODOR.



Percent Volatiles by Volume: 100%

Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, ACIDS, ZINC, ALUMINUM, & MAGNESIUM. Stability Condition to Avoid:HEAT, FLAME, FLARES, SMOKING OR OTHER SOURCES OF IGNITION.

Hazardous Decomposition Products:CO, CO2, & FORMALDEHYDE.

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. EPA HAZARDOUS WASTE NUMBER: U154. FLAMMABLE LIQUID. UN1230.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.