

W 102 PROSEAL

MSDS Number

BKTXD

National Stock Number

8010-00F017024

Product Name

W 102 PROSEAL

Manufacturer

DUNN EDWARDS CORP

Product Identification

Product ID:W 102 PROSEAL

MSDS Date:06/12/1986

FSC:8010

NIIN:00F017024

MSDS Number: BKTXD

Responsible Party

DUNN EDWARDS CORPORATION

4885 E 52ND PLACE

LOS ANGELES , CA 90040

Emergency Phone: (213) 771-3330 . 2341

Info Phone: (213) 771-3330 . 2340

Cage: 33483

Contractor

DUNN-EDWARDS CORPORATION

LOS ANGELES, CA 90040-2828

US

213-771-3330 EXT 2240

Cage: 34483

Ingredients

NON-HAZARDOUS FOR INGREDIENTS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: UPPER/LOWER RESPIRATORY TRACT IRRITATION, NAUSEA, HEADACHES, DIZZINESS, & UNCONSCIOUSNESS. EYES: IRRITATION, REDNESS, & TEARING. SKIN: IRRITATION. INGESTION: NAUSEA, VOMITING, DIARRHEA, & GASTROINTESTINAL IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: UPPER/LOWER RESPIRATORY TRACT IRRITATION, NAUSEA, HEADACHES, DIZZINESS, & UNCONSCIOUSNESS. EYES: IRRITATION, REDNESS, & TEARING. SKIN: IRRITATION. INGESTION: NAUSEA, VOMITING, DIARRHEA, & GASTROINTESTINAL IRRITATION.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF NECESSARY. EYES/SKIN: WASH THOROUGHLY W/CLEAN WATER. INGESTION: IF CONSCIOUS, GIVE 2 GLASSES OF WATER TO DRINK. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, OR WATER.
Fire Fighting Procedures:OBSERVE RECOMMENDED PROCEDURES IN HANDLING
FIRE AREAS. WEAR SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:THIS MATERIAL IS NON-COMBUSTIBLE, BUT
DRIED FILMS ARE CAPABLE OF BURNING & SUPPORTING COMBUSTION WHEN IN
CONTACT W/OPEN FLAMES.

Accidental Release

Spill Release Procedures:DIKE & ABSORB SPILLED MATERIAL W/INERT
ABSORBENT MATERIAL SUCH AS SAND, EARTH, & SAW DUST. USE RAGS TO
CLEAN UP SMALL AMOUNTS OF SPILLED MATERIAL.

Handling

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN
USE. DON'T STORE OR HANDLE NEAR HEAT, FLAMES, & STRONG OXIDANTS.
STORE IN COOL, WELL VENTILATED AREA.
Other Precautions:ROTATE STOCK. USE OLDER MATERIALS FIRST. INSPECT FOR
LEAKS IN ALL CONTAINERS. DON'T STORE IN FREEZING AREAS. KEEP >40F.
KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT W/SKIN & EYES.

Exposure Controls

Respiratory Protection:WEAR APPROVED ORGANIC VAPOR RESPIRATOR UNLESS
VENTILATION EQUIPMENT IS ADEQUATE TO KEEP Ventilation:PROVIDE SUFFICIENT LOCAL EXHAUST/GENERAL MECHANICAL
VENTILATION TO KEEP Protective Gloves:IMPERMEABLE SOLVENT RESISTANT
Eye Protection:SAFETY GOGGLES, CHEMICAL SAFETY GLASSES
Other Protective Equipment:FACE SHIELD, IMPERMEABLE APRONS, PROTECTIVE
CLOTHING, HEAD CAPS, EYE WASHES, & SAFETY SHOWERS
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:200-225F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:60.95%

Stability

Stability Indicator/Materials to Avoid:YES
WATER, ALKALAI, STRONG ACIDS & OXIDANTS
Stability Condition to Avoid:OPEN FLAMES, TEMPERATURES Hazardous Decomposition Products:CO2, CO

Disposal

Waste Disposal Methods:COLLECT MATERIAL CONTAMINATED ABSORBENT & RAGS
INTO A DISPOSABLE CONTAINER & DISPOSE OF IN ACCORDANCE W/LOCAL,
STATE, & FEDERAL REGULATIONS. CONSULT W/LOCAL HAZARDOUS WASTE
REGULATORS REGARDING LANDFILL DUMPING.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.