https://msdsreport.com/msds/BKVWG

•

A 1 ACETONE

MSDS Number

BKVWG

National Stock Number

8010-00F017488

Product Name

A 1 ACETONE

Manufacturer

DUNN EDWARDS CORP

Product Identification

Product ID:A 1 ACETONE MSDS Date:06/13/1986 FSC:8010 NIIN:00F017488 MSDS Number: BKVWG

Responsible Party

DUNN-EDWARDS CORPORATION

4885 E 52ND PLACE

LOS ANGELES, CA 90040

Emergency Phone: (213) 771-3330 EXT 2341

Info Phone: (213) 771-3330 EXT 2340

Cage: 34483

Contractor

DUNN-EDWARDS CORPORATION

LOS ANGELES, CA 90040-2828

US

213-771-3330 EXT 2240

Cage: 34483

Ingredients

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 100%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: DIZZINESS, BREATHING DIFFICULTIES, HEADACHES, LOSS OF COORDINATION, ANESTHESIA, & RESPIRATORY TRACT IRRITATION. EYES: IRRITATION, REDNESS, TEARING, & BLURRED VISION. SKIN: DRY, DEFAT, CRAC KS, IRRITATION, & DERMATITIS. INGESTION: GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, & DIARRHEA.



Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: DIZZINESS, BREATHING DIFFICULTIES, HEADACHES, LOSS OF COORDINATION, ANESTHESIA & RESPIRATORY TRACT IRRITATION. EYES: IRRITATION, REDNESS, TEARING, & BLURRED VISION. SKIN: DRY, DEFAT, CRACK S, IRRITATION, & DERMATITIS. INGESTION:GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, & DIARRHEA.

•

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE CPR IF NEEDED. EYES: FLUSH W/PLENTY OF WATER FOR 15 MINS. SKIN: WASH THOROUGHLY W/SOAP & WATER. INGESTION: DON'T INDUCE VOMITING, CAN CAUSE CHEMICAL PNEUMONITIS & PULMONARY EDEMA. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TCC Flash Point:-15F Lower Limits:2.6% Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, & DRY CHEMICAL. Fire Fighting Procedures:WEAR RESPIRATORY EQUIPMENT. USE WATER ONLY AS FOG TO KEEP NEARBY CONTAINERS COOL. Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE LIQUID CLASS 1B. VAPORS FORM AN EXPLOSIVE MIXTURE W/AIR BETWEEN THE UPPER & LOWER EXPLOSIVE LIMITS WHICH CAN BE IGNITED BY IGNITION SOURCES.

Accidental Release

Spill Release Procedures:ELIMINATE IGNITION SOURCES. DIKE SPILL AREA/ADD ABSORBENT EARTH/SAWDUST TO SPILLED LIQUID. THOROUGHLY WET W/WATER & MIX. COLLECT ABSORBENT/WATER/SPILLED LIQUID MIXTURE INTO METAL CONTAINERS & ADD ENOU GH WATER TO COVER. USE NON-SPARKING UTENSILS.

Handling

Handling and Storage Precautions:NO SMOKING WHERE MATERIAL IS USED. AVOID HOT METAL SURFACES. USE IN COOL, WELL VENTILATED AREAS. KEEP CONTAINERS CLOSED WHEN NOT IN USE. Other Precautions:AVOID BREATHING VAPORS/CONTACT W/SKIN. KEEP AWAY FROM EXCESSIVE HEAT/OPEN FLAMES. AVOID BREATHING DUST FROM SPRAYING/SANDING. TOOLS USED W/THIS MATERIAL SHOULD BE MADE FROM ALUMINUM, BRASS, OR COPPER. DON'T USE PLASTIC UTENSILS.

Exposure Controls

Respiratory Protection:WHEN SPRAYING, USE A NIOSH APPROVED CARTRIDGE RESPIRATOR OR GAS MASK TO KEEP VENTILATED CONFINED SPACES USE A FRESH-AIR SUPPLYING RESPIRATOR OR A SELF-CONTAINED BREATHING AP PARATUS. Ventilation:PROVIDE GENERAL MECHANICAL VENTILATION OR LOCAL EXHAUST TO KEP Protective Gloves:IMPERMEABLE CHEMICAL Eye Protection:CHEMICAL SAFETY GLASSES, GOGGLES Other Protective Equipment:FACESHIELDS, IMPERMEABLE APRONS, PROTECTIVE CLOTHING, HEAD CAPS, SAFETY SHOWERS, & EYE WASHES Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:123-150F Vapor Pres:181 Vapor Density:>AIR Evaporation Rate & Reference:SLOWER THAN ETHER Appearance and Odor:LIQUID Percent Volatiles by Volume:100%

Stability

Stability Indicator/Materials to Avoid:YES ALKALINE MATERIALS, STRONG ACIDS, & OXIDIZING MATERIALS. Stability Condition to Avoid:EXCESSIVE HEAT/AGING/POOR VENTILATION/CORROSIVE ATMOSPHERES/PILOT LIGHTS/OPEN FLAMES/IGNITION SOURCES/HOT METAL SURFACES Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods:CONSULT LOCAL, STATE, & FEDERAL HAZARDOUS WASTE REGULATIONS BEFORE DISPOSING INTO APPROVED HAZARDOUS WASTE LANDFILLS. OBEY RELEVANT LAWS. EXTREMELY FLAMMABLE LIQUID CLASS 1B.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.