

B-13 FLAT BLACK BRITE TOUCH SPRAY PAINT

MSDS Number

BKXSB

National Stock Number

8010-00F018340

Product Name

B-13 FLAT BLACK BRITE TOUCH SPRAY PAINT

Manufacturer

BORDEN

Product Identification

Product ID: B-13 FLAT BLACK BRITE TOUCH SPRAY PAINT

MSDS Date: 06/23/1988

FSC: 8010

NIIN: 00F018340

MSDS Number: BKXSB

Responsible Party

BORDEN

180 EAST BROAD STREET

COLUMBUS , OH 43215

Emergency Phone: (614) 431-6600

Info Phone: (614) 431-6600 OR (800) 848-9400

Cage: 9P972

Contractor

BORDEN, INC. PACKAGING AND INDUSTRIAL PRODUCTS DIVISION

COLUMBUS, OH 43215

US

614-431-6600/800-848-9400

Cage: 9P972

Ingredients

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 30-50%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 5-15%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAANT; 9192

ISOBUTANE, 2-METHYLPROPANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 5-15%

OSHA PEL1800 MG/CUM

ACGIH TLV: 1000 PPM

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 5-15%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

VM&P NAPHTHA (LIGROINE)

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: 5-15%

OSHA PEL300 PPM/400 STEL

ACGIH TLV: 300 PPM; 9192

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES/SKIN: IRRITATION. INHALATION:

NOSE/THROAT/LUNG IRRITATION/CENTRAL NERVOUS SYSTEM

DEPRESSION/HEADACHE/DIZZINESS/NAUSEA/VOMITING/UNCONSCIOUSNESS/ASPHY

XIATION/CYANOSIS/RESPIRATORY DISTRESS/DROWSINES S/HARMFUL.

INGESTION: LIVER/KIDNEY DAMAGE/HARMFUL/IRRITATION/CORROSIVE TO

MUCOUS MEMBRANES.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES/SKIN: IRRITATION. INHALATION:

NOSE/THROAT/LUNG IRRITATION/CENTRAL NERVOUS SYSTEM

DEPRESSION/HEADACHE/DIZZINESS/NAUSEA/VOMITING/UNCONSCIOUSNESS/ASPHY

XIATION/CYANOSIS/RESPIRATORY DISTRESS/DROWSINES S/HARMFUL.

INGESTION: HARMFUL/IRRITATION/CORROSIVE TO MUCOUS

MEMBRANE/LIVER/KIDNEY DAMAGE.

First Aid

First Aid:EYES/SKIN: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MIN.

INHALATION: REMOVE TO FRESH AIR, IF NOT BREATHING, GIVE ARTIFICIAL

RESPIRATION, PREFERABLY MOUTH-TO-MOUTH. INGESTION: DILUTE BY

DRINKING LARGE Q UANTITIES OF WATER. OBTAIN MEDICAL ATTENTION IN

ALL CASES.

Fire Fighting

Flash Point:Extinguishing Media:DRY CHEMICAL, FOAM OR CO2

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE, BUT SHOULD BE USED

TO KEEP FIRE-EXPOSED CONTAINERS COOL.
Unusual Fire/Explosion Hazard:HIGH TEMPERATURES MAY CAUSE BURSTING.
VAPOR MAY IGNITE EXPLOSIVELY. FLASHBACK IS OBTAINED AT ANY DEGREE
OF VALVE OPENING. EXTREMELY FLAMMABLE.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. SOAK UP
W/ABSORBENT MATERIAL & REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT
ENTRY INTO NATURAL BODIES OF WATER.

Handling

Handling and Storage Precautions:DON'T PLACE CONTAINER ON
RADIATOR/STOVE/TEMPERATURES >120F/DIRECT SUNLIGHT OR NEAR OTHER
HEAT SOURCES. USE W/ADEQUATE VENTILATION. DON'T SMOKE.
Other Precautions:AVOID BREATHING VAPOR OR MIST. DON'T PUNCTURE
CONTAINER. CONTENTS UNDER PRESSURE WILL DISCHARGE. DON'T CUT OR
WELD ON OR NEARBY. EMPTY CONTAINER MAY CONTAIN EXPLOSIVE VAPORS.
AVOID SKIN & EYE CONTACT.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTION
EQUIPMENT WHEN >TLV. OBSERVE ENGINEERING CONTROLS.
Ventilation:LOCAL EXHAUST ENCLOSED SYSTEM DESIGN IN VOLUME & AIR FLOW
PATTERNS TO KEEP Protective Gloves:IMPERVIOUS
Eye Protection:GOGGLES
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE
REUSE. WASH THOROUGHLY AFTER HANDLING.
Supplemental Safety and Health
PERCENT NON-VOLATILE BY WEIGHT: 11-20

Chemical Properties

Vapor Pres: 60 PSIG
Vapor Density:>AIR
Spec Gravity:Evaporation Rate & Reference:FASTER THAN BU AC
Solubility in Water:SLIGHT
Appearance and Odor:FLAT BLACK LIQUID W/SOLVENT ODOR
Percent Volatiles by Volume:80-89%

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZERS, ACIDS OR BASES
Stability Condition to Avoid:HEAT, TEMPERATURES >120F, OPEN FLAMES,
SPARKS, PILOT LIGHTS & OTHER SOURCES OF IGNITION
Hazardous Decomposition Products:OXIDES OF CARBON

Disposal

Waste Disposal Methods:INCINERATION MAY CAUSE CONTAINER TO BURST
VIOLENTLY. DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE & LOCAL
REGULATIONS. DON'T INCINERATE (BURN) OR PUNCTURE CONTAINER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.