

STAIN,OIL,SEMI-TRANSPARENT,WOOD,DK REDWOOD

MSDS Number

BLBBP

National Stock Number

8010-00-926-9129

Product Name

STAIN,OIL,SEMI-TRANSPARENT,WOOD,DK REDWOOD

Manufacturer

ASPEN PAINTS

Product Identification

Product ID:STAIN,OIL,SEMI-TRANSPARENT,WOOD,DK REDWOOD

MSDS Date:09/01/1991

FSC:8010

NIIN:00-926-9129

MSDS Number: BLBBP

Responsible Party

ASPEN PAINTS

1128 S.W. SPOKANE STREET

SEATTLE , WA 98134

US

Emergency Phone: 800-424-9300 (CHEMTREC)

Info Phone: 00)

Preparer: D. KIER

Cage: 0AL09

Contractor

ASPEN PAINTS/ASAMIPEN AMERICA INC

SEATTLE, WA 98134-1187

US

303-573-1014(MED ONLY)

Cage: 0AL09

Ingredients

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight: 100%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

Hazards

LD50 LC50 Mixture:SEE INGREDIENTS

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: NASAL & RESPIRATORY

IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE,

POSSIBLE UNCONSCIOUSNESS, ASPHYXIATION. MAY BE HARMFUL OR FATAL.

SKIN: PROLONGED & REPEATED CONTACT W/SKIN C AN CAUSE DEFATTING &

DRYING OF SKIN RESULTING IN IRRITATION & DERMATITIS. EYE: SEVERE

IRRITATION, REDNESS, TEARING *

Effects of Overexposure: * & BLURRED VISION. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING & DIARRHEA. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. REPORTS HAVE ASSOCIATED REPEATED & PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENT W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

First Aid

First Aid: INHALATION: REMOVE VICTIM FROM FURTHER EXPOSURE & RESTORE BREATHING IF REQUIRED. EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. SKIN: WASH CONTAMINATED SKIN W/MILD SOAP & WATER. INGESTION: DO NOT INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IMMEDIATELY.

Fire Fighting

Flash Point Method: TCC
Flash Point: 112F, 44C
Lower Limits: 0.8
Upper Limits: 5.0
Extinguishing Media: DRY CHEMICAL, CO₂, FOAM AND WATER FOG.
Fire Fighting Procedures: DO NOT ENTER CONFINED FIRE SPACE W/O ADEQUATE PROTECT CLOTH & APPROVED POSITIVE PRESS SCBA. EXCLUDE AIR. USE WATER ONLY AS FOG. COOL FIRE EXPOSED CONTNR W/WATER.
Unusual Fire/Explosion Hazard: AVOID EXCESSIVE HEAT, OPEN FLAMES & ALL IGNITION SOURCES.

Accidental Release

Spill Release Procedures: REMOVE IGNITION SOURCES. VENT AREA. ABSORB SPILL W/ABSORB MAT'L & PLACE IN CLOSED CONTNR. LARGE SPILL-DIKE AREA TO PREVENT MAT'L FROM ENTERING WATER SYSTEMS. WEAR PROTECT EQUIPMENT DURING CLEANUP. NOTIFY PROPER AUTHORITIES IF SPILL EXCEEDS 220 LBS.

Handling

Handling and Storage Precautions: COMBUSTIBLE LIQUID. STORE IN A COOL, DRY, WELL-VENTILATED AREA, AWAY FROM HEAT & IGNITION SOURCES. AVOID PROLONGED OR REPEATED CONTACT W/SKIN.
Other Precautions: AVOID BREATHING SPRAY/MIST. LAUNDRY CONTAM CLOTHING PRIOR TO REUSE. GROUND CONTAINERS WHEN POURING. LIMIT FREE FALL TO MINIMIZE STATIC CHARGE BUILD-UP. EMPTY CONTAINERS MAY BE HAZARDOUS FROM PRODUCT RESIDUE & VAPORS & ALL CAUTIONS APPLY TO THEM.

Exposure Controls

Respiratory Protection: A CANISTER-TYPE RESPIRATOR MUST BE WORN TO PREVENT THE INHALATION OF VAPORS OR SPRAY MISTS WHEN THE TLV/PEL IS EXCEEDED.
Ventilation: GENERAL VENT IS REQUIRED DURING NORMAL USE. LOCAL VENT MAY BE REQUIRED IN CERTAIN CASES TO KEEP EXPOS LEVEL BELOW LIMIT.
Protective Gloves: CHEM-RESIST NITRILE, NEOPRENE OR RUBBER.
Eye Protection: WEAR FACE SHIELD OR CHEMICAL GOGGLES.
Other Protective Equipment: WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATION/SAFETY SHOWER SHOULD BE AVAILABLE.
Work Hygienic Practices: USE GOOD PERSONAL HYGIENE.
Supplemental Safety and Health
DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP AWAY FROM CHILDREN.

Chemical Properties

Boiling Pt: B.P. Text: 301 TO 402F
Vapor Pres: >7.0 @ 38C
Vapor Density: 4.8
Spec Gravity: 0.94
Viscosity: 10"-25"
Evaporation Rate & Reference: SLOWER THAN BUTYL ACETATE
Solubility in Water: NEGLIGIBLE
Appearance and Odor: THIN LIQUID, MILD ODOR.

Percent Volatiles by Volume:27-29

Stability

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS, LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE ARE PRODUCED ON COMBUSTION.

Conditions to Avoid Polymerization:AVOID EXCESSIVE HEAT, OPEN FLAME AND ALL IGNITION SOURCES.

Disposal

Waste Disposal Methods:TREAT AS HAZARDOUS WASTE IF NOT POSSIBLE TO RECLAIM. DISPOSE OF AT A LICENSED WASTE DISPOSAL COMPANY OR INCINERATE W/APPROVAL OF ENVIRONMENTAL AUTHORITY. ALL DISPOSAL PROCEDURES MUST COMPLY W/LOCAL, S TATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.