

TEFLON FLUOROCARBON RESIN FEP, 100N

MSDS Number

BLBHT

National Stock Number

6850-00N015696

Product Name

TEFLON FLUOROCARBON RESIN FEP, 100N

Manufacturer

DU PONT E I DE NEMOURS AND CO INC

Product Identification

Product ID:TEFLON FLUOROCARBON RESIN FEP, 100N

MSDS Date:10/18/1988

FSC:6850

NIIN:00N015696

MSDS Number: BLBHT

Responsible Party

DU PONT E I DE NEMOURS & CO INC

1007 MARKET STREET

WILMINGTON , DE 19898

US

Emergency Phone: 800-441-3637/800-424-9300(CHEMTREC)

Info Phone: 800-441-7515/MSDS 302-992-3511

Preparer: W H MARTIN

Cage: 18873

Contractor

E.I. DUPONT DE NEMOURS & CO

WILMINGTON, DE 19898

US

800-441-7515;800-441-9442

Cage: 18873

Ingredients

FLUORINATED ETHYLENE PROPYLENE COPOLYMER

CAS: 25067-11-2

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:(ACUTE) INGEST & SKIN: NOT TOXIC. EYE: MECHANICAL IRRIT. INHAL: WHEN THERMALLY DECOMPOSED BY HEATING ABOVE 260C, OR BY SMOKING TOBACCO/CIGS CONTAM W/POLYMER DUST, MAY CAUSE POLYMER FUME FEVER. SYMP AR E FLU-LIKE, W/CHILLS & FEVER, WHICH MAYNOT OCCUR UNTIL SEV HRS AFTER EXPOS & PASS OFF WITHIN 36-48(SEE EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ: HRS, EVEN IN ABSENCE OF TREATMENT.

DUPONT REC TREATING POLYMER DUST AS A NUISANCE PARTICULATE, AND HAS ESTABLISHED AN AEL OF 10 MG/M3 TOTAL DUST, THE SAME AS THE TLV FOR OTHER NUISANCE PARTI CULATES. (CHRONIC) NONE KNOWN.

Medical Cond Aggravated by Exposure:NONE KNOWN.

First Aid

First Aid:INHAL: IF EXPOSED TO FUMES FROM OVERHEATING OR COMBUSTION, MOVE TO FRESH AIR. CONSULT MD IF SYMP PERSIST. EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MIN. CONSULT MD IF SYMP PERSIST. SKIN: IF MOL TEN POLYMER CONTACTS SKIN, COOL RAPIDLYWITH COLD WATER. DO NOT ATTEMPT TO PEEL POLYMER FROM SKIN. OBTAIN MED ATTN FOR THERMAL BURN. INGEST: CALL MD IMMED .

Fire Fighting

Extinguishing Media:WATER, CO*2, FOAM, DRY CHEMICAL.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP TO PROT FROM HF FUMES WHICH REACT W/WATER TO FORM HYDROFLUORIC ACID. DOES NOT BURN W/O AN (SEE SUPP DATA)
Unusual Fire/Explosion Hazard:TOXIC FLUORINE COMPOUNDS EVOLVED IN FIRE. HYDROGEN FLUORIDE (HF), CARBONYL FLUORIDE, CO & LOW MOLECULAR WEIGHT FLUOROCARBONS.

Accidental Release

Spill Release Procedures:SWEEP UP TO AVOID SLIPPING HAZARD.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:AVOID CONTAMINATION. KEEP CONTAINERS CLOSED. BEFORE USING, READ TEFLON "SAFETY IN HANDLING AND USE", BULLETIN E-35824-1.
Other Precautions:AVOID CONTAMINATION OF CIGARETTES OR TOBACCO WITH POLYMER DUST.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR WHEN TEMPERATURE EXCEEDS 260C IF VENTILATION IS INADEQUATE TO MAINTAIN HF CONC BELOW PEL.
Ventilation:USE LOCAL EXHAUST TO COMPLETELY REMOVE VAPORS AND FUMES LIBERATED DURING HOT PROCESSING FROM THE WORK AREA.
Protective Gloves:PROTECTIVE GLOVES.
Eye Protection:CHEMICAL WORKERS GOGGLES .
Other Protective Equipment:LONG SLEEVE SHIRT.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
FIRE FIGHT PROC: EXTERNAL FLAME. WEAR NEOPRENE GLOVES WHEN HANDLING REFUSE FROM A FIRE INVOLVING TEFLON. HAZ DECOMP PRODS: PARTICULATE MATTER EVOLVED FROM OVERHEATING MAY CAUSE POLYMER FUME FEVER.

Chemical Properties

HCC:N1
Melt/Freeze Pt:M.P/F.P Text:527F,275C
Spec Gravity:2.1-2.2
Solubility in Water:INSOLUBLE
Appearance and Odor:WHITE TRANSLUCENT PELLETS WITH NO ODOR.

Stability

MOLTEN ALKALI METALS, INTERHALOGEN COMPOUNDS.
Stability Condition to Avoid:TEFLON WILL BURN IN A ATMOSPHERE OF 95% OXYGEN WHEN AN IGNITION SOURCE IS PRESENT.
Hazardous Decomposition Products:>260C TEFLON FEP CAN EVOLVE TOXIC GASEOUS MATLS SUCH AS HF & PERFLUOROOLEFINS. THE OSHA PEL FOR HF IS 3 PPM. (SUPP DATA)

Disposal

Waste Disposal Methods:LANDFILL OR INCINERATION IN COMPLIANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. INCINERATION REQUIRES SCRUBBING OF GASEOUS PRODUCTS TO REMOVE HF.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.