

CERTANIUM HEAT SHIELD, 16003

MSDS Number

BLBPB

National Stock Number

7920-00N016329

Product Name

CERTANIUM HEAT SHIELD, 16003

Manufacturer

CERTANIUM ALLOYS AND RESEARCH CO

Product Identification

Product ID: CERTANIUM HEAT SHIELD, 16003

MSDS Date: 09/06/1988

FSC: 7920

NIIN: 00N016329

MSDS Number: BLBPB

Responsible Party

CERTANIUM ALLOYS & RESEARCH CO

4500 EUCLID AVENUE

CLEVELAND , OH 44103

US

Emergency Phone: 216-391-8300

Info Phone: 216-391-8300

Preparer: DS

Cage: 61404

Contractor

CERTANIUM ALLOYS & RESEARCH CO

CLEVELAND, OH 44103-1395

US

216-391-8300

Cage: 61404

Ingredients

ALUMINUM SILICATE

CAS: 12068-56-3

Fraction By Weight: 1-5%

ACGIH TLV: 5 MG/M3 (MFR)

CELLULOSE (PAPER FIBER)

CAS: 9004-34-6

RTECS: FJ5691460

Fraction By Weight: 10-30%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3; 9192

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 1-5%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

CELLULOSE, 2-HYDROXYETHYL ETHER (HYDROXY ETHYL CELLULOSE)

CAS: 9004-62-0

RTECS: FJ5958000

Fraction By Weight: 10-30%

ACGIH TLV: 10 MG/M3 (MFR)

SODIUM TETRABORATE, DECAHYDRATE

CAS: 1303-96-4

RTECS: VZ2275000

Fraction By Weight: 1-5%

OSHA PEL10 MG/M3

ACGIH TLV: 5 MG/M3; 9192

SEE ORIGINAL MSDS FOR MG/M3 EXPOSURE LIMITS

RTECS: 9999999ZZ

THE WELDING OR HIGH TEMPERATURE CUTTING ENVIRONMENT.

RTECS: 9999999ZZ

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: IRRITATION CHRONIC: CNS,
STOMACH. EYE/SKIN: MAY CAUSE IRRITATION. INGEST: HARMFUL IF
SWALLOWED.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:EYE: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15
MIN & CALL PHYSICIAN. SKIN: WASH THOROUGHLY WITH PLENTY OF WATER &
SOAP. INGEST: SEEK PHYSICIAN IMMEDIATELY, SHOW MSDS OR LABEL,
INDUCE VOMI TING.

Fire Fighting

Extinguishing Media:WATER/FOG/FOAM/DRY CHEMICAL/CARBON DIOXIDE.

Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR NIOSH/MSHA APPROVED
SCBA AND FULL PROTECTIVE EQUIPMENT .

Accidental Release

Spill Release Procedures:CONTAIN AND PICK UP WASTE MATERIALS. PUT IN A
SEALED NIOSH/MSHA APPROVED CONTAINER. DISPOSE OF AS A NON-HAZARDOUS

WASTE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:USE IN WELL VENT AREA. AVOID CONTACT W/EYES/SKIN. POISON KEEP FROM FRZNG. DO NO TAKE INTERNALLY. IN CASE OF ACCIDENT/ILLNESS, SEE MD. SHOW MSDS LABEL.

Other Precautions:WASH HANDS THOROUGHLY AFTER HANDLING. KEEP OUT OF REACH OF CHILDREN. ADDITIONAL TECHNICAL DATA SHEETS AND/OR MATERIAL SAFETY DATA SHEETS (MSDS) ARE AVAILABLE UPON REQUEST. FOR PROFESSIONAL AND INDUSTRIAL USE ONLY.

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:LOCAL/MECHANICAL REQUIRED TO KEEP CONCENTRATIONS BELOW EXPOSURE LIMITS. TLV AND PEL: 2.5 MG/M3

Protective Gloves:WELDERS GLOVES.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:EYE/FACE PROTECTION AND COLORED ABSORPTIVE LENS. WELDERS LEATHER APRON SLEEVES, AND LEGGINGS.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

HAZ DECOMP PROD:QUALITY OF BOTH DEPEND ON ALLOY BEING WELDED, THE PROCESS, PROC, & ELECTRODES USED. CONSTITUENTS OF FUME MAY BE DIFFERENT FROM INGRED, & MAY INCLUDE PARTICLES CNTNG IRON, MANGANESE, SILICON, CHROMIUM, NICKEL, & OTHER AMORPHOUS SLAGS. GASES MAY INCLUDE CO, OZONE, METAL OXIDES, METAL FLUORIDES.(ING 6)

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:212 F/100 C

Vapor Pres:22

Vapor Density:0.6

Spec Gravity:1.07

pH:8.7

Evaporation Rate & Reference:1 (WATER=1)

Solubility in Water:75%

Appearance and Odor:BLUE PASTE WITH MILD ODOR.

Percent Volatiles by Volume:20-40

Stability

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:KEEP FROM FREEZING.

Hazardous Decomposition Products:FUMES & GASES FROM WELDING & HIGH TEMPERATURE CUTTING CANNOT BE CLASSIFIED SIMPLY. THE COMPOSITION & (SEE SUPP DATA).

Disposal

Waste Disposal Methods:DISPOSE OF WASTES IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.