

## **INTERIOR/EXTERIOR VINYL ACRYLIC SEMI-GLOSS**

### **MSDS Number**

BLBVJ

### **National Stock Number**

8010-00N016791

### **Product Name**

INTERIOR/EXTERIOR VINYL ACRYLIC SEMI-GLOSS

### **Manufacturer**

AMERITONE PAINT CORP

### **Product Identification**

Product ID:INTERIOR/EXTERIOR VINYL ACRYLIC SEMI-GLOSS

MSDS Date:06/01/1990

FSC:8010

NIIN:00N016791

MSDS Number: BLBVJ

### **Responsible Party**

AMERITONE PAINT CORPORATION

18414 S SANTA FE AVENUE

COMPTON , CA 90221

US

Emergency Phone: 213-639-6791

Info Phone: 213-639-6791

Cage: FO133

### **Contractor**

AMERITONE PAINT CORP/COMPTON, CA 90221

190

LONG BEACH, CA 90801

US

310-639-6791

Cage: FO133

### **Ingredients**

3.2%.

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight:

OSHA PEL50 PPM, C

ACGIH TLV: 50 PPM VAP/MIST, C

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

ALUMINUM SILICATE

CAS: 1318-74-7

Fraction By Weight: 5%

OSHA PEL15 MG/M3 TDUST (AL)  
ACGIH TLV: 10 MG/M3 TDUST (AL)

93-125 G/L.  
RTECS: 9999999VO  
Fraction By Weight: SEE ING

RESTRICTED VENT AREA, WEAR NIOSH/MSHA APPRVD  
RTECS: 9999999ZZ

PARTICULATES & VAP. WHEN USED IN CONFINED AREA, WEAR  
RTECS: 9999999ZZ

APPRVD RESP WHEN FLAME  
RTECS: 9999999ZZ

DIRECTIONS FOR RESP USE.  
RTECS: 9999999ZZ

APPLIC SAFETY & HLTH STDS IN MIXING/APPLICATION &  
RTECS: 9999999ZZ

DECOMP PRODS DURING WELDING & FLAME CUTTING ON SURF  
RTECS: 9999999ZZ

## Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF RESPIRATORY TRACT;  
HEADACHE, NAUSEA, DIZZINESS.SKIN OR EYE CONTACT:PRIMARY  
IRRITATION.CHRONIC:PROLONGED AND REPEATED BREATHING OF SPRAY MIST  
AND/OR SANDING DUST OVER A PERIOD OF YE ARS MAY CAUSE DUST DISEASE  
OF THE LUNGS.  
Explanation of Carcinogenicity:NOT RELEVANT.  
Effects of Overexposure:SEE HEALTH HAZARDS.  
Medical Cond Aggravated by Exposure:NONE WHEN USED WITH ACCORDANCE WITH  
SAFE HANDLING AND USE INFORMATION.

## First Aid

First Aid:INHAL: REMOVE TO FRESH AIR. EYE: FLUSH IMMEDIATELY WITH LARGE  
AMOUNTS OF WATER FOR AT LEAST 15 MINUTES.CONSULT A PHYSICIAN FOR  
MEDICAL TREATMENT. SKIN:REMOVE WITH SOAP AND WATER. REMOVE SOILED  
CLOTHIN G. INGEST: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT  
INDUCE VOMITING. CONSULT PHYSICIAN IMMEDIATELY. TREAT  
SYMPTOMATICALLY.

## Fire Fighting

Flash Point:NONE  
Lower Limits:SEE ING  
Extinguishing Media:IN CASE OF FIRE USE CARBON DIOXIDE, DRY CHEMICAL,

FOAM OR OTHER NFPA APPROVED METHOD FOR TREATING A CLASS B FIRE.  
Fire Fighting Procedures:SUMMON PROF FIREFIGHTERS. USE NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP . WATER SPRAY MAY BE INEFT. IF WATER IS USED, FOG NOZZ ARE PREF. IF EXPOSED(SUPDAT)  
Unusual Fire/Explosion Hazard:DUE TO PRESS BUILD-UP,CLSD CNTNRS EXPOS TO EXTREME HEAT MAY EXPLODE.DURING EMER CONDITIONS,OVEREXP TO DECOMP PROD MAY CAUSE HLTH HAZ.SYMP MAY (SEE SUPP DATA)

## Accidental Release

Spill Release Procedures:WASH W/WATER. BEFORE ATTEMPTING CLEAN-UP, REFER TO HAZARD CAUTION INFORMATION IN OTHER SECTIONS. CONTAIN SPILLED MATERIAL & REMOVE W/INERT ABSORBENT. STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED OF.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:STORE BELOW 110 F AND KEEP FROM FREEZING.KEEP CNTNR CLSD WHEN NOT IN USE.  
Other Precautions:DO NOT TRANFER TO BOTTLES OR OTHER UNLABELED CONTAINERS. KEEP OUT OF REACH OF CHILDREN.

## Exposure Controls

Respiratory Protection:DO NOT BREATHE VAP/SPRAY MIST/SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR/OPEN AREA W/UNRESTRICTED VENT & DURING SANDING/GRINDING OPERATIONS, USE NIOSH/MSHA APPRVD MECH FILTER RESP TO REMOVE SOLID AIR BORNE PARTICLES OF OVERSPRAY & (SUPDAT)  
Ventilation:USE ONLY W/ADEQ VENT. PROVIDE GEN DILUTION/LOC EXHST VENT IN VOL/PATTERN TO KEEP AIR CONTAM CONC BELOW CURRENT (ING 8)  
Protective Gloves:IMPERVIOUS GLOVES .  
Eye Protection:CHEMICAL WORKERS GOGGLES. .  
Other Protective Equipment:NONE REQUIRED.  
Work Hygienic Practices:REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHROOM.  
Supplemental Safety and Health  
MFR'S TRADE NAME/PART NO:ENAMEL, PA250D. VAP DENS:HVR/AIR, AMMONIA & WATER ARE LTR/AIR. % VOLAT:67.8-70.92. FIRE FIGHT PROC:TO FIRE/EXTREME HEAT, WATER SHLD BE USED TO COOL CLSD CNTNRS & PVNT PRESS BU ILT-UP/POSS AUTO-IGNIT. EXPLO HAZ:NOT BE IMMED APPARENT. OBTAIN MED ATTN. RESP PROT:SANDING DUST. WHEN USED IN (ING 4)

## Chemical Properties

HCC:N1  
Boiling Pt:B.P. Text:>212F,>100C  
Vapor Pres:SEE INGS  
Vapor Density:SUPP DATA  
Spec Gravity:1.078-1.26  
Evaporation Rate & Reference:SLOWER THAN ETHER.  
Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.  
Percent Volatiles by Volume:SUPDAT

## Stability

Stability Indicator/Materials to Avoid:YES  
NONE SPECIFIED BY MANUFACTURER.  
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.  
Hazardous Decomposition Products:MAY CAUSE HAZ FUMES WHEN HEATED TO DECOMPOSITION.FUMES MAY CONTAIN CARBON MONOXIDE,CARBON DIOXIDE,OXIDES OF NITROGEN.

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.