

## **CONCRETE SEAL**

### **MSDS Number**

BLBWJ

### **National Stock Number**

8010-00N016854

### **Product Name**

CONCRETE SEAL

### **Manufacturer**

A B C COMPOUNDING COMPANY INC

### **Product Identification**

Product ID: CONCRETE SEAL

MSDS Date: 11/12/1986

FSC: 8010

NIIN: 00N016854

MSDS Number: BLBWJ

### **Responsible Party**

A B C COMPOUNDING COMPANY INC

6970 JONESBORO ROAD

MORROW , GA 30260

US

Emergency Phone: 404-968-3630

Info Phone: 404-968-3630

Cage: 97257

### **Contractor**

A B C COMPOUNDING CO INC

MORROW, GA 30260

US

404-968-3630

Cage: 97257

### **Ingredients**

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8925000

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

### **Hazards**

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: ACUTE/CHRONIC: OVEREXPOSURE AND TOXICITY DEPEND UPON DURATION OF EXPOSURE.

Explanation of Carcinogenicity: NOT RELEVANT.

Effects of Overexposure: SYMPTOMS OF OVEREXPOSURE INCLUDE DIZZINESS, NAUSEA, HEADACHE AND EVEN LOSS OF CONSCIOUSNESS.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

### **First Aid**

First Aid: INHAL: REMOVE TO FRESH AIR. IF BRTHG HAS STOPPED ADMINISTER ART RESP. CALL MD. INGEST: DO NOT INDUCE VOMITING. GET MD IMMED. EYE: FLUSH IMMEDIATELY WITH WATER FOR AT LEAST 15 MINUTES. CALL MD. SKIN: FLUSH W/ PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. WASH WITH PLENTY OF SOAP AND WATER FOR 15 MINUTES.

## Fire Fighting

Flash Point Method: TOC  
Flash Point: 110F, 43C  
Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICAL  
Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. DRUMS MAY BUILD PRESSURE AND RUPTURE UNDER EXTREME HEAT.  
Unusual Fire/Explosion Hazard: CONCENTRATED VAPORS CAN BE IGNITED BY EXTREME HEAT OR ANY IGNITION SOURCE. DO NOT CUT OR WELD DRUM.

## Accidental Release

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. CONTAIN SPILL AND PUMP TO RECOVER. SMALL SPILLS MAY BE MOPPED UP. FLUSH AREA WITH WATER.  
Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions: STORE IN COOL PLACE AWAY FROM IGNITION SOURCES. KEEP CONTAINER CLOSED WHEN NOT IN USE.  
Other Precautions: NONE SPECIFIED BY MANUFACTURER.

## Exposure Controls

Respiratory Protection: NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN.  
Ventilation: EQUIVALENT TO OUTDOORS. USE EXPLOSION PROOF MOTOR FOR MECHANICAL VENTING.  
Protective Gloves: IMPERVIOUS GLOVES.  
Eye Protection: CHEMICAL WORKERS GOGGLES.  
Other Protective Equipment: AS REQUIRED TO LIMIT SKIN CONTACT.  
Work Hygienic Practices: WASH HANDS THOROUGHLY AFTER USE.  
Supplemental Safety and Health  
NONE SPECIFIED BY MANUFACTURER.

## Chemical Properties

HCC: F4  
Boiling Pt: B.P. Text: 275F, 135C  
Spec Gravity: 0.86  
Solubility in Water: INSOLUBLE  
Appearance and Odor: CLEAR AMBER LIQUID; MINERAL SPIRIT ODOR.

## Stability

Stability Indicator/Materials to Avoid: YES  
STRONG ACIDS AND OXIDIZERS.  
Stability Condition to Avoid: EXTREME TEMPERATURES.  
Hazardous Decomposition Products: CO, CO\*2.

## Disposal

Waste Disposal Methods: KEEP OUT OF SEWERS AND SURFACE WATERS. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.