

## **LEMON OIL FURNITURE POLISH, 5815**

### **MSDS Number**

BLBXL

### **National Stock Number**

7930-00N016938

### **Product Name**

LEMON OIL FURNITURE POLISH, 5815

### **Manufacturer**

CELLO CORP

### **Product Identification**

Product ID: LEMON OIL FURNITURE POLISH, 5815

MSDS Date: 01/12/1989

FSC: 7930

NIIN: 00N016938

MSDS Number: BLBXL

### **Responsible Party**

CELLO CORPORATION

1354 OLD POST RD

HAVRE DE GRACE , MD 21078

Emergency Phone: 301-879-4248

Info Phone: 301-939-1234

Cage: DO840

### **Contractor**

CELLO CORPORATION

HAVRE DE GRACE, MD 21078

US

301-879-2770

Cage: DO840

### **Ingredients**

PROPANE, 2-METHYL- (ISOBUTANE)

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 15%

OSHA PEL1000 PPM

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 15%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

BUTANE

CAS: 106-97-8

RTECS: EJ4200000

Fraction By Weight: 15%

OSHA PEL800 PPM

ACGIH TLV: 800 PPM; 9192

LOW ODOR PETROLEUM SOLVENT

CAS: 64742-48-9

Fraction By Weight: 28.5%

## Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: EYE CONTACT NEAR SOURCE OF SPRAY  
MAY PRODUCE BURNS DUE TO THE FREEZING EFFECT OF AEROSOL PROPELLANT.

PRODUCT IS AN EYE IRRITANT. INHAL: LEVELS ABOVE TLV MAY PRDCE  
ANESTHETIC EFFECTS, DIZZ, DROW, NAUSEA, VOMITING. SKIN:CONTACT  
NEAR SOURCE MAY PRDCE BURNS DUE TO COOLING EFFECT OF  
PROPELLANT,(SEE EFTS OF OVEREXP)

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure:HLTH HAZ: ALSO DRYING OUT CONDITION(SURFACE  
DEFATTING). INGEST:POSSIBLE DAMAGE TO MUCOUS MEMBRANES AND  
ESOPHAGUS DUE TO COOLING EFFECT OF PROPELLANT. IN ADDITION, NAUSEA,  
VOMITING, DIZZINESS AND DROWS INESS MAY OCCUR.

Medical Cond Aggravated by Exposure:EXISTING CONDITIONS OF DERMATITIS  
CAN BE AGGRAVATED BY OVEREXPOSURE.

## First Aid

First Aid:EYE:IMMED FLUSH W/RUNNING H\*20 FOR AT LEAST 15 MIN WHILE  
HOLDING EYELIDS APART FOR MAX IRRIGATION. IF IRRIT PERSISTS,  
CONTACT PHYS.SKIN:WASH THORO W/RUNNING H\*20 TO REMOVE PROD;IF  
DRYING HAS OCCURRED, APPLY A SUITABLE HAND LOTION.IF IRRIT  
PERSISTS, CONTACT PHYS.INHAL:REMOVE PATIENT TO FRESH AIR & APPLY  
ARTF RESP, IF NECESSARY, BY QUALIFIED PERSONNEL. CONTACT PHYS  
IMMED.INGEST:DRINK (SEE SUPP DATA)

## Fire Fighting

Flash Point:NON-FLAMMABLE

Extinguishing Media:FOAM, CO\*2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA AND WEAR  
PROTECTIVE CLOTHING. USE WATER SPRAY TO COOL CANS EXPOSED TO FIRE.  
Unusual Fire/Explosion Hazard:AEROSOL CANS, WHEN HEATED TO HIGH TEMPS,  
MAY BURST AND "ROCKET" RELEASING A FLAM PROPELLANT. PROD CONTAINS  
SILICONE OIL WHICH WILL MAKE SURFACES SLIPPERY.

## Accidental Release

Spill Release Procedures:AVOID OPEN FLAMES OR OTHER SOURCES OF  
IGNITION. TAKE CARE IN WALKING AS PROD CAN BE VERY SLIPPERY. PICK  
UP UTILIZING ABSORBENTS I.E. SAND, SAWDUST, DIATOMACEOUS EARTH,  
ETC. SHOVEL UP AND PUT INTO CONTAINERS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:CONTENTS UNDER PRESS. DO NOT  
PUNCTURE/INCINERATE. DO NOT USE/STORE CLOSE TO HEAT OR OPEN FLAME.  
DO NOT STORE NEAR STRONG ACIDS OR OXIDIZING AGENTS.

Other Precautions:EXPOSURE TO TEMPERATURE ABOVE 120F MAY CAUSE CAN TO  
BURST. DO NOT THROW CAN INTO FIRE OR INCINERATE.

## Exposure Controls

Respiratory Protection:WEAR NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:NONE NECESSARY WHEN USING INDIVIDUAL UNITS. IN SMALL CONFINED AREAS LOCAL EXHAUST WILL BE ADEQUATE.

Protective Gloves:RUBBER GLOVES RECOMMENDED.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:EYE WASH IF AVAILABLE.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

FIRST AID PROC: LARGE QUANTITIES OF MILK OR WATER; DO NOT INDUCE VOMITING. CONTACT PHYS IMMEDIATELY.

## Chemical Properties

HCC:V3

Boiling Pt:B.P. Text:210F,99C

Vapor Pres:40

Vapor Density:HEAVIER

Spec Gravity:0.913

Evaporation Rate & Reference:SLOWER THAN WATER.

Appearance and Odor:WHITE EMULSION SLIGHTLY VISCOUS LIQUID WITH LEMON ODOR.

Percent Volatiles by Volume:94.0

## Stability

Stability Indicator/Materials to Avoid:YES

DO NOT MIX OR STORE WITH STRONG OXIDANTS.

Stability Condition to Avoid:EXTREME HEAT, FIRE AND OTHER SOURCES OF IGNITION.

Hazardous Decomposition Products:CARBON DIOXIDE AND MONOXIDE.

## Disposal

Waste Disposal Methods:DEPOSIT IN LANDFILL OR INCINERATE ONLY IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.