

RED SHOP COAT PRIMER, 7069

MSDS Number

BLBYD

National Stock Number

8010-00N016958

Product Name

RED SHOP COAT PRIMER, 7069

Manufacturer

RUST OLEUM CORP

Product Identification

Product ID:RED SHOP COAT PRIMER, 7069

MSDS Date:01/10/1990

FSC:8010

NIIN:00N016958

MSDS Number: BLBYD

Responsible Party

RUST-OLEUM CORPORATION

11 HAWTHORNE PARKWAY

VERNON HILLS , IL 60061

US

Emergency Phone: 708-367-7000

Info Phone: 708-367-7000

Cage: DO883

Contractor

RUST-OLEUM CORPORATION

VERNON HILLS, IL 60061-1583

US

847-367-7700

Cage: DO883

Ingredients

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 20%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight: 15%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHAL: HARMFUL IF INHALED. MAY AFFECT BRAIN & NERV SYS CAUSING DIZZ, HDCH/NAUSEA. RPTD OVEREXP MAY LEAD PROGRESSIVELY TO STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS OR COMA. CAUSES NOSE & THROA T IRRIT. SKIN OR EYE: CAUSES EYE & SKINIRRIT WHICH CAN LEAD TO DERMATITIS W/RPTD OVEREXP. INGEST:(SEE EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ: GI IRRIT, NAUSEA, VOMIT & DIARR.

CHRONIC: REPORTS HAVE SHOWN RPTD & PRLNGD OCCUP OVEREXP TO SOLV W/PERMANENT BRAIN & NERV SYS DAMAGE. OVEREXP TO XYLOL IN LAB ANIMALS HAS SHOWN LIVER ABNORMAL ITIES, KIDNEY, LUNG, SPLEEN & EYE DAMAGE AS WELL AS ANEMIA. HUMAN AFFECTS HAVE SHOWN LIVER & CARDIAC ABNORMALITIES.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:INHAL: REMOVE FROM EXP, RESTORE BRTHG & NOTIFY A PHYSICIAN.

EYE: FLUSH IMMED W/LRG AMTS OF H*2O FOR AT LEAST 15 MIN. NOTIFY MD.

SKIN: WASH AFFECTED AREA W/SOAP & WATER, REMOVE CONTAMINATED CLOTHING AN D WASH BEFORE REUSE. INGEST: DO NOT INDUCE VOMITING. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTEN. ASPIRATION OF THIS MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

Fire Fighting

Flash Point Method:TCC

Flash Point:81.0F,27.2C

Extinguishing Media:NFPA CLASS B EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:FULL PROT EQUIP INCLUDING NIOSH/MSHA APPRVD SCBA SHOULD BE USED. H*2O SPRAY MAY BE INEFT. H*2O MAY BE USED TO COOL CLSD CNTNRS TO PVNT PRESS BUILD-UP(SUPP DATA)

Unusual Fire/Explosion Hazard:KEEP CNTNRS TIGHTLY CLSD. ISOLATE FROM HEAT, ELEC EQUIP, SPARKS & OPEN FLAME. CLSD CNTNRS MAY EXPLO WHEN EXP TO EXTREME HEAT. DO NOT APPLY TO HOT SURFACES.

Accidental Release

Spill Release Procedures:REMOVE ALL SOUCES OF IGNITION, VENTIILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120 F. STORE LARGE QUANTITIES IN BUILDING DESIGNED & PROT FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUID.

Other Precautions:CNTNRS SHOULD BE GROUNDED WHEN POURING. EMPTY CNTNRS MAY BE HAZ. PENNSYLVANIA/NEW JERSEY RIGHT-TO-KNOW LAWS- OTHER ING IN THIS PROD SUCH AS RESIN, PIGMENT & ADDITIVES ARE NON-HAZ & CONSIDERED TRADE SE CRET UNDER THESE REGS.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED CHEMICAL CARTRIDGE RESPIRATOR (TC23C) TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY AND ORGANIC VAPORS DURING SPRAY APPLICATION. IN CONFINED AREAS: USE NIOSH/MSHA APPROVED SU PPLIED-AIR RESP OR HOODS (TC19C).

Ventilation:PROVIDE GENERAL DILUTION/LOCAL EXHAUST VENT IN VOLUME & PATTERN TO KEEP TLV OF HAZ INGREDIENTS BELOW ACCEPTABLE LIMITS.

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:IMPERVIOUS CLOTHING TO PREVENT PROLONGED SKIN CONTACT.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

FIRE FIGHT PROC: AND POSSIBLE AUTOIGNITION OR EXPLOSION. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:281F,138C

Vapor Pres:SEE INGRED

Vapor Density:HVR/AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:58

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE, BY OPEN FLAME.

Disposal

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.