

TT-P-29J PAINT, LATEX BASE INTERIOR FLAT 32

MSDS Number

BLBZZ

National Stock Number

8010-00N017117

Product Name

TT-P-29J PAINT, LATEX BASE INTERIOR FLAT 32

Manufacturer

CON LUX COATINGS INC

Product Identification

Product ID:TT-P-29J PAINT, LATEX BASE INTERIOR FLAT 32

MSDS Date:12/21/1987

FSC:8010

NIIN:00N017117

MSDS Number: BLBZZ

Responsible Party

CON-LUX COATINGS INC

226 TALMADGE ROAD

EDISON , NJ 08818-0847

US

Emergency Phone: 201-287-4000

Cage: 60189

Contractor

CON-LUX COATINGS INC

847

EDISON, NJ 08818-0847

US

732-287-4000

Cage: 60189

Ingredients

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: >1%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

ALUMINUM SILICATE (KAOLIN)

CAS: 66402-68-4

Fraction By Weight: >1%

OSHA PEL10 MG/M3 (TDUST)

ACGIH TLV: 10 MG/M3 (TDUST)

CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: >1%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9192

SILICONE DIOXIDE (DIATOMACEOUS EARTH)

CAS: 68855-54-9

Fraction By Weight: >1%

OSHA PEL6 MG/M3 (TDUST)

ACGIH TLV: 10 MG/M3 (TDUST)

17.60.

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: >1%

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: IRRITATION OF EYES AND SKIN MAY OCCUR WITH OVEREXPOSURE. CONTINUED BREATHING OF VAPORS MAY IRRITATE RESPIRATORY TRACT CAUSING HEADACHE, NAUSEA AND DIZZINESS. CHRONIC: UNKNOWN.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:INHAL:REMOVE TO FRESH AIR. RESTORE RESP IF NEC. TREAT SYMPTOMATICALLY. EYE:FLUSH IMMED W/COPIOUS QTYS OF WATER FOR AT LEAST 15 MIN. GET MD. SKIN:WASH AFFECTED AREAS W/SOAP & WATER. REMOVE CONTAM CLTHG . GET MD IF IRRIT PERSISTS. INGEST:DRINK 1/2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMIT. IF SPONTANEOUS VOMIT OCCURS KEEP HEAD AT/BELOW KNEE LEV TO PVNT ASPIR IN LUNGS. GET MD/POIS CTL CTR IMMED.

Fire Fighting

Flash Point:NONE DETECTED

Extinguishing Media:USE MEDIA SUITABLE FOR SURROUNDING FIRE .

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . WATER MAY BE USED TO COOL DOWN UNOPENED CONTAINERS IN VICINITY.

Unusual Fire/Explosion Hazard:NONE REQUIRED.

Accidental Release

Spill Release Procedures:ELIM ALL IGNIT SOURCES. WEAR APPROPRIATE PERSONAL PROT EQUIP & NIOSH/MSHA APPRVD RESP. CONTAIN SPILL W/ABSORBENT MATERIAL AND PUT INTO VAPOR TIGHT CONTAINERS. PREVENT MATERIAL FROM CONTACTING ANY WATE R SOURCES OR SEWERS LEADING TO SURFACE WATERS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:STORE IN COMPLIANCE WITH GOOD HOUSEKEEPING PROCEDURES. PROTECT FROM FREEZING, STORE AT TEMPERATURES ABOVE 45F.

Other Precautions:GROUND CNTNRS WHEN POURING LIQ & POWDERS TO AVOID STATIC CHARGE BUILD UP. DO NOT HANDLE UNTIL MFR SAFETY PREC HAVE BEEN READ & UNDERSTOOD. PROVIDE ADEQ VENT/RESP PROT TO REMOVE DECOMP PRODS DURING WEL DING/FLAME CUTTING COATED (SUPP DATA)

Exposure Controls

Respiratory Protection:IN OUTDOOR/OPEN AREAS, USE NIOSH/MSHA APPRVD RESP TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY DURING APPLICATN. IN RESTRICTED VENT AREAS USE NIOSH/MSHA APPRVD RESP DESIGN TO REMOVE A COMBINATION O F PARTICLES AND VAPOR.

Ventilation:SUFFICIENT VENT, IN VOLUME & PATTERN, SHOULD BE PROVIDED TO KEEP AIR CONTAM CONC BELOW CURRENT APPLIC TLV AND PELS.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR USING WASHROOM FACILITIES.

Supplemental Safety and Health

OTHER PREC: SURFACES. PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:86.0F,30.0C

Vapor Pres:SEE INGRED

Vapor Density:HVR/AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:65.97

Stability

Stability Indicator/Materials to Avoid:YES

ANY MATERIAL THAT REACTS WITH WATER.

Stability Condition to Avoid:PROTECT FROM FREEZING.

Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN HEATED.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.