

## **TT-P-98C PAINT STENCIL FLAT CLASS I 32246 O**

### **MSDS Number**

BLCCC

### **National Stock Number**

8010-00N017158

### **Product Name**

TT-P-98C PAINT STENCIL FLAT CLASS I 32246 O

### **Manufacturer**

CON LUX COATINGS INC

### **Product Identification**

Product ID:TT-P-98C PAINT STENCIL FLAT CLASS I 32246 O

MSDS Date:03/27/1989

FSC:8010

NIIN:00N017158

MSDS Number: BLCCC

### **Responsible Party**

CON-LUX COATINGS INC

226 TALMADGE ROAD

EDISON , NJ 08818-0847

US

Emergency Phone: 201-287-4000

Cage: 60189

### **Contractor**

CON-LUX COATINGS INC

847

EDISON, NJ 08818-0847

US

732-287-4000

Cage: 60189

### **Ingredients**

VM&P NAPHTHA (LIGROINE)

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: >1%

OSHA PEL300 PPM/400 STEL

ACGIH TLV: 300 PPM; 9192

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 2 - 8%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

MOLYBDATE ORANGE.

CAS: 12656-85-8

RTECS: QA4660000

Fraction By Weight: 8%

OSHA PEL5 MG(MO)/M3

ACGIH TLV: 5 MG(MO)/M3

LEAD CHROMATE.

CAS: 1344-37-2

Fraction By Weight: 9%

OSHA PEL0.05 MG(CR)/M3

ACGIH TLV: 0.05 MG(CR)/M3

TALC (CONTAINING NO ASBESTOS)

CAS: 14807-96-6

RTECS: WW2710000

Fraction By Weight: >1%

OSHA PEL2 MG/M3 RDUST

ACGIH TLV: 2 MG/M3 RDUST; 9192

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight: >1%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

## Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: IRRITATION OF EYES AND SKIN MAY OCCUR WITH OVEREXPOSURE. CONTINUED BREATHING OF VAPORS MAY IRRITATE RESPIRATORY TRACT CAUSING HEADACHE, NAUSEA AND DIZZINESS. CHRONIC: REPORTS HAVE ASSOCIATED RE PEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

## First Aid

First Aid:INHAL:REMOVE TO FRESH AIR. RESTORE RESP IF NEC. TREAT SYMPTOMATICALLY. EYE:FLUSH IMMED W/COPIOUS QTYS OF WATER FOR AT LEAST 15 MIN. GET MD. SKIN:WASH AFFECTED AREAS W/SOAP & WATER. REMOVE CONTAM CLTHG . GET MD IF IRRIT PERSISTS. INGEST:DRINK 1/2

GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMIT. IF SPONT VOMIT OCCURS, KEEP HEAD AT/BELOW KNEE LEVEL TO PVNT ASPIR IN LUNGS. GET MD/POIS CTL CTR IMMED.

## Fire Fighting

Flash Point Method:TCC  
Flash Point:50.0F,10.0C  
Lower Limits:SEE INGRED  
Extinguishing Media:FOAM, CO\*2, DRY CHEMICAL, WATER MIST.  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . CONTAINS FLAMMABLE SOLVENT. DO NOT USE IN AREAS WHERE SPARKS OR OPEN FLAMES ARE PRESENT.  
Unusual Fire/Explosion Hazard:SMOTHER FLAMES WITH ONE OF THE ABOVE EXTINGUISHING MEDIA. WATER MAY BE USED TO COOL DOWN UNOPENED CONTAINERS IN VICINITY.

## Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. WEAR APPROPRIATE PERSONAL PROT EQUIP & NIOSH/MSHA APPRVD RESP. CONTAIN SPILL W/ABSORB MATL & PUT IN VAPOR TIGHT CNTNRS. PVNT MATL FROM CONTACTING ANY WATER SOURCES/S EWERS LEADING TO SURFACE WATERS.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:STORE IN AREAS DESIGNED TO COMPLY WITH ANSI/NFPA 30 FLAMMABLE & COMBUSTIBLE LIQUIDS CODE.  
Other Precautions:GROUND CNTNRS WHEN POURING LIQ & POWDERS TO AVOID STATIC CHARGE BUILD UP. DO NOT HANDLE UNTIL MFR SAFETY PREC HAVE BEEN READ & UNDERSTOOD. PROVIDE ADEQ VENT/RESP PROT TO REMOVE DECOMP PRODS DURING WEL DING/FLAME CUTTING COATED (SUPP DATA)

## Exposure Controls

Respiratory Protection:IN OUTDOOR/OPEN AREA, USE NIOSH/MSHA APPRVD RESP TO REMOVE SOLID AIRBORNE PARTICLES OF OVER SPRAY DURING SPRAY APPLICATION. IN RESTRICTED VENT AREAS, USE NIOSH/MSHA APPRVD RESP DESIGNED TO REMOVE A CO MBINATION OF PARTICLES AND VAPOR.  
Ventilation:SUFFICIENT VENT, IN VOLUME & PATTERN, SHOULD BE PROVIDED TO KEEP AIR CONTAM CONC BELOW CURRENT APPLIC OSHA PEL UNITS.  
Protective Gloves:IMPERVIOUS GLOVES.  
Eye Protection:CHEMICAL WORKERS GOGGLES .  
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.  
Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR USING WASHROOM FACILITIES.  
Supplemental Safety and Health  
INGRED 2-4 ARE REGULATED UNDER SARA TITLE III, SECTION 313. OTHER PREC: SURFACES. PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.

## Chemical Properties

Boiling Pt:B.P. Text:148F,64C  
Vapor Pres:SEE INGRED  
Vapor Density:HVR/AIR  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.  
Percent Volatiles by Volume:5-10

## Stability

Stability Indicator/Materials to Avoid:YES  
OXIDIZING AGENTS.  
Stability Condition to Avoid:EXTREME HEAT, SPARKS OR OPEN FLAMES.  
Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN HEATED.

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.