

ULTRA STICK RP 8OZ BRUSH TOP, 45051

MSDS Number

BLCDD

National Stock Number

8040-00N017190

Product Name

ULTRA STICK RP 8OZ BRUSH TOP, 45051

Manufacturer

PREMIER INDUSTRIAL CORP

Product Identification

Product ID:ULTRA STICK RP 8OZ BRUSH TOP, 45051

MSDS Date:01/27/1990

FSC:8040

NIIN:00N017190

MSDS Number: BLCDD

Responsible Party

PREMIER INDUSTRIAL CORPORATION

4500 EUCLID AVENUE

CLEVELAND , OH 44103

US

Emergency Phone: 216-391-8300

Info Phone: 216-391-8300

Preparer: G.F.S.

Cage: 18399

Contractor

PREMIER FARNELL CORPORATION

CLEVELAND, OH 44103-3736

US

216-391-8300

Cage: 18399

Ingredients

2-BUTANONE; (METHYL ETHYL KETONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 1-5%

OSHA PEL200 PPM;300 PPM STEL

ACGIH TLV: 200 PPM;300 PPM STEL

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

2-METHYL STYRENE RESIN

CAS: 25014-31-7

Fraction By Weight: >3%

POLYOXYETHYLENE SORBITOL

CAS: 9011-29-4

Fraction By Weight: >3%

HYDROCARBON RESIN

CAS: 8050-31-5

Fraction By Weight: >3%

SILICA (AMORPHOUS)

CAS: 112945-52-5

RTECS: VV7310000

Fraction By Weight: >3%

OSHA PEL6 MG/M3

ACGIH TLV: 10 MG/M3

STYRENE POLYMER WITH 1,3-BUTADIENE; (STYRENE BUTADIENE

CAS: 9003-55-8

RTECS: WL6478000

Fraction By Weight: >3%

3.39 LBS/GAL, 406 G/L.

RTECS: 9999999VO

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 21%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

HEXANE

CAS: 110-54-3

RTECS: MN9275000

Fraction By Weight: 11%

OSHA PEL500 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

HEPTANE

CAS: 142-82-5

RTECS: MI7700000

Fraction By Weight: 11%

OSHA PEL500 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9293

Hazards

LD50 LC50 Mixture:LD50:(ORAL,RAT) 2737 MG/KG.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NOTE:TOLUENE (108-88-3) APPEARS ON NAVY LIST OF OCCUP CHEMICAL REPRO HAZS. CONSULT WITH APPROP HLTH PROFS CONCERNING LATEST HAZ LIST INFO & SAFE HNDLG & EXPOS RECS . CAUSES EYE IRRIT. MAY CAUSE IRRIT OF SKIN. EXCESS INHAL MAY CAUSE DIZZ, GIDD & NAUS. RPTD & PRLNG OVEREXP TO SOLVS MAY CAUSE PERM (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ:DMG TO CNS. PRLNG & RPTD INHAL MAY BE HARMFUL TO RESP SYSTEM, CNS, LIVER & KIDNEYS. HARMFUL IF SWALLOWED.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:EYE: IMMED FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CALL PHYS. SKIN: WASH THOROUGHLY WITH PLENTY OF SOAP AND WATER.

INHAL: MOVE TO FRESH AIR, ADMINISTER OXYGEN, CALL PHYS. INGEST:

SEEK P HYS IMMED, SHOW MSDS OR LABEL, DO NOT INDUCE VOMITING.

Fire Fighting

Flash Point:-7F,-22C

Lower Limits:1.2

Upper Limits:10

Extinguishing Media:FOAM, DRY CHEMICAL, CO*2, WATERFOG.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL

PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:IF USED IN CONFINED SPACES, HAZARDOUS

VAPORS MAY SPREAD, BURN OR BUILD UP IN LOW AREAS.

Accidental Release

Spill Release Procedures:EVAC AREA. REMOVE ALL SOURCES OF IGNITION.

VENT AREA. WEAR NIOSH/MSHA APPRVD RESP PROT. PROT CLOTHING, GLOVES,

EYE/FACE PROT. CLEAN UP WITH ABSORBENT MATL. CONTAIN AND PICK UP

WASTE MATERIAL, PUT IN A SEALED APPROVED CONTAINER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:USE ONLY IN WELL VENTED AREAS. KEEP

AWAY FROM HEAT, SPKS, FLAMES/SOURCES OF IGNIT. AVOID PRLNG/RPTD

BRTHG OF GAS, FUMES, VAP/SPRAY MIST.

Other Precautions:AVOID PRLNG & RPTD CONT W/SKIN. DO NOT TAKE

INTERNALLY. IN CASE OF ACCIDENT/ILLNESS, SEEK MD IMMED & SHOW

LBL/MSDS. KEEP OUT OF REACH OF CHILDREN. DO NOT EMPTY INTO DRAINS.

ALWAYS READ & FOLLOW DIRECT IONS ON PROD LBL. ADDNL MSDS'S (SUPDAT)

Exposure Controls

Respiratory Protection:USE ONLY IN WELL VENTILATED AREA. IF VENTILATION IS INADEQUATE, WEAR NIOSH/MSHA APPROVED RESPIRATORY EQUIPMENT.

Ventilation:LOCAL & MECHANICAL VENTILATION REQUIRED. KEEP AWAY FROM HEAT OR FLAME.

Protective Gloves:SOLVENT RESISTANT.

Eye Protection:CHEMICAL WORKER GOGGLESS .

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH THOROUGHLY AFTER USING.
Supplemental Safety and Health
OTHER PREC:ARE AVAILABLE UPON REQUEST. FOR PROFESSIONAL & INDUSTRIAL
USE ONLY.

Chemical Properties

HCC:F2
Boiling Pt:B.P. Text:156F,69C
Melt/Freeze Pt:M.P/F.P Text:-139F,-95C
Vapor Pres:127
Vapor Density:3
Spec Gravity:0.89
Evaporation Rate & Reference:14.5 (BUTYL ACETATE=1)
Solubility in Water:SOLUBLE
Appearance and Odor:PASTE-LIKE LIQUID W/TOLUENE ODOR.
Percent Volatiles by Volume:49

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS.
Stability Condition to Avoid:KEEP AWAY FROM HEAT, SPARKS, FLAMES, OR
SOURCES OF IGNITION.
Hazardous Decomposition Products:CO, SMOKE, PYROLYSIS PRODUCTS.

Disposal

Waste Disposal Methods:DISPOSE OF WASTES I/A/W FEDERAL, STATE & LOCAL
REGULATIONS. DO NOT EMPTY INTO DRAINS. HAZ WASTE #: D001, U220,
U159 (FLAMMABLE, TOXIC). REPORTABLE QTY: 4762 LBS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.