

## **COVENTRY S/G SUPER WHITE 0133517**

### **MSDS Number**

BLCFM

### **National Stock Number**

8010-00N017258

### **Product Name**

COVENTRY S/G SUPER WHITE 0133517

### **Manufacturer**

MOBILE PAINT MANUFACTURING CO INC

### **Product Identification**

Product ID: COVENTRY S/G SUPER WHITE 0133517

MSDS Date: 03/22/1991

FSC: 8010

NIIN: 00N017258

MSDS Number: BLCFM

### **Responsible Party**

MOBILE PAINT MANUFACTURING CO INC

THEODORE , AL 36582

US

Emergency Phone: 800-255-3924

Info Phone: 205-443-6110

Preparer: JULIE HOAGLAND

Cage: 88663

### **Contractor**

MOBILE PAINT MANUFACTURING CO INC

717

THEODORE, AL 36582

US

334-443-6110

Cage: 88633

### **Ingredients**

0.1.

CAS: 57-55-6

RTECS: TY2000000

Fraction By Weight: 5%

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 20 - 25%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

### **Hazards**

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHAL:MAY CAUSE HEADACHE, NAUSEA, AND IRRITATION OF NOSE, THROAT AND LUNGS. SKIN:POSSIBLE PRIMARY SKIN IRRITATION (MATERIAL IS SLIGHTLY ALKALINE). EYE:PRIMARY IRRITATION. (SENSITIZER TO SOME PEOPLE).  
Explanation of Carcinogenicity:NOT RELEVANT.  
Effects of Overexposure:SEE HEALTH HAZARDS.  
Medical Cond Aggravated by Exposure:MAY PROVOKE ASTHMATIC RESPONSE IN PERSONS WITH ASTHMA WHO ARE SENSITIVE TO AIRWAY IRRITANTS.

## First Aid

First Aid:INHAL:REMOVE TO FRESH AIR. SKIN:REMOVE WITH SOAP AND WATER. REMOVE AND LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. EYE:FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MD. IN GEST:DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CALL MD OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

## Fire Fighting

Flash Point:NO FLASH  
Lower Limits:2.6%  
Upper Limits:12.5%  
Extinguishing Media:FOAM, ALCOHOL FOAM, CO\*2, DRY CHEMICAL, WATER FOG.  
Fire Fighting Procedures:CLOSED CONTAINERS MAY EXPLODE, DUE TO BUILD-UP OF STEAM PRESS WHEN EXPOSED TO EXTREME HEAT. WATER MAY BE USED TO COOL CLSD CNTNRS TO PVNT PRESS BUILD(SUPP DATA)  
Unusual Fire/Explosion Hazard:MATERIAL MAY SPLATTER WHEN TEMPERATURE GOES ABOVE 212F. DRIED SOLIDS MAY BURN, GIVING OFF OXIDES OF CARBON.

## Accidental Release

Spill Release Procedures:FLOOR MAY BE SLIPPERY, USE CARE TO AVOID FALLS. DIKE AND ABSORB WITH INERT MATERIAL, TRANSFER TO CONTAINER FOR DISPOSAL. KEEP SPILL OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

## Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. DO NOT FREEZE. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106. KEEP CONTAINERS CLOSED.

Other Precautions:USE WITH ADEQUATE VENTILATION. AVOID CONTACT WITH SKIN AND CLOTHING. WASH THOROUGHLY AFTER HANDLING. DO NOT HANDLE UNTIL THE MANUFACTURERS SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.

## Exposure Controls

Respiratory Protection:IN OPEN AREAS OF USE NIOSH/MSHA APPRVD MECH FILTER RESP TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY DURING SPRAY APPLIC. IN RESTRICTED VENT AREAS USE NIOSH/MSHA APPROVED RESPIRATOR TO REMOVE A COM BINATION OF PARTICULATES AND VAPOR.

Ventilation:PROVIDE VENTILATION IN VOLUME AND PATTERN TO KEEP TLV OF HAZ INGREDIENTS BELOW ACCEPTABLE LIMIT, LEL BELOW (SUPP DATA)

Protective Gloves:USE GLOVES IMPERVIOUS TO WATER & SOAP.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:USE PROTECTIVE OUTERWEAR & PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.

Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING, SMOKING OR DRINKING, AND AT THE END OF EACH WORK PERIOD.

Supplemental Safety and Health

AFIRE FIGHT PROC:UP AND POSSIBLE EXPLOSION WHEN EXPOSED TO EXTREME HEAT. WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .

VENT:STATED LIMIT, AND TO REMOVE DECOMPOSITION PRODUCTS DUR ING WELDING OR FLAME CUTTING ON SURFACES COATED WITH THIS PRODUCT.

---

## Chemical Properties

HCC:B3  
Boiling Pt:B.P. Text:369F,187C  
Vapor Density:LTR/AIR  
Spec Gravity:1.2  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:DILUTABLE  
Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

## Stability

Stability Indicator/Materials to Avoid:YES  
NONE.  
Stability Condition to Avoid:FIRE.  
Hazardous Decomposition Products:OXIDIZING MATERIALS WILL BE GIVEN OFF.

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND  
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.