

75-313

MSDS Number

BLCGV

National Stock Number

9150-00N017308

Product Name

75-313

Manufacturer

VALVOLINE OIL CO

Product Identification

Product ID:75-313
MSDS Date:01/26/1988
FSC:9150
NIIN:00N017308
MSDS Number: BLCGV

Responsible Party

VALVOLINE OIL CO
ASHLAND , KY 41114
US

Emergency Phone: 606-324-1133

Info Phone: 606-329-3333

Cage: 72527

Contractor

VALVOLINE OIL CO
14000
LEXINGTON, KY 40512
US
606-357-7206 / 800-274-5263
Cage: 72527

Ingredients

PETROLEUM BASED-LUBRICATING OIL

SPILL TO PRVNT SPREADING, PUMP LIQ TO SALVAGE

RTECS: 9999999ZZ

FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL &

RTECS: 9999999ZZ

(SEE YOUR SAFETY EQUIP SUPPLIER). ENGINEERING OR

RTECS: 9999999ZZ

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TOXICOLOGICAL TESTING INDICATES THAT
SIMILAR PRODUCTS ARE NOT HAZARDOUS AS DEFINED BY OSHA (29 CFR
1910.1200).
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:SKIN:THORO WASH EXPOSED AREA W/SOAP & WATER. REMOVE CONTAMD
CLTHG. LAUNDER CLTHG BEFORE REUSE. EYES: FLUSH W/LG AMTS OF H*2O,
LIFTING UPPER/LOWER LIDS OCCASNLY, GET MD ATTN. INGEST: IMMED DRINK
2 GLAS SES OF H*2O/INDUCE VOMIT BY EITHER GIVING IPECAC SYRUP OR BY
PLACING FINGER AT BACK OF THROAT. NEVER GIVE ANYTHING BY MOUTH TO
UNCONC PERSON. GET MD ATTN IMMED. IF BRTHG AFFECTED REMOVE TO(SUPP
DATA)

Fire Fighting

Flash Point:400F,204C
Extinguishing Media:REGULAR FOAM, CARBON DIOXIDE, OR DRY CHEMICALS.
Fire Fighting Procedures:WEAR NIOSH/MSHA APRVD SCBA AND FULL PROTECTIVE
EQUIPMENT . H*2O/FOAM MAY CAUSE FROTHING WHICH CAN BE VIOLENT &
POSS ENDANGER LIFE (SUPP DATA)
Unusual Fire/Explosion Hazard:NEVER USE WELDING/CUTTING TORCH ON OR
NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT(EVEN JUST RESIDUE) CAN
IGNITE EXPLOSIVELY.

Accidental Release

Spill Release Procedures:SM:ABSORB LIQ ON PAPER,VERMICULITE,FLOOR
ABSORB/OTHER ABSORB MATL/TRANSFER TO HOOD.LG:PRVNT RUN-OFF TO
SEWERS,STREAMS, OR OTHER BODIES OF H*2O.IF RUN-OFF OCCURS,NOTIFY
PROPER AUTH AS REQ,THAT SPILL HA S OCCURED.PERS NOT WEARING PROT
EQUIP (SUPP DATA)
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:DO NOT TRANSFER TO UNLABELED
CONTAINER. DO NOT USE CUTTING/WELDING TORCH ON THIS CONTAINER(EVEN
EMPTY).
Other Precautions:FOR INDUSTRIAL USE ONLY. REFER TO MATERIAL SAFETY
DATA SHEET(AVAILABLE UPON REQUEST)FOR FURTHER INFORMATION. 24-HOUR
EMERGENCY NUMBER: 1-800-ASHLAND.

Exposure Controls

Respiratory Protection:IF WORKPLACE EXPOS LIMITS OF PROD OR ANY
COMPONENT IS EXCEEDED A NIOSH/MSHA APPRVD AIR SUPP RESP IS ADVISED
IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL.OSHA REGS ALSO PERMIT
OTHER NIOSH/MSHA RESP (NEG PRESS TYPE)UNDER SPECD CNDTNS(SEE ING
4)
Ventilation:PROVIDE SUFFICIENT MECHANICAL (GEN &/OR LOCAL EXHAUST) VENT
TO MAINTAIN EXPOSURE BELOW TLV.
Protective Gloves:WEAR RESISTANT GLOVES SUCH AS NEOPRENE.
Eye Protection:CHEMICAL WORKERS GOGGLES .
Other Protective Equipment:WEAR IMPERVIOUS CLOTHING AND BOOTS.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
FIRE FIGHT PROC:ESPECIALLY IF SPRAYED INTO CNTNRS OF HOT, BURNING LIQ.
FIRST AID PROC:FRESH AIR. IF BRTHG IS DFCLT,ADMIN O*2. IF BRTHG HAS
STOPPED GIVE ARTF RESP. KEEP WARM, QUIET & GET MD ATTN. SPILL
PROC: SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN
COMPLETED. STOP SPILL AT SOURCE. DIKE AREA OF(ING2)

Chemical Properties

HCC:V6
Boiling Pt:B.P. Text:>425F,>218C
Vapor Density:HVR/AIR
Spec Gravity:0.876 @60F

Evaporation Rate & Reference: SLOWER THAN ETHER
Appearance and Odor: LIQUID, HOMOGENOUS SOLUTION

Stability

Stability Indicator/Materials to Avoid: YES
AVOID CONTACT WITH STRONG OXIDIZING AGENTS.
Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products: MAY FORM TOXIC MATERIALS: CARBON DIOXIDE, CARBON MONOXIDE, VARIOUS HYDROCARBONS, ETC.

Disposal

Waste Disposal Methods: SM: ALLOW VOLATILE PORTION TO EVAP IN HOOD. ALLOW ENOUGH TIME FOR VAPORS TO COMPLETELY CLEAR HOOD DUCT WORK. DISPOSE OF REMAINING MATL I/A/W APPLIC REGS. LG: DESTROY BY LIQ INCIN. CONTAMD ABSORB MAY BE DEPOSITED IN LANDFILL I/A/W LOCAL, STATE & FED REGS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.