

RUST SCAT/URETHANE ALKYD, 31-192 SATIN BLAC

MSDS Number

BLCHN

National Stock Number

8010-00N017350

Product Name

RUST SCAT/URETHANE ALKYD, 31-192 SATIN BLAC

Manufacturer

CORONADO PAINT COMPANY

Product Identification

Product ID:RUST SCAT/URETHANE ALKYD, 31-192 SATIN BLAC

MSDS Date:12/16/1987

FSC:8010

NIIN:00N017350

MSDS Number: BLCHN

Responsible Party

CORONADO PAINT COMPANY

308 OLD COUNTY ROAD

EDGEWATER , FL 32032

US

Emergency Phone: 904-428-6461

Info Phone: 904-428-6461

Cage: 33200

Contractor

CORONADO PAINT COMPANY, INC.

EDGEWATER, FL 32132-1812

US

904-428-6461

Cage: 33200

Ingredients

PIGMENTS

Fraction By Weight: 20.9%

VEHICLE

Fraction By Weight: 30.6%

ALIPHATIC HYDROCARBONS

Fraction By Weight: 48.5%

OSHA PEL500 PPM (MFR)

ACGIH TLV: 500 PPM (MFR)

Hazards

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PRODUCES SEVERE EYE IRRITATION, DRYING
OF SKIN. EXCESSIVE INHALATION CAUSES HEADACHE, DIZZINESS, NAUSEA.
Explanation of Carcinogenicity:NOT RELEVANT.
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:EYE: FLUSH WITH WATER FOR AT LEAST 15 MIN. SKIN: WASH WITH
MILD SOAP AND WATER AND APPLY SKIN CREAM. INHAL: REMOVE TO FRESH
AIR AND CALL PHYS. APPLY ARTIFICIAL RESPIRATION IF NECESSARY.
INGEST: SEEK M D IMMED .

Fire Fighting

Flash Point Method:SCC
Flash Point:104F,40C
Lower Limits:1.1%
Upper Limits:6.0%
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL
PROTECTIVE EQUIPMENT . WATER IS NOT ORDINARILY EFFECTIVE, TENDS TO
SCATTER LIQUID AND SPREAD FIRE.
Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURES WITH
AIR.

Accidental Release

Spill Release Procedures:WEAR NIOSH/MSHA APPROVED RESPIRATOR. FLUSH
WITH WATER INTO RETAINING AREA OR CONTAINER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, OPEN
FLAME. USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED
SKIN CONTACT.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

Exposure Controls

Respiratory Protection:WEAR NIOSH/MSHA APPROVED RESPIRATOR IF TLV IS
EXCEEDED.
Ventilation:LOCAL EXHAUST.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:CHEMICAL WORKERS GOGGLES .
Other Protective Equipment:EYE BATH AND SAFETY SHOWER.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:300
Vapor Pres:2
Vapor Density:>1
Spec Gravity:1.125
Evaporation Rate & Reference:Solubility in Water:NEGLIGIBLE
Appearance and Odor:BLACK OPAQUE LIQUID, MINERAL SPIRITS ODOR.
Percent Volatiles by Volume:71.9

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS.
Stability Condition to Avoid:EXCESSIVE HEAT, SPARKS, OPEN FLAMES.
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON
MONOXIDE.

Disposal

Waste Disposal Methods:LAND FILL, INCINERATION UNDER SAFE AND
SUPERVISED CONDITIONS. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE

AND LOCAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.