

6-84 SPEEDHITE FLAT OFF WHITE LATEX

MSDS Number

BLPJT

National Stock Number

8010-00F019089

Product Name

6-84 SPEEDHITE FLAT OFF WHITE LATEX

Manufacturer

PPG INDUSTRIES INC

Product Identification

Product ID:6-84 SPEEDHITE FLAT OFF WHITE LATEX

MSDS Date:10/30/1981

FSC:8010

NIIN:00F019089

MSDS Number: BLPJT

Responsible Party

PPG INDUSTRIES INC

ONE GATEWAY CENTER

PITTSBURGH , PA 15222

Emergency Phone: (304) 843-1300

Info Phone: (304) 843-1300

Cage: 93915

Contractor

PPG INDUSTRIES INC CHEMICAL DIVISION

PITTSBURGH, PA 15222-1416

US

304-843-1300

Cage: 93915

Ingredients

2,2,4 TRIMETHYLPENTANEDIOL 1,3 MONOISOBUTYRATE

Fraction By Weight:

ALIPHATIC HYDROCARBON MIXTURE

CAS: 68514-35-2

Fraction By Weight:

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: HEADACHE & NAUSEA.
SKIN/EYES: IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: HEADACHES & NAUSEA. SKIN/EYES:
IRRITATION.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH W/COPIOUS
QUANTITIES OF RUNNING WATER FOR AT LEAST 15 MINS. SKIN: REMOVE
W/SOAP & WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:PMCC

Flash Point:>200F

Fire Fighting Procedures:IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.

Unusual Fire/Explosion Hazard:WATER SPRAY MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP, POSSIBLE EXPLOSION OR BURSTING WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:RETURN MATERIAL TO CONTAINER.

Handling

Handling and Storage Precautions:PROTECT FROM FREEZING.

Other Precautions:DON'T TAKE INTERNALLY. DON'T FLAME CUT, BRAZE, OR WELD W/O NIOSH APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.

Exposure Controls

Respiratory Protection:OUTDOOR/OPEN AREAS: USE FILTER RESPIRATOR TC21C TO REMOVE SOLID AIRBORNE PARTICULATES FROM OVERSPRAY. USE COMBINATION ORGANIC VAPOR-FILTER RESPIRATORS TC23C DESIGNED TO PURIFY THE AIR BY REMOVING SOLID AIRBORNE PARTICULATES/ORGANIC VAPORS.

Ventilation:GENERAL DILUTION OR LOCAL EXHAUST IN VOLUME & PATTERN TO KEEP Protective Gloves:AS REQUIRED

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:AS NEEDED

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:112-495F

Vapor Density:Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:WHITE LIQUID

Percent Volatiles by Volume:68.98%

Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:PROTECT FROM FREEZING.

Hazardous Decomposition Products:CO

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.