

207 SOLVENT BASED ARCHITECTURAL COATING

MSDS Number

BLQWG

National Stock Number

8010-00F019725

Product Name

207 SOLVENT BASED ARCHITECTURAL COATING

Manufacturer

O'BRIEN CORP

Product Identification

Product ID:207 SOLVENT BASED ARCHITECTURAL COATING

MSDS Date:03/01/1990

FSC:8010

NIIN:00F019725

MSDS Number: BLQWG

Responsible Party

O'BRIEN CORPORATION

450 EAST GRAND AVENUE

SOUTH SAN FRANCISCO , CA 94080

Emergency Phone: (800) 338-8084

Info Phone: (800) 338-8084

Preparer: CECILIA R STODDARD

Cage: 91988

Contractor

O'BRIEN CORPORATION

SOUTH SAN FRANCISCO, CA 94080

(800) 338-8084

Cage: 91988

Ingredients

CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 5%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9192

CARBON BLACK

CAS: 1333-86-4

RTECS: FF5800000

Fraction By Weight: 5 - 10%

OSHA PEL3.5 MG/M3

ACGIH TLV: 3.5 MG/M3; 9192

CHROMIUM (SARA III)

CAS: 7440-47-3

RTECS: GB4200000

Fraction By Weight:

OSHA PEL1 MG/M3

ACGIH TLV: 0.5 MG/M3; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

SILICA, CRYSTALLINE - QUARTZ

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight:

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

SILICA, CRYSTALLINE - CRISTOBALITE

CAS: 14464-46-1

RTECS: VV7325000

Fraction By Weight:

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.05 MG/M3 RDUST9293

ETHYL SILICATE

CAS: 78-10-4

RTECS: VV9450000

Fraction By Weight:

OSHA PEL100 PPM

ACGIH TLV: 10 PPM; 9293

MICA - SILICATES (< 1% CRYSTALLINE SILICA)

CAS: 12001-26-2

RTECS: VV8760000

Fraction By Weight:

OSHA PEL20 MPPCF

ACGIH TLV: 3 MG/M3 RDUST; 9293

MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPTHANES

CAS: 64742-88-7

Fraction By Weight: 60%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

SILICON DIOXIDE

CAS: 7631-86-9

RTECS: VV3100000

Fraction By Weight:

OSHA PEL80 MG/CUM

ACGIH TLV: 10 MG/CUM

TALC (CONTAINING NO ASBESTOS)

CAS: 14807-96-6

RTECS: WW2710000

Fraction By Weight: 5%

OSHA PEL2 MG/M3 RDUST

ACGIH TLV: 2 MG/M3 RDUST; 9192

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 15 - 20%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight:

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ZINC OXIDE

CAS: 1314-13-2

RTECS: ZH4810000

Fraction By Weight:

OSHA PEL15MG/M3 TDUST/5 FUME

ACGIH TLV: 10MG/M3 TDUST; 9293

250-440 G/L

RTECS: 9999999VO

ALUMINUM (SARA III)

CAS: 7429-90-5

RTECS: BD0330000

Fraction By Weight: 5%

OSHA PEL15MG/M3 DUST/5 FUME

ACGIH TLV: 10MG/M3 DUST; 9192

SOLVENT NAPHTHA, PETROLEUM, LIGHT AROMATIC C8-C10 (AROMATIC

CAS: 64742-95-6

Fraction By Weight:

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

BARIUM SULFATE

CAS: 7727-43-7

RTECS: CR0600000

Fraction By Weight:

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

BENZENE (SARA III)

CAS: 71-43-2

RTECS: CY1400000

Fraction By Weight:

OSHA PEL1PPM/5STEL;1910.1028

ACGIH TLV: 10 PPM; A2; 9192

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:INGESTION:

MOUTH/THROAT/GASTROINTESTINAL TRACT IRRITATION & CNS DEPRESSION.

INHALATION: ANESTHETIC, RESPIRATORY TRACT IRRITATION & NERVOUS

SYSTEM DEPRESSION. EYES: IRRITATION & BLURRED VISION. SKIN: I

RRITATION, DERMATITIS, RASH, & SENSITIZER.

Explanation of Carcinogenicity:CARBON BLACK, CHROMIUM, CRYSTALLINE

SILICA, AS QUARTZ/CRISTOBALITE ARE SUSPECTED HUMAN CARCINOGENS.

Effects of Overexposure:INHALATION: PULMONARY/HEART CHANGES, POISONING

EFFECTS TO KIDNEYS/LUNGS/LIVER/BLOOD CELLS, SILICOSIS, DELAY LUNG

INJURY, PNEUMONCONIOSIS, PULMONARY FIBROSIS. PERMANENT BRAIN, CNS,

KIDNEY, LIVER, LUNGS , BLOOD CELLS, BLOOD PRODUCING ORGANS, BLOOD

STORING ORGAN, & PERIPHERAL NERVOUS SYSTEM DAMAGE.

Medical Cond Aggravated by Exposure:LUNG DISEASES

First Aid

First Aid:INGESTION: DRINK 1-2 GLASSES OF WATER. KEEP WARM/QUIET.

CONSULT PHYSICIAN BEFORE INDUCING VOMITING. NEVER GIVE ANYTHING BY

MOUTH TO AN UNCONSCIOUS PERSON. INHALATION: REMOVE TO FRESH AIR.

RESTORE BREA THING. EYES: FLUSH W/WATER FOR 15 MINS.SKIN: WIPE OFF

W/RAG & WASH W/SOAP & WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.
NOTE TO PHYSICIAN: SEE SUPPLEMENTAL.

Fire Fighting

Flash Point:105F
Lower Limits:1%
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, OR WATER FOG.
Fire Fighting Procedures:USE FULL PROTECTIVE EQUIP & SCBA. USE WATER TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP & AUTO-IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.
Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID.

Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION. SOAK UP & REMOVE W/INERT ABSORBENT MATERIAL W/NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:STORE UPRIGHT IN SEALED CONTAINERS & USE AWAY FROM HIGH TEMPS, SPARKS, FLAME, & ELECTRICAL EQUIPMENT. KEEP CONTAINER TIGHTLY SEALED WHEN NOT IN USE.
Other Precautions:KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT W/SKIN. DON'T INGEST. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS. AVOID BREATHING VAPOR OR SPARY MIST DURING MIXING, SPRAYING, APPLICATION OR CURING. PROVIDE ADEQUATE VENTILATION.

Exposure Controls

Respiratory Protection:USE A NIOSH/MSHA APPROVED PROPERLY FITTED MECHANICAL RESPIRATOR/MASK DURING MIXING, SPRAYING, APPLICATION OR CURING. USE A NIOSH/MSHA APPROVED PROPERLY FITTED POSITIVE AIR SUPPLIED RESPIRATOR IN CONFINE D AREAS OR IF OVERSPRAYING IS PRESENT.
Ventilation:SUFFICIENT IN VOLUME & PATTERN TO KEEP AIR CONTAMINATION
Protective Gloves:RECOMMENDED
Eye Protection:GOGGLES, SAFETY GLASSES W/SIDE SHIELDS
Other Protective Equipment:PROTECTIVE OVERALLS
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. DISCARD CONTAMINATED SHOES.
Supplemental Safety and Health
11 LB/GAL. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING/INHALING THE CONTENTS MAY BE HARMFUL/FATAL. PHYSICIAN NOTE: BIOLOGICAL INDICES INCLUDE PHENOL, METHYLHIPURIC ACIDS IN URINE, & BENZENE IN EXHALED AIR. BENZENE/CHROMIUM/MINERAL SPIRITS/TALC ARE KNOWN TO CALIFORNIA TO CAUSE CANCER OR REPRODUCTIVE TOXICITY.

Chemical Properties

Boiling Pt:B.P. Text:241-419F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:60%

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS, ACIDS, & BASES.
Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, FLAME, HEAT, OR OTHER SOURCES OF IGNITION.
Hazardous Decomposition Products:CO, CO2, & NITROGEN DIOXIDE.

Disposal

Waste Disposal Methods:DISPOSE IN SEALED CONTAINER AWAY FROM HEAT & FLAME IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS. COMBUSTIBLE LIQUID. UN1263.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.