

METHANOL, 9049

MSDS Number

BLTVQ

National Stock Number

6810-00N023021

Product Name

METHANOL, 9049

Manufacturer

J T BAKER COMPANY

Product Identification

Product ID:METHANOL, 9049

MSDS Date:05/01/1989

FSC:6810

NIIN:00N023021

MSDS Number: BLTVQ

Responsible Party

J.T. BAKER COMPANY

222 RED SCHOOL LANE

PHILLIPSBURG , NJ 08865-2219

US

Emergency Phone: 908-859-2151/800-424-9300(CHEMTREC)

Info Phone: 908-859-2151

Preparer: QUALITY ASSURANCE DEPT

Cage: 70829

Contractor

MALLINCKRODT BAKER, INC.

PHILLIPSBURG, NJ 08865

US

800-582-2537

Cage: 70829

Ingredients

METHANOL; (METHYL ALCOHOL)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight: 90-100%

OSHA PELS,200PPM/250STEL

ACGIH TLV: S,200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

LD50 LC50 Mixture:LD50:(ORAL,RAT)5628 MG/KG.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL:HARMFUL & MAY BE FATAL,

HEADACHE, NAUSEA, VOMITING, DIZZINESS, NARCOSIS, RESPIRATORY FAILURE, LOW BLOOD PRESSURE, CENTRAL NERVOUS SYSTEM DEPRESSION. SKIN:IRRITATION, PROLONGED CONTACT MAY CAUSE DERMATITIS. EYE:IRRITATION, MAY CAUSE TEMPORARY CORNEAL DAMAGE. INGEST:HARMFUL & MAY BE FATAL, (SEE EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ:BLINDNESS, HEADACHE, NAUSEA, VOMITING, DIZZINESS, GASTROINTESTINAL IRRITATION, CENTRAL NERVOUS SYSTEM DEPRESSION, HEARING LOSS. CHRONIC: KIDNEY & LIVER DAMAGE. TARGET ORGANS:EYES, SKIN, CENTR AL NERVOUS SYSTEM, GI TRACT, RESPIRATORY SYSTEM, LUNGS.

Medical Cond Aggravated by Exposure:EYE DISORDERS, SKIN DISORDERS, LIVER OR KIDNEY DISORDERS.

First Aid

First Aid:INGEST:CALL MD. IF CONSCIOUS, GIVE LG AMTS OF WATER. INDUCE VOMITING. INHAL:REMOVE TO FRESH AIR. IF NOT BRTHG, GIVE ARTF RESP. IF BRTHG DFCLT, GIVE O*2. SKIN:IMMED FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MIN WHILE REMOVING CONTAMD CLTHG & SHOES. WASH CLTHG BEFORE RE-USE. EYE:IMMED FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MIN.

Fire Fighting

Flash Point Method:CC

Flash Point:54.0F,12.2C

Lower Limits:6%

Upper Limits:36%

Extinguishing Media:USE ALCOHOL FOAM, DRY CHEMICAL OR CARBON DIOXIDE. (WATER MAY BE INEFFECTIVE.)

Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP . MOVE CNTNRS FROM FIRE AREA IF CAN BE DONE W/O RISK. USE WATER TO KEEP FIRE-EXPOSED CNTNRS COOL.

Unusual Fire/Explosion Hazard:VAPS MAY FLOW ALONG SURFS TO DISTANT IGNIT SOURCES & FLASH BACK. CLOSED CNTNRS EXPOSED TO HEAT MAY EXPLODE. CNTCT W/STRONG OXIDIZERS MAY CAUSE FIRE. (SUPP DATA)

Accidental Release

Spill Release Procedures:WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT CLTHG. SHUT OFF IGNIT SOURCES; NO FLARES, SMOKING/FLAMES IN AREA. STOP LEAK IF CAN DO SO W/O RISK. USE WATER SPRAY TO REDUCE VAPS. TAKE UP W/SAND/OTHER NON-COMB UST ABSORB MATL & PLACE INTO CNTNR FOR (SUPP DATA)

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED. STORE IN COOL, DRY, WELL-VENTILATED, FLAMMABLE LIQUID STORAGE AREA.

Other Precautions:BOND & GROUND CNTNRS WHEN TRANSFERRING LIQ. FLAMM. CANNOT BE MADE NON-POISONOUS. KEEP AWAY FROM HEAT, SPARKS, FLAME. DO NOT GET IN EYES, ON SKIN/CLTHG. AVOID BRTHG VAP. USE W/ADEQ VENT.

Exposure Controls

Respiratory Protection:RESPIRATORY PROTECTION REQUIRED IF AIRBORNE CONCENTRATION EXCEEDS TLV. AT CONCENTRATIONS ABOVE 200 PPM, A NIOSH/MSHA APPROVED SCBA IS ADVISED.

Ventilation:USE GENERAL OR LOCAL EXHAUST VENTILATION TO MEET TLV REQUIREMENTS.

Protective Gloves:RUBBER GLOVES RECOMMENDED.

Eye Protection:CHEM WORK GOG & FULL LENGTH FSHLD.

Other Protective Equipment:UNIFORM AND PROTECTIVE SUIT.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

EXPLO HAZ:BURNS W/CLEAR, ALMOST INVISIBLE FLAME. SPILL PROC:LATER DISPOSAL. FLUSH AREA W/WATER. J.T. BAKER SOLUSORB(R) SOLVENT ADSORBENT IS RECOMMENDED FOR SPILLS OF THIS PRODUCT.

Chemical Properties

HCC:F5
Boiling Pt:B.P. Text:149F,65C
Melt/Freeze Pt:M.P/F.P Text:-144F,-98C
Vapor Pres:96 @ 20C
Vapor Density:1.11
Spec Gravity:0.79
Evaporation Rate & Reference:4.6 (BUTYL ACETATE = 1)
Solubility in Water:COMPLETE (100%)
Appearance and Odor:CLEAR, COLORLESS LIQUID, PUNGENT ODOR.
Percent Volatiles by Volume:100

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG ACIDS, ZINC, ALUMINUM, MAGNESIUM.
Stability Condition to Avoid:HEAT, FLAME, OTHER SOURCES OF IGNITION.
Hazardous Decomposition Products:CO, CO*2, FORMALDEHYDE.

Disposal

Waste Disposal Methods:DISPOSE I/A/W ALL APPLICABLE FEDERAL, STATE, AND
LOCAL ENVIRONMENTAL REGULATIONS. EPA HAZ WASTE #U154.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.