

ROHCO ARMOR HB-65

MSDS Number

BLWJJ

National Stock Number

6810-00N016675

Product Name

ROHCO ARMOR HB-65

Manufacturer

MCGEAN ROHCO INC

Product Identification

Product ID:ROHCO ARMOR HB-65 MSDS Date:03/01/1991 FSC:6810

NIIN:00N016675 MSDS Number: BLWJJ

Responsible Party

MCGEAN-ROHCO INC

1250 TERMINAL TOWER

CLEVELAND, OH 44113

Emergency Phone: 216-441-4900,800-424-9300(CHEMTREC)

Info Phone: 216-621-6425
Preparer: TSCA COORDINATOR

Cage: 02984

Contractor

MCGEAN-ROHCO INC

DETROIT, MI 48208-1742

_ . _ . .

US

216-441-4900 Cage: 02984

Ingredients

1)

CAS: 7786-81-4 RTECS: QR9350000

Fraction By Weight: 10%

OSHA PEL1 MG NI/M3

ACGIH TLV: 0.1 MG NI/M3; 9293 EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

Hazardo

Hazards

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation: YES Skin: YES Ingestion: NO Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic:PRIMARY ENTRY THROUGH SKIN. POSSIBLE

SKIN SENSITIZATION RESULTING IN CHRONIC ECZEMA OR NICKEL ITCH.

Explanation of Carcinogenicity: NOT RELEVANT.



Effects of Overexposure: NONE SPECIFIED BY MANUFACTURER. Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid: WASH SKIN WITH SOAP AND WATER. FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. IF ANY IRRITATION PERSISTS, SEE A PHYSICIAN.INGEST: GET MD IMMEDIATELY. . INHAL: REMOVE TO FRESH AIR. SUPPORT BREATH ING (GIVE O*2/ARTF RESP) .

Fire Fighting

Flash Point: NONE

Extinguishing Media: NONE SPECIFIED BY MANUFACTURER. Fire Fighting Procedures: NONE SPECIFIED BY MANUFACTURER. Unusual Fire/Explosion Hazard: NONE SPECIFIED BY MANUFACTURER.

Accidental Release

Spill Release Procedures: COLLECT SPILLED MATERIAL IN THE MOST CONVENIENT AND SAFE MANNER FOR RECLAMATION OR DISPOSAL. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: NORMAL HANDLING AND STORAGE. Other Precautions: NONE SPECIFIED BY MANUFACTURER.

Exposure Controls

Respiratory Protection: IF TLV IS EXCEEDED, USE ONLY NIOSH/MSHA APPROVED RESPIRATOR.

Ventilation: SUFFICIENT TO KEEP BELOW TLV LIMITS.

Protective Gloves: RUBBER GLOVES.

Eye Protection: CHEMICAL WORKERS GOGGLES. .

Other Protective Equipment: SUFFICIENT TO PREVENT SKIN CONTACT.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

HCC:C3

Boiling Pt:B.P. Text:212F,100C Vapor Pres: AS HOH

Vapor Density: AS HOH

Spec Gravity: 1.63

pH:3.9

Evaporation Rate & Reference: Solubility in Water: COMPLETE

Appearance and Odor: GREEN LIQUID, ODORLESS.

Percent Volatiles by Volume: 70

Stability

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products: NONE SPECIFIED BY MANUFACTURER.

Disposal

Waste Disposal Methods: PRECIPITATE NICKEL AS CARBONATE OR HYDROXIDE. RECLAIM OR DISPOSE OF IN AN EPA-APPROVED LAND FILL. FOLLOW ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever. expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.