

EPOXY COATING MIL-C-22750D #35044 PTB

MSDS Number

BLYZW

National Stock Number

8010-01-053-2657

Product Name

EPOXY COATING MIL-C-22750D #35044 PTB

Manufacturer

STEELCOTE MFG CO

Product Identification

Product ID:EPOXY COATING MIL-C-22750D #35044 PTB

MSDS Date:11/15/1991

FSC:8010

NIIN:01-053-2657

Kit Part:Y

MSDS Number: BLYZW

Responsible Party

STEELCOTE MFG CO

ONE STEELCOTE SQUARE

ST LOUIS , MO 63103

US

Emergency Phone: 800-424-9300 CHEMTREC

Info Phone: 314-771-8053

Cage: DO668

Contractor

STEELCOTE MFG CO

ST. LOUIS,, MO 63103

US

(314) 771-8053

Cage: DO668

Ingredients

POLYMERS OF EPOXY RESIN AND BISPHENOL A

CAS: 25036-25-3

Fraction By Weight: 25-30%

OSHA PEL5 MG/M3 (TOTAL DUST)

ACGIH TLV: 5 MG/M3 (TOTAL DUST)

1-METHOXY-2-PROPANOL (SARA 313) (VAPOR PRESSURE 12.50 MM HG

CAS: 107-98-2

RTECS: UB7700000

Fraction By Weight: 5-10%

ACGIH TLV: 100 PPM; 150 STEL

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 1-5%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

COPPER COMPOUNDS (SARA 313)

Fraction By Weight: 1-5%

CARBON BLACK

CAS: 1333-86-4

RTECS: FF5800000

Fraction By Weight: 1-5%

OSHA PEL3.5 MG/M3

ACGIH TLV: 3.5 MG/M3

TALC

CAS: 14807-96-6

RTECS: WW2710000

Fraction By Weight: 25-30%

OSHA PEL20 MPPCF

ACGIH TLV: 2 MG/M3; RESP. DUST

N-BUTYL ACETATE (VAPOR PRESSURE 10 MM HG @ 20 C) (LEL 1.38

CAS: 123-86-4

RTECS: AF7350000

Fraction By Weight: 1-5%

OSHA PEL150 PPM

ACGIH TLV: 150 PPM;200 PPM STEL

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

2-ETHOXYETHYL ACETATE (SARA 313) (VAPOR PRESSURE 2.00 MM HG

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 10-15%

OSHA PEL100 PPM, SKIN

ACGIH TLV: 5 PPM, SKIN

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 1-5%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

XYLENE (SARA 313) (VAPOR PRESSURE 6.60 MM HG @ 20 C) (LEL

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 1-5%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM;150 PPM STEL

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

2-BUTANONE /METHYL ETHYL KETONE (SARA 313) (VAPOR PRESSURE

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 5-10%

OSHA PEL200 PPM

ACGIH TLV: 200 PPM;300 PPM STEL

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

SANDING OR GRINDING DRIED FILM OF PRODUCT PRODUCES NUISANCE

RTECS: 9999999ZZ

OSHA PEL15MG/M3 TOTAL DUST*

ACGIH TLV: 10MG/M3 TOTAL DUST

ABSORPTION MAY CONTRIBUTE TO OVERALL EXPOSURE TO THIS

RTECS: 9999999ZZ

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:EYE: MODERATELY IRRITATE. SKIN:

MODERATELY IRRITATE. PROLONGED CONTACT: MAY DAMAGE-SKIN. ABSORP:

SYMPTOMS SAME AS DESCRIBED--INHALE/INGEST. DEFAT/DRY/DERMATITIS.

INHALE: IRRITATE: NOSE/ THROAT/RSPRTRY TRACT/MUSOUS MEMBRANE. CENT

NERV SYST DEPRESS/PERM BRAIN/ NERV SYST DAMAGE. INGEST: MODER

TOXIC. NERV SYST DAMAGE.

Explanation of Carcinogenicity:N/K ASPIRATION OF LIQUID INTO LUNGS

DURING INGESTION/VOMITING-SEVERE LUNG DAMAGE.

Effects of Overexposure:EYE: IRRITATE/PAIN/TEAR/SWELL. SKIN:

IRRITATE/RED/SWELL/RASH/RED. RSPRTRY: IRRITATE/RUNNY NOSE/SORE

THROAT/ COUGH/CHEST DISCOMFORT/SHORT BREATH/REDUCED LUNG FUNCTION.

GASTROINTESTINAL: IRRITATE/SORE T HROAT/ABDOMINAL

PAIN/NAUSEA/VOMIT/ DIARRHEA. CENT NERV SYST DEPRESS:

HEADACHE/DIZZY/NAUSEA/SYMPTS OF INTOXICATION/
Medical Cond Aggravated by Exposure:PREEXISTING SKIN/EYE RSPRTRY
DISORDERS. IMPAIRED CENTRAL NERVOUS SYSTEM FUNCTION.
UNCONSCIOUSNESS/DEATH. CHRONIC: LOSS OF MEMORY/LOSS OF INTELLECTUAL
ABILITY/LOSS OF COORDINATION.

First Aid

First Aid:EYE: FLUSH W/WATER FOR 15 MIN HOLD EYELIDS OPEN. IMMED MED
AID. SKIN: WIPE EXCESS OFF, WASH W/SOAP/WATER. MED AID IF IRRITATE
OCCURS. INHALE: GROSS OVEREXPOSURE TO NUISANCE DUST MAY CAUSE
IRRITATE TO RSPRTRY TRACT. INGEST: NO VOMIT. IF VOMIT OCCURS KEEP
HEAD BELOW HIPS, NO ASPIRATION INTO LUNGS. INDUCTION OF VOMITING
DECIDED BY DR. CONSULT A PHYSICIAN/HOSPITAL/POISON/CNTR/TRANSPORT
TO EMERG CNTR

Fire Fighting

Flash Point Method:TCC
Flash Point:20.0F,-6.7C
Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL, CARBON DIOXIDE.
Fire Fighting Procedures:WARNING: FLAMMABLE. CLEAR AREA OF UNPROTECT
PERSONNEL. DONT ENTER CONFINED FIRE SPACE W/O HELMET/FACE
SHIELD/BUNKER COAT/GLOVES/RUBBER BOOTS/POSITIVE PRESSURE
Unusual Fire/Explosion Hazard:COOL CNTNRS EXPOSED TO INTENSE HEAT
W/WTR-- PREVENT VAPOR PRESSURE BUILDUP/CNTNR RUPTURE. CNTNR AREAS
EXPOSED TO DIRECT FLAME CONTACT COOLED W/WTR PREVENT

Accidental Release

Spill Release Procedures:LGE SPILLS: NO UNPROTECT PEOPLE. APPROP
RSPRTR/PROTEC CLOTH. SHUT OFF LEAK IF SAFE. DIKE/CONTAIN. USE WTR
FOGTO SUPPRESS VAPOR CLOUD. CONTAIN RUN-OFF. RMOVE W/VACUUM
TRUCKS/PUMP--STORAGE/ SALVAGE VESS EL. SOAK UP RESIDUE W/ABORB
(CLAY/SAND/SUIT MAT'L)

Handling

Handling and Storage Precautions:KEEP LIQ/VAPOR FROM HEAT/SPARKS/FLAME.
NO PILOT LIGHTS/CIGARETTES/HOT SURFACES/SOURCES OF IGNITE UNTIL
VAPORS GONE. VAPORS MAY TRAVEL DISTANCES
Other Precautions:TO IGNITION SOURCES. CONTAINERS CLOSED WHEN NOT IN
USE. ADEQUATE VENT. CONTAINERS EVEN EMPTY CONTAIN EXPLOSIVE VAPORS,
NO CUT/DRILL/GRIND/WELD NEAR CONTAINERS.

Exposure Controls

Respiratory Protection:AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS-AT
LEAST 10 AIR CHANGES PER HOUR RECOMMENDED. IF EXPOSURE EXCEEDS
PEL/TLV, APPROPRIATE NIOSH/MSHA RESPIRATOR.
Protective Gloves:APPROPRIATE GLOVES PREVENT SKIN CONTACT
Eye Protection:SAFETY GLASSES/GOGGLES/SPLASH SHIELD
Other Protective Equipment:NO CONTACT LENSES. EYE WASH FOUNTAINS/SAFETY
SHOWERS AVAILABLE.
Work Hygienic Practices:WASH W/SOAP/WATER BEFORE
EATING/DRINKING/SMOKING/ USING TOILET. REMOVE/WASH CONTAMINATED
CLOTHING BEFORE REUSE.
Supplemental Safety and Health
KEY1;F5.PRODUCT IS PRESUMED TO BE FETOTOXIC. CHRONIC OVEREXPOSURE MAY
CAUSE INJURY TO KIDNEYS/LIVER/DAMAGE TO LUNGS. OVEREXPOSURE TO
DUST: SLIGHT LUNG FIBROSIS. OVEREXPOSURE TO SILICA DUST: TISSUE RES
PONSE (PNEUMONITIS). OVEREXPOSURE TO TALC DUST: SCARRING OF THE
LUNGS.

Chemical Properties

HCC:F5
Vapor Density:>1 (AIR=)
Spec Gravity:10.73
Evaporation Rate & Reference:Percent Volatiles by Volume:50.81

Stability

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS, STRONG ACIDS, ALKALI METAL HYDROXIDES, AMINES, POLYAMINES, POLYAMIDES UNDER UNCONTROLLED CONDITIONS
Stability Condition to Avoid:N/K NIOSH-APPROVED SCBA. WEAKENING OF CONTAINER STRUCTURE.

Hazardous Decomposition Products:ALDEHYDES AND ACIDS, CARBON DIOXIDE, CARBON MONOXIDE, UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

Disposal

Waste Disposal Methods:OBSERVE ALL LOCAL, STATE AND FEDERAL REGULATIONS REGARDING DISPOSAL.PUT IN NON-LEAK CNTNRS-DISPOSAL. FLUSH AREA W/WTR-- REMOVE RESIDUE. SMALL: TAKE UP W/ABSORB MAT'L/PUT IN NON-LEAKING CNTNRS/ SEAL TI GHTLY FOR PROPER DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.